# SUREFIT<sup>TM</sup> ACETATE VISOR 20CM UNBOUND

### PRODUCT CODE: ANX010-230-000

OFFERS PROTECTION AGAINST LOW ENERGY HIGH-SPEED PARTICLES AT 45M/S (101 MPH) & LIQUID DROPLETS

# **TECHNICAL SPECIFICATION**

**HEAD PROTECTION** 

**ACCESSORIES** 

# **INSTRUCTIONS FOR USE**

In use ensure that the faceshield fits comfortably and securely on the head

Ensure that a suitable visor has been fitted with the protective film removed from it

Ensure the visor is in place before entering the hazard area

# **DIMENSIONS OF VISOR**

Weight: 92g (Approx.)
Thickness: 1mm
Length: 200mm
Size: 530 - 620mm

# DIMENSIONS OF OUTER PACKAGING

Quantity: 50 Weight: 5.3kg (Approx.)



## **LIMITATIONS OF USE**

Protection will only be offered if the visor carrier and a visor are fitted correctly to a suitable Industrial Safety Helmet with the helmet attachment kit

If the visor becomes scratched or damaged they should be replaced, likewise if the visor is subjected to severe impact it should be replaced immediately

Do not apply paint, solvents, adhesives or self-adhesive labels, except in accordance with instructions from the manufacturer The visor, when in contact with the skin may cause allergic reactions to susceptible individuals

If this occurs leave the hazard area, remove the eyeshield and seek medical advice

The visor is not suitable for use with all chemicals - if you are unsure contact your supplier or JSP for help and advice

# CONFORMITY

Meets the requirements of EN 166

EC Type Examination Certificate Number 85724, issued by BSi Product Certification



**Clear Acetate** 

# **VISOR PERFORMANCE**

#### 20cm Acetate

Offers protection against low energy high-speed particles at 45m/s (101 mph) and liquid droplets

The optical qualities of the visor comply with the requirements of optical class 1 (highest)

Markings: EN166 1.F.3

# **CLEANING & MAINTENANCE**

The visor may be cleaned with soap and warm water and dried with a soft cloth

Do not clean with chemical or abrasive cleaners

The visor should be stored out of direct sunlight away from chemicals and extremes of temperature



MANUFACTURING FOR SAFETY WWW.JSP.CO.UK

UKSALES@JSP.CO.UK TEL: +44 (0)1993 826050