EVOLite®

ID HOLDER- WHEEL RATCHET - VENTILATED - CR2

TECHNICAL SPECIFICATION

THE JSP EVOLite® HELMET FEATURING THE NEW ID HOLDER ALLOWING EASY IDENTIFICATIONS OF PERSONNEL ON SITE

HEAD PROTECTION

SHELL:

High strength engineering grade ABS which has been UV

INSTRUCTIONS FOR USE

WEBBING HARNESS:

HDPE Strap & Webbing Clips

with Polyester Webbing Straps

Fit helmet on head and fasten strap to ensure fit

For adequate protection this helmet must be worn with peak facing forward

Ensure the helmet is adjusted to the size of the user's head



CHAMLON™ SWEATBAND:

Egyptian cotton core with porous PU coating for maximum sweat absorption. PH neutral, dermatologically tested



CR2 REFLECTIVE:

High Intensity Reflective offering, on average, 60% more reflectivity than standard reflective clothing material



ID HOLDER:

Fully waterproof card holder with easy visibility and quick interchanging of cards from the simple push and slide mechanism. Accommodate standard UK (85 x 55mm) and US (89 x 51mm) business cards



WHEEL RATCHET:

The Revolution® Wheel Ratchet RE is the new easy to use wheel ratchet adjustment system to create a firm comfort fit with added security





CR2 REFLECTIVE

EVOLite CR2 is the biggest step-up in night time visibility/ reflectivity of head protection to date

Meeting reflective performance requirements of EN12899-1 (High performance reflective sign face material)

CONFORMITY

EN 397 for Industrial Safety Helmets

EC Certificate Number 00279, issued by BSi Product Certification

Meets optional Lateral Deformation performance

Meets optional Molten Metal Splash performance

Wide size range. Slip or wheel ratchet - High comfort fit

Available vented. Available with mid or micro peak

Company personalisation available by printing

















UNSHLES@ISP.CU.UK TEL: +44 (0)1993 826050

ID HOLDER- WHEEL RATCHET - VENTILATED - CR2

TECHNICAL SPECIFICATION

THE JSP EVOLite® HELMET FEATURING THE NEW ID HOLDER ALLOWING EASY IDENTIFICATIONS OF PERSONNEL ON SITE

HEAD PROTECTION

DIMENSIONS OF OUTER PACKAGING

Quantity: 10

Weight: 4.1kg (Approx.)



DIMENSIONS OF HELMET

Size: 530 - 640mm

Weight: 363g (Approx.)

CLEANING & MAINTENANCE

The unit may be cleaned with soap and warm water and dried with a soft cloth

The helmet should not be cleaned with chemical or abrasive cleaners

The helmet should be stored out of direct sunlight

The helmet should be stored away from chemicals and extremes of temperature



HELMET COLOURS

















HEIGHT: 450mm

HELMET FEATURES

EN STANDARD	EN397 EN12899-1	Yes Yes
PERFORMANCE	Impact Resistance Lateral Deformation	Yes 50 Joules Yes
TEMPERATURE RESISTANCE	Molten Metal (MM) +50°C -30°C	Yes Yes Yes
SHELL MATERIAL	ABS Recyclable UV Stabilised	Yes Yes Yes
HARNESS MATERIAL	HDPE Textile	Yes Yes
OPTIONS	Universal Accessories Reflective CR2 option Integrated Eyewear ID Holder	Yes Yes Yes Yes
HARNESS SYSTEM OPTIONS	JSP 3D Slip Ratchet 6 pts	Yes Yes Yes
CHINSTRAP OPTIONS	4 pts 2 pts	Yes Yes
LOGO OPTIONS	Front Rear Side MOQ Logo Individual Name	Yes Yes Yes 10 Yes

LIMITATIONS OF USE

Protection will only be offered if the helmet is fitted correctly

Any helmet subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer

The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice

The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer



















