

# TECHNICAL SPECIFICATION

## EYE PROTECTION



## EVOGuard™ C1 Industrial Visor

EVOGuard™ C1 Industrial Visor / Code: ADA240-060-000



[Image Pack \(ZIP\)](#)

[Declaration of Conformity \(PDF\)](#)

### SAFETY STANDARDS

EN 166

EN 170

### SPECIFICATIONS



ULTRAVIOLET FILTER SCALE NUMBER  
2C-1.2



MANUFACTURERS TRADEMARK  
JSP Dagger



OPTICAL QUALITY (1=HIGH, 3=LOW)  
1



MEDIUM ENERGY IMPACT 120 M/S  
B when fitted to an EVO Helmet



MEDIUM ENERGY IMPACT 120 M/S  
B When Fitted to EVOGuard Browguard



FOR PROTECTION AT EXTREMES OF TEMPERATURE  
T



RESISTANCE TO LIQUID DROPLETS  
3



BSI KITEMARK  
Yes

MATERIAL  
Polycarbonate Shield



PRODUCT WEIGHT  
185g



RECYCLABLE  
Yes



KIT  
Supplied With: EVO 2,3,5,DS,Lite,Skyworker Arms.  
EVO8/EVOLite Badgeholder Arms. EVOGuard  
Browguard Mounting System

### FEATURES



#### Compatibility

EVOGuard™ visors maximise compatibility with JSP half masks, disposable respirators, prescription glasses and the Sonis® helmet mounted ear defender range.



#### Vision

The optical class 1 visor offers a panoramic view with minimal distortion, ideal for comfortable all day wear.



#### Impact

Five high performance visors offering up to A rated impact resistance when fitted to a safety helmet and fully compatible with EVOGuard™ browguard for medium energy impact protection.



#### Coverage

EVOGuard™ visors provide comprehensive facial coverage without limiting movement. EVOGuard™ MAX visors offer enhanced coverage with an integral chinguard.



JSP Limited. Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.  
Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com  
Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com.  
Information correct in the United Kingdom at date of issue and may be subject to change.  
Issued 1 Jun 2020 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.

