

Technical File

Art. 5280PG



DESCRIPTION

Cut resistant glove with excellent resistance to various mechanical risks while maintaining optimal dexterity and very good breathability.

CHARACTERISTICS

- seamless knitted HDPE fiber liner
- PU coated palm and fingers
- ventilated back
- elastic knit wrist
- gauge: 13
- colour: grey liner / grey PU coating

SIZES

Available in sizes 7 to 11

APPLICATIONS

In a dry environment presenting risks of cuts and other mechanical risks which can be found in sectors such as:

- industry
- transport
- assembly
- mechanical risk jobs
- logistics
- general purpose

MAINTENANCE - STORAGE

- heavily damaged gloves will affect level of protection and should be replaced
- in the original package in a well-ventilated area away from extreme temperatures

PRACTICAL INFORMATION

Sizes	Reference	Packing quantities
7	5280PG 07	All sizes individually packed in bundles of 12 and cartons of 120 pairs
8	5280PG 08	
9	5280PG 09	
10	5280PG 10	
11	5280PG 11	



CERTIFICATIONS



CAT II

in accordance with **EU Regulation 2016/425**
EN 420:2003+A1:2009 : dexterity level 5



EN388:2016

4 : abrasion resistance (0 to 4)

X : coup test cut resistance (0 to 5)

4 : tear resistance (0 to 4)

3 : puncture resistance (0 to 4)

D : cut resistance ISO 13997 (A to F)