

INFRA OVERCAP - FLEX S3 Réf. : 51103





Suitable for :	Inside/Outside
Туре :	Ankle shoe
Activity :	Oil and Gas / Chemical Industry / Welding, Foundry
Upper :	Water resistant full Nubuck leather, reflective strips on the sides and on the heel
Lining :	POROMAX® light grey color, printed "MTS"
Tongue :	Waterproof bellows tongue in black leather lined in POROMAX® light grey color, padded on 10mm thick
Ankle protection :	Black leather on 10mm thick foam, special rear reinforcement PU coated leather, abrasion resistant
Fastening :	Stainless eyelets, round polyamide/polyester black laces and YKK® zip on the interior side
Toe cap :	Ultralight and extra wide Composite toe cap 200 joules LIGHT SYSTEM®
Midsole :	Composite FLEX SYSTEM®, anti-magnetic and thermal insulated
Insole :	Foamed PU, anatomical, antistatic and anti bacterial
Sole :	PU/NITRILE HRO 300°C, antistatic, oil and acid resistant FO, HI-CI, with phosphorescent inserts
Sole pattern :	SRC, deep cleated, exceptional stability on oil platforms ground
Weight (Kg/pair) :	
Colors :	Black upper and dark grey/black outsole + orange inserts
Sizes :	38-48 (5-13)
Standard :	EN ISO 20345:2011 SRC
CE certificate of conformity N° :	0075/020/161/01/15/0035 - EXT 02/01/15
Special features :	
Special features 2 :	Overcap in TPU material, high shock and abrasion resistance
Special features 3 :	Fastening with zip on the interior side

SPECIAL FEATURES



Integral 100% composite (Air System + Light System + Flex System) Water absorption and

penetration resistance of upper (WRU)

Direct contact heat resistance of sole < 300° C (HRO)



G **GENERAL FEATURES** × Antistatic properties (A) Heel energy absorption (E) Abrasion resistance Crampon sole Heat-insulated sole (HI) Cold-insulated sole (CI) 200 joule extra-wide toecap Hyper-ventilated lining YSTER ÷... Perforation-resistance 1100 N (P)