



Fall Protection

Technical Data Sheet  
1150909

# 3M™ Protecta® Harness Extension Strap 1150909, Black

Part Number: 1150909

## Description


Sub-brand:	Protecta®
Industry:	Various
Applications:	Typically used with an Overhead Self-Retracting Lifeline

## Features

Harness Connection	
Type:	Delta Link Connector
Material - Finish:	Steel - zinc plated
Lanyard Connection	
Type:	Standard D-Ring
Material - Finish:	Steel - zinc plated
Webbing	
Material - Finish:	45mm Polyester - water & dirt resistant
Thread	
Material:	Polyester
Lanyard Parking Point:	Hook and loop end to attach to the shoulder
Effective Length:	40 cm
Net Weight :	220 g
Weight Capacity:	140 kg
Operating Temperature:	-35°C +57°C
Standards:	CE EN354:2010



1150909



Version: 1

This version is the sole document applicable to the product(s) since its date of publication

---

## Important Notice

The mounting and use of the product described within this document assumes that the user has previous experience of this type of product and that it will be assembled by a competent professional according to product documentation. Before any use of this product it is recommended to complete some trials to validate the performance of the product within its expected application.

All information and specification details contained within this document are inherent to this specific 3M product and would not be applied to other products or environment. Any action or usage of this product made in violation of this document is at the risk of the user.

Compliance to the information and specification relative to the product contained within this document does not exempt the user from compliance with additional guidelines (safety rules, procedures). Compliance to operational requirements especially in respect to the environment and usage of tools with this product must be observed. The 3M Group (who cannot verify or control these elements) would not be held responsible for the consequences of any violation of these rules which remain external to its decision and control.

Warranty conditions for products are determined with the sales contract documents and with the mandatory and applicable law, excluding any other warranty or compensation.



Fall Protection

Phone: +33 (0)4 83 58 08 08  
Email: [informationfallprotection@mmm.com](mailto:informationfallprotection@mmm.com)  
Web: [3M.com/FallProtection](http://3M.com/FallProtection)

### Registered Offices:

**Capital Safety (Northern Europe) Limited**  
3M Centre, Cain Road  
Bracknell, Berkshire, RG12 8HT, UK

**Capital Safety Group (EMEA)**  
Le Broc Center, Bâtiment A, Z.1. 1re Avenue  
– BP15, 06511 Carros Le Broc, Cedex, FRANCE