

Optrel b400 & b500 series



Technical data

Part No 3800079, 3800289, 3800071, 3800070

Product description Leather hoods with a passive filter (standard: DIN 11) inside.

Ideal for working in extremely restricted areas within fabricated constructions, cramped conditions, pipe work repairs aso.

 Part N°
 Type

 3800079
 b420 split leather

 3800289
 b430 split leather, flip-up

 3800071
 b520 top grain leather

 3800070
 b520 top grain leather, flip up

Window size 50 x 105 mm / 2" x 4 1/4"

Material Split grain leather for b420/430

and top grain leather for b520/530

Light transmittance Permanent ultraviolet- / infrared-protection

Shape stability Leather mask up to 250°C / 482°F

Leather colour white

Filters Shade level 8 until 12, depending on the welding

process and the amperage

Weight 260 g / 9.171 oz (b420/b520)

300 g / 10.582 oz (b430/b530))

Application ranges Electrode Welding (Stick Welding, SMAW): 10 – 300 Amp

MIG, heavy metals 80 – 300 Amp MIG, light metals 125 – 225 Amp

MAG 40 – 225 Amp TIG 1 – 225 Amp

prohibited for laser welding!

Spare parts Front cover lens / Filter shade DIN 8 – 12

Packaging Unit / box with 1 piece

Scope of delivery Leather mask, front cover lens, welding lens DIN 11 and instruction manual

Markings EN166

Subject to change without prior notice Status 2010-10-07 Optrel AG, Switzerland



