

Compatible safety products to protect your head, face, hearing, and vision



WE KNOW WHAT'S AT STAKE.



### Join the millions around the globe who choose MSA: For safety. For value.

This catalog highlights **MSA's comprehensive head, eye, face and hearing (HEFH) protection line**. Our hard hats, eye/face protection products, helmet accessories, hearing protection products—and more—provide seamless safety solutions to protect workers around the world. For a complete product listing, see the most recent MSA Safety Equipment Catalog, call our award-winning customer service department, or visit **MSAsafety.com**.

### **V-Gard® Hard Hats**



#### **MATTE FINISH**

Classification	Type I
Application	General purpose
Shell Material	Polyethylene
Styles	Slotted cap only
Sizes	<i>Cap-Style:</i> standard (6½ – 8")
Standards	ANSI/ISEA Z89.1-2014 (Class E); CSA Z94.1-2015 (Class E)
Certification	Third-party by SEI
Customization	Imprinting and striping available (see pages 6–7
Replacement Suspensi	ons See page 5





#### **DID YOU KNOW?**

All V-Gard Helmets have UV inhibitor molded right in.

CUSTOMIZATION: Imprinting and striping available—see pages 6–7 REPLACEMENT SUSPENSIONS: See page 5



#### DID YOU KNOW?

MSA helmets marked LT meet voluntary requirements for "Lower Temperature." Helmets marked LT are conditioned to -22°F and then tested for impact and penetration, as outlined in the Standard. Any helmet NOT marked with LT is tested to 0°F.



### V-Gard Cap-Style Hard Hats

STANDARD V-GARD SLOTTED CAPS						
Color		w/ Staz-On Suspension	w/ 1 Touch® Suspension <sup>1</sup>	w/ Fas-Trac III Suspension <sup>1</sup>		
GLOSS FINISH						
WHITE		463942	10057441	475358		
BLUE		463943	10057442	475359		
YELLOW		463944	10057443	475360		
ORANGE		463945	10057444	475361		
RED		463947	10057446	475363		
GREEN		463946	10057445	475362		
GRAY		463948	10057447	475364		
HI-VIZ <sup>®</sup> ORANGE <sup>2</sup>		488148	10057420	488146		
HI-VIZ YELLOW-GREEN <sup>2</sup>		-	10061514	10061512		
BRIGHT LIME GREEN		815558	_	815565		
DARK (CANADIAN) BLUE		-	—	802972		
GOLD		464852	_	475365		
ROBIN'S EGG BLUE		463111	—	495853		
BROWN		464658	_	495854		
SILVER		484340	_	495855		
TAN		461180	_	_		
BLACK		475235	_	492559		
LIGHT BUFF		478237	_	495856		
PURPLE		488398	_	495858		
PINK		-	_	495862		
HOT PINK		10155231	_	10155230		

STANDARD V-GARD SLOTTED CAPS					
Color	w/ Fas-Trac III Suspension <sup>1</sup>				
MATTE FINISH	MATTE FINISH				
WHITE	10203081				
BLUE	10203082				
YELLOW	10203083				
ORANGE	10203087				
RED	10203086				
GREEN	10203085				
GRAY	10203084				
HI-VIZ® ORANGE <sup>2</sup>	10203089				
HI-VIZ YELLOW <sup>2</sup>	10203088				
BLACK	10203092				

SMALL V-GARD SLO	TED	CAPS	
	Color	w/ Staz-On® Suspension	w/ Fas-Trac® III Suspension¹
GLOSS FINISH			
WHITE		466354	477477
BLUE		466355	477478
YELLOW		466356	477479
BRIGHT LIME GREEN		_	489368

STANDARD V-GARD CAP SPECIAL ASSEMBLIES					
Color	w/ Staz-On Suspension	w/1Touch Suspension <sup>1</sup>	w/ Fas-Trac III Suspension <sup>1</sup>		
GLOSS FINISH	·				
HI-VIZ ORANGE w/yellow-green stripe <sup>2</sup>	-	10102195	10102193		
HI-VIZ YELLOW-GREEN w/red-orange stripe <sup>2</sup>	-	10102234	10102233		
HI-VIZ YELLOW-GREEN w/silver stripe <sup>2</sup>	-	10102196	10102194		
WHITE w/lamp bracket and cord holder (Class C)	460018	-	-		
WHITE w/American Flag	474159	-	-		
WHITE w/Swing-Ratchet Suspension	10004689	-	-		



<sup>1</sup>Certified to CSA.

<sup>2</sup>V-Gard Cap/Hat meets voluntary standard for hi-visibility as prescribed by ANSI/ISEA Z89.1-2014. Look for official hi-visibility marking [HV] on the helmet's ANSI label.

### **V-Gard Full-Brim Hard Hats**

STANDARD V-GARD FULL-BRIM HATS					
Color	w/ Staz-On Suspension	w/ 1 Touch Suspension <sup>1</sup>	w/ Fas-Trac III Suspension <sup>1</sup>		
GLOSS FINISH					
WHITE	454733	10058321	475369		
BLUE	454732	10058320	475368		
YELLOW	454730	10058318	475366		
ORANGE	454734	10058322	496075		
RED	454736	10058324	475371		
GREEN	454735	10058323	475370		
GRAY	454731	10058319	475367		
HI-VIZ <sup>®</sup> ORANGE <sup>2</sup>	489360	10058326	10021292		
HI-VIZ YELLOW-GREEN <sup>2</sup>	-	10061516	10061515		
BRIGHT LIME GREEN	815562	_	815570		
DARK (CANADIAN) BLUE	-	_	802975		
HOT PINK	10156374	-	10156373		

STANDARD V-GARD FULL-BRIM HAT SPECIAL ASSEMBLIES						
Color w/ Staz-On w/ Fas-Trac III Suspension Suspension <sup>1</sup>						
GLOSS FINISH						
<b>WHITE</b> <i>w</i> /lamp bracket and cord holder (Class C)	460069	815009				



#### **DID YOU KNOW?**

**NFPA 70E** is a work practice; it is not a standard and does not specify any test methods. No products "meet" NFPA 70E—users simply follow the practice of NFPA 70E. For head protection, NFPA 70E recommends that users wear Class E hard hats in following this work practice.



<sup>1</sup>Certified to CSA.

<sup>2</sup>V-Gard Cap/Hat meets voluntary standard for hi-visibility as prescribed by ANSI/ISEA Z89.1-2014. Look for official hi-visibility marking [HV] on the helmet's ANSI label.



### **Replacement Suspensions for MSA Hard Hats**

### MSA Fas-Trac<sup>®</sup> III Ratchet Suspension

The MSA Fas-Trac III Suspension helps to reduce pressure headaches and pulled hair, and stays on your head.

- Sweatband fully covers headband and worker's forehead
- 2 Three levels of nape strap adjustment for customized fit
- **3** Lower nape strap improves retention
- Smooth ratchet rotation and secure hold

Learn how the Fas-Trac III Suspension can relieve your headaches. Visit **www.MSAsafety.com/fastrac.** 



	Suspension Type (4-point, unless otherwise noted)				
	Fas-Trac III	1 Touch	Staz-On	Swing Ratchet <sup>1</sup>	
HELMET TYPE (SIZE)	CO T		James Linne		
V-GARD CAP OR HAT (STANDARD)	10148708	10061123	10087218	816645	
V-GARD CAP (SMALL)	10148706	_	467386	—	
V-GARD CAP (LARGE)	10148707	_	492566	—	
V-GARD 500 CAP (STANDARD)	10148708	10061123	10087218	816645	
V-GARD 500 HAT (STANDARD)	10148708	—	10087218	-	
SMOOTHDOME CAP (STANDARD)	10148708	10061123	10087218	816645	
TOPGARD CAP OR HAT (STANDARD)	10153384	10061127	-	816648	
THERMALGARD CAP (STANDARD)	10153384	10061127	—	-	
SKULLGARD CAP OR HAT (STANDARD)	10153385	10061128	454231	816654	
SKULLGARD CAP (LARGE)	10126693	—	468096	—	
SUPER-V CAP (STANDARD)	10126683	—	—	_	
VANGUARD CAP (STANDARD)	10153386	_	-	-	
COMFO-CAP (STANDARD)	10153385	10061128	454231	_	

'Swing ratchet size is 6½" through 7%"

The Fas-Trac III Suspension sweatband accessory keeps workers cool and dry.

Part No.	Product Specifics
10153518	<ul> <li>•For use with MSA Fas-Trac<sup>®</sup> III Suspension</li> <li>•Optional, moisture-wicking and washable</li> <li>•Can be attached/replaced while suspension is assembled in helmet</li> <li>•Sold ONLY in packages of 10</li> </ul>

#### **A WARNING**

Use only the indicated MSA suspension in your MSA helmet. Do not mix suspension sizes and helmet sizes (i.e., putting a standard sized suspension in a large helmet or any other mismatched combination). Do not use competitor suspensions in MSA helmets. Inspect your suspension frequently. Suspensions should be replaced every 12 months, regardless of inspection results. Replace immediately (along with the helmet), if an impact has occurred. Failure to follow these instructions will reduce the energy absorbing ability of the protective helmet to receive impact, and could result in serious injury or death.

### Helmet Customization For 30+ Years



### Practice makes perfect logos

- MSA uses inks and processes that create durable logos. We have never had a complaint about a logo "scratching off" in the 30+ years we have been in the logo business!
- It can be tricky to avoid logo distortion due to the curvature of the hard hat. That's why MSA Logo Express® Service employs graphic designers who process logos onto hard hats. These skilled artisans ensure each logo is placed properly so it not only endures, but also accurately represents your brand and logo in color, size and shape-despite the curve of the hard hat.
- MSA offers multiple printing services from simple one-color logo to digital photos, in up to four locations
- We don't require "color-separated" artwork for 1+ color logos; nor do we require customers to identify the PMS colors in their logos. Our graphic artists can manage that, if you do not have these details.
- Re-ordering is easy because we keep your logo on file until you change it<sup>1</sup>.

## Our Process

Once your order has been received by the MSA Logo Express Service Design center we get to work. Files are imported from your on-line hard hat configuration, assessed for usability and colors separated (if the PMS colors have not been identified) and layout finalized. Should you choose to personalize your hard hat, don't forget to complete form ID# 0617-17 and submit with your order.



### Deliverv

Once the layout process is complete, our factory craftsman get to work on your order. Your order for a new hard hat logo should ship within eight (8) days from our Murrysville, PA plant from the date we receive your approval on the artwork<sup>2</sup>.



MSA requires MOQs, by hard hat type, for logoing and striping. Qualifying MOQs of custom-imprinted or striped hard hats must be of the same size, model and options (i.e., color and suspension). MOQs are:

- 20 for V-Gard, SmoothDome®, Topgard, Comfo Cap Hard Hats, and Nexus Climbing Helmets
- 16 for Skullgard or Thermalgard® Hard Hats
- 12 for Super-V and Vanguard Hard Hats
- 40 for Bump Caps



## Pricing

Please refer to your local distributor for pricing details on standard and non-standard charges that may apply to your order.



Add any of 27+ different reflective and retro-reflective stripes to your hard hat. MSA reflective stripes help enhance the visibility of workers in daytime conditions, while retro-reflective stripes<sup>3</sup> offer additional enhancement in nighttime or low-light conditions. Stripes are available in various sizes and shapes, and can be placed on all types of MSA hard hats.

Keep in mind too, that while you can order more stripes for self-application, MSA does not recommend doing this. The reason for this is MSA pre-treats all hard hats prior to striping with an electrical discharge treatment to enhance the ability of the stripes adhesive bonds.



### Stock Logos and Slogans

With 23 "pre-built" stock logos and slogans, MSA offers more "off-the-shelf" hard hat graphics than anyone in the industry. Standard logos make it easy for you to place emphasis on safety. patriotism or personnel identification without having to develop your own artwork. They can be can be used alone or with your customized logo and striping.



### Hard Hat Color Choices

MSA offers more stocked color options than competitors—in our popular V-Gard hard hat, we offer 21 stocked colors. There are non-stocked color options available for all MSA hard hats; a qualifying MOQ of 100 hard hats is required.

You can create a shell color of your choice. You need only order a qualifying MOQ of 500 hard hats or more.



### Personalization

The same quality and precision that MSA logos have become famous for is available with personalization. You can add your name, ID#, title, or anything else with this additional option.

<sup>1</sup> Files are purged from MSA's system if no logoed hard hat order is received within three (3) years of the first order. <sup>2</sup> Orders for repeat logos ship within seven (7) days. This includes 2-3 days for order processing, and 5 days for production.



### Placing Customized Hard Hat Orders

Steps to complete your online logo configuration order:

## Summary of how to submit artwork to MSA Logo Express Service

#### Please review the document for process details.

METHOD FOR SUBMITTING ARTWORK	Electronic file emailed to your MSA distributor
PROGRAMS FOR SUBMITTING ARTWORK	Corel Draw (version x6 or lower) Adobe Illustrator (version cs6 or lower) Adobe Photoshop (version cs6 or lower)
ARTWORK FILES	<b>VECTOR FILES:</b> .cdr ( <i>Corel Draw</i> ) .ai ( <i>Adobe Illustrator</i> ) .eps ( <i>encapsulated postscript</i> )
FONT REQUIREMENTS	<ul> <li>Convert all fonts to "outlines" (Adobe Illustrator) or "curves" (Corel Draw).</li> <li>Provide a list of actual fonts used with artwork file. Font type must be truetype and/or postscript type 1.</li> </ul>

#### Did you know?

If you **only** have other types of artwork, (e.g. printed copies of letterhead or business cards), please contact MSA Logo Express Service for submission instructions.

If you are personalizing your hard hat, please fill out form ID #0617-17-MC.



### The "Try-It" Sample Program

The "Try It" sample program offers some of the most popular MSA head, eye, face and hearing protection products, including V-Gard Helmets, V-Gard Accessories, left/RIGHT Hearing Protection, and Sightgard® Eyewear —completely FREE of charge! Look for the (m) that tells you which products are included in the program.



#### **Submitting Artwork**

- 1. Send the artwork by email to the MSA distributor taking your order. They will send it to MSA Logo Express Service.
- 2. Name the Pantone Matching System (PMS) ink colors used in your artwork (if you know them). Type the actualnumbers in the email, as colors sometimes don't transmit properly through email. For example, MSA's logo is green, but specifically, the color of our brand logo is PMS 355.
- 3. Provide all linked graphics and fonts (see "Font Submission")

Note: Should you not have access to email please contact MSA Logo Express for alternate methods.

#### Personalization

Add your name, ID#, title or anything else with this option. Fill out form ID# 0617-17-MC and submit with order. ONLY AVAILABLE FOR V-GARD LINE OF MSA HARD HATS.

#### **Font Submission**

Failure to specify or provide files for the typefaces used in your artwork is the most common source of delays and logo errors. If your artwork includes text, please be sure to:

- Convert type to outlines:
  - Adobe Illustrator (Type > Create Outlines)
  - Corel Draw (Convert to Curves using Ctrl+Q or Command+Q)
- Submit a list of all fonts used, along with the actual font files. All fonts should be TrueType and/or Postscript Type 1 formats.
- *NOTE:* Do not use Helvetica Narrow; it is unreliable and could complicate the printing process.



### Questions About Helmet Customization?

Contact your MSA distributor or MSA Logo Express Service.

EMAIL:	Logo.Express@msasafety.com
PHONE:	1-800-MSA-LOGO (1-800-672-5646)
ADDRESS:	MSA Logo Express 3880 Meadowbrook Rd. Murrysville, PA 15668-1753

Visit us on the web:

us.msasafety.com/logoexpress KEYWORD: Logo

### Freedom Series<sup>™</sup> and Specialty V-Gard Hard Hats

Classification	Туре I	Suspension	Fas-Trac III
Application	General purpose	Sizes	Standard (6½ – 8")
Shell Material	Polyethylene with thermoformed graphics	Standards	ANSI/ISEA Z89.1-2014 (Class E);
Styles	Slotted cap;		CSA Z94.1-2015 (Class E)
	Slotted full-brim hat (Freedom Series only)	Certification	Third-party by SEI



CUSTOMIZATION: Imprinting and striping available—see pages 6–7 REPLACEMENT SUSPENSIONS: See page 5

<sup>1</sup>Not pictured

<sup>2</sup>Extreme Hi-Viz Cap meets high-visibility requirements of ANSI/ISEA 107.



### Hydro Dip V-Gard Hard Hats

ClassificationType I	SizesStandard (6½ – 8")
ApplicationGeneral purpose	StandardsANSI/ISEA Z89.1-2014 (Class E);
Shell Material Polyethylene	CSA Z94.1-2015 (Class E)
StylesSlotted cap; Slotted full-brim hat	Certification Third-party by SEI
SuspensionFas-Trac III	

### The #1 Selling Hard Hat Has a New Look!

The features that have set the MSA V-Gard as a world leader in head protection remain: comfort, durability, customization, and support. The hydro dip finish provides a new twist on style, without sacrificing safety or performance. Choose from eight different standard looks, with the ability to customize to your specific design.\* All V-Gard hydro dip hard hats come with the first-in-class comfort of the Fas-Trac<sup>®</sup> III Suspension and are products of the U.S.

IYDRO DIP V-GARD ASSEMBLIES			
STANDARD CAP STYLES			
Muddy Girl V-Gard Slotted Cap Part No. <b>10204770</b>	One Nation <i>V-Gard Slotted Cap</i> Part No. <b>10204771</b>	Italian Leather <i>V-Gard Slotted Cap</i> Part No. <b>10204773</b>	Oilfield Camo <i>V-Gard Slotted Cap</i> Part No. <b>10204774</b>
Multi Camo <i>V-Gard Slotted Cap</i> Part No. <b>10204775</b>	Silver Carbon Fiber <i>V-Gard Slotted Cap</i> Part No. <b>10204776</b>	Sport Carbon Fiber V-Gard Slotted Cap Part No. <b>10204777</b>	Devil's Kanyon <i>V-Gard Slotted Cap</i> Part No. <b>10204778</b>
TANDARD FULL-BRIM HAT STYLES			
Muddy Girl <i>V-Gard Slotted Hat</i> Part No. <b>10204779</b>	One Nation V-Gard Slotted Hat Part No. <b>10204780</b>	Italian Leather <i>V-Gard Slotted Hat</i> Part No. <b>10204782</b>	Oilfield Camo V-Gard Slotted Hat Part No. <b>10204783</b>
Multi Camo V-Gard Slotted Hat	Silver Carbon Fiber V-Gard Slotted Hat Part No. <b>10204785</b>	Sport Carbon Fiber V-Gard Slotted Hat Part No. <b>10204786</b>	Devil's Kanyon <i>V-Gard Slotted Hat</i> Part No. <b>10204787</b>

### V-Gard 500 Hard Hats

Vented V-Gard 500 Caps and Hats provide cooling vents for improved air circulation and comfort; Non-Vented V-Gard 500 Caps and Hats provide dielectric head protection.

Classification	Type I
Application	General purpose
Shell Material	Polyethylene
Styles	Vented or non-vented slotted cap; Vented or non-vented hat
Sizes	Standard (6½ – 8")
Standards	ANSI/ISEA Z89.1-2014 (Vented Class C; Non-Vented Class E)
	CSA Z94.1-2015 (Vented Class C; Non-Vented Class E)
Certification	Third-party by SEI



Color	w/4-Point Fas-Trac III Suspension	w/6-Point Fas-Trac III Suspension	Color	w/4-Point Fas-Trac III Suspension	w/6-Point Fas-Trac III Suspension
VENTED CAP			<b>VENTED FULL-BRIM HAT</b>		
WHITE	10034018	10034027 🕅	WHITE	10167911	10167950 🕅
BLUE	10034019	10034028	BLUE	10167912	10167951 🕅 🕅
YELLOW	10034020	10034029 mm	YELLOW	10167913	10167952 🕅 🖷
RED	10034022	10034031 🕅 🖷	RED	10167915	10168437 🕅 🕅
GREEN	10034023	10034032 🕅 🖷	GREEN	10167916	10168438
HI-VIZ ORANGE <sup>1</sup>	10034026	10034035 🕅 🖷	HI-VIZ ORANGE <sup>1</sup>	10167921	10168453 🕅 🖷
HI-VIZ YELLOW-GREEN <sup>1</sup>	10074819	10074820 🕅 🕅	HI-VIZ YELLOW-GREEN <sup>1</sup>	10167931	10168461 🕅
NON-VENTED CAP		<u> </u>	NON-VENTED FULL-BRIM H	AT	Ŭ
WHITE	10034088	10034097	WHITE	10168521	10168589

CUSTOMIZATION: Imprinting and striping available—pages 6–7 REPLACEMENT SUSPENSIONS: See page 5

### **Topgard® Hard Hats**

Classification	Type I
Application	General purpose; elevated temperature <sup>2</sup>
Shell Material	Polycarbonate
Styles	Slotted cap; Non-slotted full-brim hat
Sizes	Standard (6½ – 8")
Standards	ANSI/ISEA Z89.1-2014 (Class E)
	CSA Z94.1-2015 (Class E)
Certification	Third-party by SEI



YELLOW     454721     475378       GRAY     454722     475379       BLUE     454723     475380       ORANGE     454725     475382       GREEN     454726     475383	Color	w/ 1 Touch Suspension	w/ Fas-Trac III Suspension
YELLOW     454721     475378       GRAY     454722     475379       BLUE     454723     475380       ORANGE     454725     475382       GREEN     454726     475383	TOPGARD SLOTTED CAP (STANDARD SIZE)		
GRAY     454722     475379       BLUE     454723     475380       ORANGE     454725     475382       GREEN     454726     475383	WHITE	454728	475385 🕅
BLUE         454723         475380           ORANGE         454725         475382           GREEN         454726         475383	YELLOW	454721	475378 🕅
ORANGE         454725         475382           GREEN         454726         475383	GRAY	454722	475379
GREEN 454726 475383	BLUE	454723	475380 🕅
	ORANGE	454725	475382
RED 454727 475384 (m	GREEN	454726	475383
	RED	454727	475384 mm
BRIGHT ORANGE – 804396	BRIGHT ORANGE	-	804396
WHITE W/LAMP BRACKET & CORD HOLDER -	WHITE W/LAMP BRACKET & CORD HOLDER		_

Cole	or	w/ 1 Touch Suspension	w/ Fas-Trac III Suspension
TOPGARD SLOTTER	) H/	AT (STANDARD SIZI	=)
WHITE		454719	475393 🕅
YELLOW		454712	475387 🕅
GRAY		454713	-
BRIGHT ORANGE		-	804397

#### **CUSTOMIZATION:** Imprinting and striping available—pages 6–7

**REPLACEMENT SUSPENSIONS:** See page 5

<sup>1</sup>V-Gard Cap/Hat meets voluntary standard for hi-visibility as prescribed by ANSI/ISEA Z89.1-2014. Look for official hi-visibility marking [HV] on the helmet's ANSI label. <sup>2</sup>Topgard Caps and Hats have been tested to radiant heat loads producing temperatures up to, but not exceeding, 275°F.



### **SmoothDome® Hard Hats**

Classification	Type I	
Shell Material		
Styles	Vented or non-vented slotted cap	
Sizes	Standard (6½ – 8")	
Standards	ANSI/ISEA Z89.1-2014 (Class E); CSA Z94.1-2015 (Class E)	
Certification	Third-party by SEI	
Certification	Third-party by SEI	

Color	w/4-Point Fas-Trac III Suspension	w/6-Point Fas-Trac III Suspension
SMOOTHDOME CAP (STANDARD SIZE)		
WHITE	10074067	10084078
BLUE	10074068	10084079
YELLOW	10074069	10084080
ORANGE	10074070	10084081
RED	10074071	10084082
GREEN	10074072	10084083
GRAY	10074073	10084084
HI-VIZ ORANGE <sup>1</sup>	10074077	10084088
HI-VIZ YELLOW-GREEN <sup>1</sup>	10074084	10084095
HI-VIZ ORANGE w/yellow-green stripe <sup>1</sup>	10095987	10095988
HI-VIZ YELLOW-GREEN w/orange stripe <sup>1</sup>	10095989	10095990
HI-VIZ ORANGE w/silver stripe <sup>1</sup>	10096141	-
HI-VIZ YELLOW-GREEN w/silver stripe <sup>1</sup>	10096142	_

**CUSTOMIZATION:** Imprinting and striping available—pages 6–7 **REPLACEMENT SUSPENSIONS:** See page 5

### Thermalgard® Hard Hats

	. General purpose; elevated temperature <sup>2</sup>	
Shell Material	. Glass-reinforced nylon	
Styles	. Slotted cap	
Sizes		1
Standards	. ANSI/ISEA Z89.1-2014 (Class G); CSA Z94.1-2015 (Class G)	
Certification	. Third-party by SEI	



Color	w/ 1 Touch Suspension	w/ Fas-Trac III Suspension
THERMALGARD CAPS (STANDARD SIZE)		
YELLOW	486964	486959
WHITE	486965	486960
RED	-	486961
ORANGE	486967	486962
BLUE	486968	486963
BRIGHT ORANGE	800359	800360
GREEN	487399	814343
STEEL GRAY	-	10095325
	-	

**CUSTOMIZATION:** Imprinting and striping available—pages 6–7 **REPLACEMENT SUSPENSIONS:** See page 5

V-Gard Cap/Hat meets voluntary standard for hi-visibility as prescribed by ANSI/ISEA Z89.1-2014. Look for official hi-visibility marking [HV] on the helmet's ANSI label. <sup>2</sup>Thermalgard Caps and Hats have been tested to radiant heat loads producing temperatures up to, but not exceeding, 350°F.

### **Skullgard® Hard Hats**

Classification	Type I
Application	General purpose; elevated temperature <sup>1</sup>
Shell Material	Phenolic
Styles	Non-slotted cap; full-brim hat
Sizes	<b>Cap:</b> Standard (6½ – 8"); Small (6 – 7½"); Large (7 – 8½")
	Hat: Standard (6½ – 8")
Standards	ANSI/ISEA Z89.1-2014 (Class G)
Certification	Third-party by SEI



Color	w/ Staz-On Suspension	w/ Fas-Trac III Suspension	w/ Swing-Ratchet Suspension	
SKULLGARD CAP (STAN	DARD SIZE)			
NATURAL TAN	454617	475395	816651	
WHITE	454618	475396	_	
YELLOW	454619	475397	—	
RED	454620	-	-	
GREEN	454621	_	_	
GRAY	454622	-	-	
BLUE	454623	-	-	
ORANGE	454626	-	-	
HI-VIZ RED-ORANGE <sup>2</sup>	458702	-	-	
SKULLGARD HAT (STANDARD SIZE)				
NATURAL TAN	454664	475407	—	
WHITE	454665	475408	-	
YELLOW	454666	-	-	
GREEN	454668	_	_	
ORANGE	454673	_	_	

	w/ Staz-On Suspension	w/ Fas-Trac III Suspension	
<b>ALTERNATIVE SK</b>	ULLGARD ASS	SEMBLIES	
SKULLGARD	82018	475405	Large size, natural tan
CAP	-	10104377	Small size, natural tan
	460409	-	Standard size, with lamp bracket and cord holder, natural tan <sup>3</sup>
	-	482002	With welder's lugs, natural tan <sup>3</sup>
SKULLGARD HAT	460389	-	Standard size, with lamp bracket and cord holder, natural tan <sup>3</sup>

#### CUSTOMIZATION: Imprinting and striping available—pages 6–7 REPLACEMENT SUSPENSIONS: See page 5

### Super V<sup>®</sup> Hard Hats

Classification	Type II (ANSI and CSA)
Application	Lateral protection
Shell Material	Polyethylene
Styles	Slotted cap w/foam liner
Sizes	Standard (6½ – 7¾")
Standards	ANSI/ISEA Z89.1-2014 (Class E); CSA Z94.1-2015 (Class E)
Certification	Third-party by SEI



Colo	w/Fas-Trac III Suspensi	on	
SUPER V ASSEMBLIES			
WHITE	C217091	TT VAT	
YELLOW	C217093	וח אשר	
RED	C217095	0	
ORANGE	C217094		
BLUE	C217092		
NAVY GRAY	C217097		
HI-VIZ ORANGE <sup>2</sup>	C217100		

**CUSTOMIZATION:** Imprinting and striping available—pages 6–7

Col	or	w/Fas-Trac III Suspension
SUPER V ASSEMBLIES		
GREEN		C217096
GOLD		C217098
BLACK		C217140
SILVER		10025227

#### **A WARNING**

Use only MSA's Fas-Trac III Suspension designed for Super-V Helmets. Use of any other suspension will reduce the energy-absorbing ability of the protective helmet, which can result in serious personal injury or death.

#### **REPLACEMENT SUSPENSIONS:** See page 5

<sup>1</sup>Skullgard caps and hats have been tested to radiant heat loads producing temperatures up to, but not exceeding, 350°F. <sup>2</sup> Hi-Viz red-orange Skullgard Cap meets voluntary standard for hi-visibility as prescribed by ANSI/ISEA Z89.1-2014. Look for official hi-visibility marking [HV] on the helmet's ANSI label. <sup>3</sup>Alternative Skullgard Assemblies that include welder's lugs or lamp bracket and cord holder are certified to Class C electrical rating.



### **V-Gard H1 Safety Helmets**

The V-Gard H1 Safety Helmet and accessories provide exceptional comfort and ease of use in a stylish low-profile design. A complete above-theneck platform for all applications.

- Fas-Trac® III Pivot ratchet suspension for superior comfort, adjustability and range of motion
- Non-contact foam liner maximizes air flow & breathability for **optimal cooling and hygiene**
- Vented options for **optimal air flow and cooling**
- Field replaceable 4-point chinstrap with multiple adjustment points for customized fit and comfort
- Premium sweatband with sweat-wicking fabric, breathable foam and Velcro® attachment for easy field replacement
- Patented "push-button" accessory attachment rail and universal lighting clips for quick installation and removal
- Convenient rescue whistle integrated into the chin strap buckle

Classification	The Safety Company
Shell Material       HDPE (high-densitypolyethylene)         Styles       Trivent; no vent         Sizes       Standard 6½ - 8" (52-64 cm) head circumference	V-Gard H1 Safety Helmet
Standards See chart on page 14 CUSTOMIZATION: Stylish dark gray reflective striping standard. Imprinting available—see pages 6–7	with vents
ACCESSORIES: See page 14	V-Gard HI Safety Helmet without vents

Color	TRIVENT w/ pivoting Fas-Trac III Suspension	NO VENT w/ pivoting Fas-Trac III Suspension		
V-GARD H1 SAFETY HELMET ASSEMBLIES				
WHITE	10194783	10194791		
RED	10194784	10194792		
BLUE	10194785	10194793		
GREEN	10194786	10194794		
YELLOW	10194787	10194795		
HI-VIZ YELLOW GREEN	10194788	10194796		
ORANGE	10194789	10194797		
BLACK	10194790	10194798		
GRAY	10204346	10204347		

V-GARD HI SAFETY HELMETS: STANDARDS				
STANDARD	Aspect	TRIVENT	NO VENT	
ANSI/ISEA Z89.1-2014	Class C (Conductive 0 V ac)			
TYPE 1	Class E (20,000 V ac)			
	-22° F (-30° C) (Lower Temperature)			
	$140^{\circ}F \pm 3.6^{\circ}F (60^{\circ}C \pm 2^{\circ}C) (Higher Temperature)$			
EN 12492:2012 MOUNTAINEERING STANDARD	_			
EN 397:2012 + A1:2012	-22° F (-30° C) (Lower Temperature)			
	440 V ac (Electrical Resistance)			
EN 50365:2002 (1000V A.C.) FOR USE ON LOW VOLTAGE INSULATIONS	_			

V-GARD III	V-UARD HI SAFEI Y HELMEI ACCESSURIES				
Part No.	Product Name	Color	Product Specifics	Approvals	
10194818	V-Gard H1 Clear Face Shield	Clear	<ul> <li>Clear polycarbonate contoured visor for closer fit and optimal resistance to impact and splash hazards</li> <li>Simple push button donning and doffing on the V-Gard H1 Safety Helmet—no additional frames or adapters required</li> <li>Dual pivot hinge maintains a low profile to the helmet when stowed for improved balance and wind resistance</li> <li>Frameless design with anti-fog and anti-scratch coatings for greater visibility</li> </ul>	• ANSI/ISEA Z87.1-2015 • CSA Z94.3 • EN 166	
10194819	V-Gard H1 Mesh/ Forestry Face Shield	Mesh	<ul> <li>Steel mesh contoured visor for closer fit and optimal protection from flying chips and other light debris</li> <li>Simple push button donning and doffing on the V-Gard H1 Safety Helmet—no additional frames or adapters required</li> <li>Dual pivot hinge maintains a low profile to the helmet when stowed for improved balance and wind resistance</li> </ul>	• ANSI/ISEA Z87.1-2015 • EN 1731	
10194820	V-Gard H1 Half-Face Spectacles	Clear	<ul> <li>Clear polycarbonate contoured spectacles for closer fit and optimal resistance to impact and splash hazards</li> <li>Simple push button donning and doffing on the V-Gard H1 Safety helmet—no additional frames or adapters required</li> <li>Dual pivot hinge maintains a low profile to the helmet when stowed for improved balance and wind resistance</li> <li>Frameless design with anti-fog and anti-scratch coatings for greater visibility</li> </ul>	• ANSI/ISEA Z87.1-2015 • CSA Z94.3 • EN 166	
10217333	V-Gard H1 Shaded Half-Face Spectacles	Shaded	<ul> <li>Smoke-shaded polycarbonate contoured spectacles for closer fit and improved resistance to impact and splash hazards</li> <li>Simple push button donning and doffing on the V-Gard H1 Safety Helmet—no additional frames or adapters required</li> <li>Dual pivot hinge maintains a low profile to the helmet when stowed for improved field of vision and wind resistance</li> <li>Frameless design coupled with anti-fog &amp; anti-scratch coatings improve visibility</li> </ul>	• ANSI/ISEA Z87.1-2020 • CSA Z94.3 • EN 166	

Part No.	V-Gard H1 Replacemenet Parts	
10194760	/-Gard H1 Replacement Suspension Assembly, Fas-Trac III Pivot	
10194761	V-Gard H1 Replacement Sweatband, Fas-Trac III Pivot, 3-pack	
10194765	V-Gard H1 Replacement Chin Strap, Trivent	
10194766	V-Gard H1 Replacement Chin Strap, Novent/Bivent	



### **Comfo-Cap® Hard Hats**

Classification	Type I
Application	Mining
Shell Material	Polycarbonate
Styles	Non-slotted cap w/ lamp bracket & cord holder
Sizes	.Standard (6½ – 8")
Standards	ANSI/ISEA Z89.1-2014 (Class G)
Certification	Third-party by SEI



Color	w/ Staz-On Suspension	w/ Fas-Trac III Suspension				
COMFO CAP ASSEMBLIES						
WHITE	91522	475336				
BLUE	91586	—				
YELLOW	91585	-				
ORANGE	91589	—				
RED	91590	—				
GREEN	91584	—				
BLACK	82769	_				

CUSTOMIZATION: Imprinting and striping available—pages 6–7 REPLACEMENT SUSPENSIONS: See page 5

### **Bump Caps**

Classification	Non
Application	Non-impact
Shell Material	Polyethylene
Styles	Non-slotted cap w/ plastic suspension
Sizes	Standard (6½ – 8")
Standards	Not applicable
Certification	None

Color	w/ Plastic Suspension			
BUMP CAP ASSEMBLIES				
WHITE	10033652			
BLUE	10033650			
YELLOW	10033651			
ORANGE	10033654			
RED	10033653			
GREEN	10033655			



#### **A WARNING**

Bump caps are not safety helmets and do not meet OSHA or ANSI/ISEA Z89.1 requirements. DO NOT use bumps caps for impact protection, for sports or when an ANSI-compliant helmet is required.

#### CUSTOMIZATION:

Imprinting and striping available (locations limited)

### V-Gard Accessory System: V-Gard Frames for Cap-Style Hard Hats

V-GARD U	ARD UNIVERSAL CAP FRAME					
Part No.	Debris Control		Produc	t Specifics		
10187161	With debris control	Easy to Use • Add and remove ac • Quicker visor install removal • Green color coded p	essories <sup>1</sup> • [ ation and	educing Complexity Designed to work with all MSA /-Gard cap-style hard hats		
		Built to Last • Infinity joints • Universal strap • Debris control				
10187162	Without debris control	Easy to Use • Add and remove ac • Quicker visor install removal • Green color coded p	essories <sup>1</sup> • [ ation and	educing Complexity Designed to work with all MSA /-Gard cap-style hard hats		
		<ul><li>Built to Last</li><li>Infinity joints</li><li>Universal strap</li></ul>				
Part No.	Product Specifics		Part No.	Product Specifics		
10187163	Replacement d	Replacement debris wiper		Replacement rubber strap		

#### **V-GARD FRAMES FOR GENERAL PURPOSES**

Markets: General industry, manufacturing, repair and maintenance, construction, oil and gas, forestry, shipbuilding, metalworking, automotive, mining Applications: Chipping, splash, chiseling, drilling, grinding, machining, power fastening, sanding, sawing

Standards<sup>2</sup>: ANSI/ISEA Z87.1-2015; CSA Z94.3; EN 166; AS/NZS 1337 Certification: Third-party by Intertek, INSPEC International Ltd., CSA International and SAI Global Ltd. Min Order Qty: 10

Part No.	Material	Debris Control	Product Specifics			
10115730	High density polyethylene (HDPE)	Includes replaceable debris control which creates tight seal between frame and cap	<ul> <li>Fits all MSA Slotted Caps</li> <li>Stowable slot adaptors secure frame tightly in slotted MSA caps, and allow frame to work with or without earmuffs<sup>3</sup></li> <li>Sliding adjustment bladesallow visor to work with most half-mask respirators and other PPE worn under a visor</li> </ul>			
10121266	High density polyethylene (HDPE)	Debris control sold separately	<ul> <li>Fits all MSA Slotted Caps<sup>4</sup></li> <li>Stowable slot adaptors secure frame tightly in slotted MSA caps, and allow frame to work with or without earmuffs<sup>3</sup></li> <li>Sliding adjustment blades allow visor to work with most half-mask respirators and other PPE worn under a visor</li> </ul>	L Xess		
	A WARNING					

Use V-Gard Frames ONLY with V-Gard Visors, to ensure compliance with safety standards. Misuse can result in death, permanent impairment of sight, or other serious injury.

IMSA does not recommend the use of the V-Gard Universal Frame with the MSA SmoothDome when using cap-mounted muffs and large V-Gard molded Visors. The V-Gard Frame for Slotted Caps should be worn with this particular combination.

<sup>2</sup>Standards requirements met by each V-Gard Frame/V-Gard Visor combination designated on each V-Gard Visor.

<sup>3</sup>Patent pending

MSA recommends the use of debris control on V-Gard frames when wearing BOTH large V-Gard molded Visors and cap-mounted earmuffs.



### V-Gard Accessory System: V-Gard Frames for Cap-Style Hard Hats

#### **V-GARD FRAMES FOR ELEVATED TEMPERATURE APPLICATIONS**

**Markets:** Food manufacturing/canneries, steel mills, construction, open-pit mining, agriculture, oil/gas/petrochemical refineries, rubber manufacturing, and steam tunnels

Applications: Food processing, machine operation, maintenance, millwright, cutting, punching, extrusion, drilling, blasting, casting/conveying,

chemical mixing, sanding

Features: Tested to withstand temperatures of 350°F (176.7°C), reducing warping, cracking or crazing Standards<sup>1</sup>: ANSI/ISEA Z87.1-2015; CSA Z94.3; EN 166; AS/NZS 1337 Certification: Third-party by Intertek, INSPEC International Ltd., CSA International and SAI Global Ltd.

Min Order Qty: 10

Part No.	Material	Debris Control	Product Specifics	
10115821	Polycarbonate — all non-metal construction	Replaceable debris control tested against EN 166 hot solids requirements	•Stowable slot adaptors secure frame tightly in slotted MSA caps, and allow frame to work with or without earmuffs <sup>2</sup> •Sliding adjustment blades allow visor to work with most half-mask respirators and other PPE worn under a visor	
10121267	Polycarbonate — all non-metal construction	Debris control sold separately <sup>3</sup>	<ul> <li>Stowable slot adaptors secure frame tightly in slotted MSA caps, and allow frame to work with or without earmuffs</li> <li>Sliding adjustment blades allow visor to work with most half-mask respirators and other PPE worn under a visor</li> </ul>	
10116552	Polycarbonate — all non-metal construction	Replaceable debris control tested against EN 166 hot solids requirements	<ul> <li>Heavy duty flat rubber strap allows easy and secure placement on all MSA caps, including non-slotted models<sup>4</sup></li> <li>Design allows use with other PPE, including MSA earmuffs and respirators</li> </ul>	

### V-Gard Accessory System: V-Gard Frames for Full-Brim Hard Hats

#### **V-GARD FRAMES FOR GENERAL PURPOSES**

Markets: General industry, manufacturing, repair and maintenance, construction, oil and gas, forestry, shipbuilding, metalworking, automotive, mining Applications: Chipping, splash, chiseling, drilling, grinding, machining, power fastening, sanding, sawing Standards<sup>1</sup>: ANSI/ISEA Z87.1-2015; CSA Z94.3; EN 166; AS/NZS 1337 Certification: Third-party by Intertek, INSPEC International Ltd., CSA International and SAI Global Ltd. Min Order Qty: 10

Part No.	Material	Debris Control	Product Specifics	
10116627	High density polyethylene (HDPE)	Offered without debris control ONLY	<ul> <li>Heavy duty flat rubber strap allows easy and secure placement on all MSA hats, including non-slotted models</li> <li>Design allows use with other PPE, including MSA earmuffs and respirators</li> <li>Fits MSA Full-Brim Safety Helmets</li> </ul>	

#### **V-GARD FRAMES FOR ELEVATED TEMPERATURE APPLICATIONS**

**Markets:** Food manufacturing/canneries, steel mills, construction, open-pit mining, agriculture, oil/gas/petrochemical refineries,

rubber manufacturing, and steam tunnels Applications: Food processing, machine operation, maintenance,

millwright, cutting, punching, extrusion, drilling, blasting, casting/conveying,

chemical mixing, sanding

**Features:** Tested to withstand temperatures of 350°F (176.7°C), reducing warping, cracking or crazing

Standards<sup>1</sup>: ANSI/ISEA Z87.1-2015; CSA Z94.3; EN 166; and AS/NZS 1337 Certification: Third-party by Intertek, INSPEC International Ltd., CSA International and SAI Global Ltd.

Min Order Qty: 10

Part No.	Material	Debris Control	Product Specifics	
10116628	Polycarbonate — all non-metal construction	Offered without debris control ONLY	<ul> <li>Heavy duty flat rubber strap allows easy and secure placement on all MSA hats, including non-slotted models</li> <li>Design allows use with other PPE, including MSA earmuffs and respirators</li> <li>Fits MSA Full-Brim Safety Helmets</li> </ul>	

<sup>1</sup>Standards requirements met by each V-Gard Frame/V-Gard Visor combination designated on each V-Gard Visor. <sup>2</sup>Patent pending

<sup>3</sup>MSA recommends the use of debris control on V-Gard frames when wearing BOTH large V-Gard molded Visors and cap-mounted earmuffs.

<sup>4</sup>MSA does not recommend the use of the V-Gard Universal Frame with the MSA SmoothDome when using cap-mounted muffs and large V-Gard molded Visors. The V-Gard Frame for Slotted Caps should be worn with this particular combination.

### V-Gard Accessory System: V-Gard Frames for MSA Slotted Full-Brim Hard Hats

#### **V-GARD FRAMES FOR GENERAL PURPOSES**

**Markets:** Oil, gas & petrochemical, manufacturing, repair and maintenance, construction, general industry, forestry, shipbuilding, metalworking, automotive, mining

Applications: Chipping, splash, chiseling, drilling, grinding, machining, power fastening, sanding, sawing

Standards<sup>1</sup>: ANSI/ISEA Z87.1-2015 and CSA Z94.3 Certification/Testing: CSA International and Intertek Min Order Qty: 10

Part No.	Material	Debris Control	Product Specifics	
10154622	Polybutylene terephthalate (PBT)	Sold with replaceable debris control which creates tight seal between frame and hat	<ul> <li>Fits MSA Slotted Full Brim Hats</li> <li>Sliding adjustment blades allow visor to work with most half-mask respirators and other PPE worn under a visor</li> <li>Patented Infini-just allows lift/closure adjustment using grippable knobs that can't be lost <sup>2</sup></li> </ul>	
10154604	Polybutylene terephthalate (PBT)	Debris control sold separately	<ul> <li>Fits MSA Slotted Full Brim Hats</li> <li>Sliding adjustment blades allow visor to work with most half-mask respirators and other PPE worn under a visor</li> <li>Patented Infini-just allows lift/closure adjustment using grippable knobs that can't be lost <sup>2</sup></li> </ul>	
10116628	All rubber construction	Exceeds EN requirements for molten metal	Debris Control	

### V-Gard Accessory System: V-Gard Metal Frames for Hard Hats

#### V-GARD FRAMES FOR GENERAL PURPOSES AND ELEVATED TEMPERATURE APPLICATIONS

Markets: Manufacturing; construction; steel/smelting operations Applications: Machine operation, maintenance, millwright, extrusion, drilling, blasting, casting/conveying Standards<sup>1</sup>: ANSI/ISEA Z87.1-2015; CSA Z94.3 Certification: Third-party by Intertek, CSA International (as marked)

Part No.	Material	Product Specifics	
10158799	Heavy-duty anodized aluminum	<ul> <li>For use with MSA cap-style hard hats</li> <li>Spring coil for fast loading of frame to helmet</li> <li>Three visor resting positions</li> <li>Locking device holds visor securely in the down position</li> </ul>	
10158800	Heavy-duty anodized aluminum	<ul> <li>For use with MSA Skullgard cap-style hard hats</li> <li>Spring coil for fast loading of frame to helmet</li> <li>Three visor resting positions</li> <li>Locking device holds visor securely in the down position</li> </ul>	
10176739	Heavy-duty anodized aluminum	<ul> <li>For use with MSA full-brim hard hats</li> <li>Spring coil for fast loading of frame to helmet</li> <li>Three visor resting positions</li> <li>Locking device holds visor securely in the down position</li> </ul>	

#### **A WARNING**

MSA does not recommend V-Gard Metal Frames for use where electrical hazards, including but not limited to arc flash, could occur.

<sup>1</sup>Standards requirements met by each V-Gard Frame/V-Gard Visor combination designated on each V-Gard Visor. <sup>2</sup>Patent pending



V-GARD VI	SORS: GENERAL PURI	POSE		
constructior automotive, <b>Application</b>	i, oil and gas, forestry, shi mining	uring, repair and maintenance, pbuilding, metalworking, ling, drilling, grinding, machining,	Standards <sup>1</sup> : ANSI/ISEA Z87.1-2015; CSA Z9 1337 (except as noted) Certification: Third-party by Intertek, INS CSA International and SAI Global Ltd. Min Order Qty: 10	
	Product Specifics			
Part No.	Impact-rated (Z87+) w	vith Maximum UV Protection		
10144486	<b>Material</b> Polycarbonate — clear	<ul> <li>5" (14.61 cm) x 17" (43.2 cm) x .04" (1.0</li> <li>Contoured visor; closer fit and improv</li> <li>Approved to ANSI and CSA<sup>2</sup> standards</li> <li>Nitrometer; for use with V-Gard Retraction</li> </ul>	ed resistance to impact and splash hazards ;; does not meet EN standards	
10115836	<b>Material</b> Polycarbonate — clear	<ul> <li>8" (20.3 cm) x 17" (43.2 cm) x .04" (1.</li> <li>Contoured visor; closer fit and improv</li> </ul>	02 mm) ed resistance to impact and splash hazards	Comments of Contraction of Contraction
10115837	<b>Material</b> Polycarbonate — clear	<ul> <li>8" (20.3 cm) x 17" (43.2 cm) x .04" (1.</li> <li>Contoured visor; closer fit and improv</li> <li>Nitrometer; for use with V-Gard Retrained</li> </ul>	ed resistance to impact and splash hazards	
10120108	<b>Material</b> Polycarbonate — clear	<ul> <li>8" (20.3 cm) x 17" (43.2 cm) x .04" (1.</li> <li>Bulk pack of 20</li> <li>Contoured visor; closer fit and improv</li> </ul>	02 mm) ed resistance to impact and splash hazards	
10115863	<b>Material</b> Polycarbonate — clear	<ul> <li>9.5" (24.1 cm) x 17" (43.2 cm) x .04" (</li> <li>Contoured visor; closer fit and improv</li> </ul>	1.02 mm) ed resistance to impact and splash hazards	
10115839	Material Polycarbonate with antifog/anti-scratch coatings for humid conditions — clear	<ul> <li>8" (20.3 cm) x 17" (43.2 cm) x .06" (1.</li> <li>Slightly thicker for industrial impact ar splash hazards</li> <li>Contoured visor; closer fit and improv</li> </ul>		
10115841	Material Polycarbonate with antifog/anti-scratch coatings for humid conditions — clear	<ul> <li>8" (20.3 cm) x 17" (43.2 cm) x .06" (1.</li> <li>Slightly thicker for industrial impact ap splash hazards</li> <li>Contoured visor; closer fit and improv</li> <li>Nitrometer; for use with V-Gard Retraction</li> </ul>	oplications resistance to impact and ed resistance to impact and splash hazards	
10115842	Material Polycarbonate with antifog/anti-scratch coatings for humid conditions — green tint to reduce glare	<ul> <li>8" (20.3 cm) x 17" (43.2 cm) x .06" (1.</li> <li>Slightly thicker for industrial impact ar splash hazards</li> <li>Contoured visor; closer fit and improv</li> <li>Not for use where a Shade infrared</li> </ul>	oplications resistance to impact and ed resistance to impact and splash hazards	

<sup>1</sup>Standards requirements met by each V-Gard Frame or Headgear/V-Gard Visor combination designated on each V-Gard Visor.

#### **V-GARD VISORS: GENERAL PURPOSE** Markets: General industry, manufacturing, repair and maintenance, Standards1: ANSI/ISEA Z87.1-2015; CSA Z94.3 and EN 166 (2C-1.2 MSA 1B); AS/NZS

construction, oil and gas, forestry, shipbuilding, metalworking, automotive, mining

Applications: Chipping, splash, chiseling, drilling, grinding, machining, power fastening, sanding, sawing

1337 (except as noted) Certification: Third-party by Intertek, INSPEC International Ltd., CSA International and SAI Global Ltd.

Min Order Qtv: 10

Part No.	Product Specifics				
Part NO.	Impact-rated (Z87+) with Maximum UV Protection				
10115840	<b>Material</b> Polycarbonate — clear	<ul> <li>8" (20.3 cm) x 17" (43.2 cm) x .06" (1.52 mm)</li> <li>Slightly thicker for industrial impact applications resistance to impact and splash hazards</li> <li>Contoured visor; closer fit and improved resistance to impact and splash hazards</li> </ul>			
10117783	<b>Material</b> Polycarbonate — clear	<ul> <li>8" (20.3 cm) x 17" (43.2 cm) x .06" (1.52 mm)</li> <li>Slightly thicker for industrial impact applications resistance to impact and splash hazards</li> <li>Wider design; improved resistance to impact and splash hazards</li> <li>Does not meet CSA Z94.3</li> <li>Flat Nitrometer; for use with V-Gard Retractable or Standard Chin Protectors</li> </ul>			

#### V-GARD VISORS: GENERAL PURPOSE (NON-IMPACT)

Markets: General industry, manufacturing, repair and maintenance, construction, oil and gas, forestry, shipbuilding, metalworking, automotive, mining

Standards1: ANSI/ISEA Z87.1-2015; EN 1731-F; and AS/NZS 1337 Certification: Third-party by Intertek, INSPEC International Ltd., and SAI Global Ltd. Min Order Qty: 10

Applications: Flying chips and other light debris

Devis Me	Product Specifics					
Part No.	General Protector (Z8	7) — NOT FOR IMPACT HAZARDS				
10115840	Material Epoxy-coated steel mesh (20 x 20) — black, plastic edged	<ul> <li>•8" (20.3 cm) x 17" (43.2 cm)</li> <li>•Not for use against splash, impact, elevated temperatures or UV hazards</li> <li>• Can be worn with earmuffs</li> </ul>				
10117783	<b>Material</b> Epoxy-coated steel mesh (20 x 20) — black, plastic edged	<ul> <li>•8" (20.3 cm) x 17" (43.2 cm)</li> <li>•Not for use against splash, impact, elevated temperatures or UV hazards</li> <li>• Can be worn with earmuffs</li> <li>Nitrometer; for use with V-Gard Retractable or Standard Chin Protectors</li> </ul>				
10115837	Material Epoxy-coated steel mesh (20 x 20) — aluminum-bound mesh	<ul> <li>•8" (20.3 cm) x 16.5" (41.9 cm)</li> <li>•Not for use against splash, impact, electrical or UV hazards</li> </ul>				

'Standards requirements met by each V-Gard Frame or Headgear/V-Gard Visor combination designated on each V-Gard Visor.



#### V-GARD VISORS: HEAVY-DUTY CHEMICAL AND SPLASH

Markets: General industry, heavy manufacturing, laboratories, chem/petrochemical, agriculture, pharmaceutical, oil and gas, mining Applications: Chipping, splash, chemical mixing, grinding, machining, power fastening, sanding, sawing Standards': ANSI/ISEA Z87.1-2015; EN 166 (MSA 1B 3); CSA Z94.3 and AS/NZS 1337 Certification: Third-party by Intertek, INSPEC International Ltd., CSA International and SAI Global Ltd. Min Order Qty: 5

Part No.	Product Specifics					
Part NO.	Impact-rated (Z87+)					
10115855	<b>Material</b> Propionate — clear	<ul> <li>•8" (20.3 cm) x 17" (43.2 cm) x .098" (2.5mm)</li> <li>•Extra-thick to help prevent warping, cracking or crazing under tough conditions</li> <li>•Please refer to MSA's <i>Chemical Application Quick Reference Guide</i> (ID 0670-007-MC) for chemical performance details</li> </ul>				
10115856	<b>Material</b> Propionate — clear	<ul> <li>•8" (20.3 cm) x 17" (43.2 cm) x .098" (2.5mm)</li> <li>•Extra-thick to help prevent warping, cracking or crazing under tough conditions</li> <li><b>Mitrometer; for use with V-Gard Retractable or Standard Chin Protectors</b></li> <li>•Please refer to MSA's <i>Chemical Application Quick Reference Guide</i> (ID 0670-007-MC) for chemical performance details</li> </ul>				
10115851	<b>Material</b> Propionate — clear	<ul> <li>9.25" (23.5 cm) x 18" (45.7 cm) x .098" (2.5mm)</li> <li>Extra-thick to help prevent warping, cracking or crazing under tough conditions</li> <li>Extended length and width for greater coverage of neck and face</li> <li>Please refer to MSA's <i>Chemical Application Quick Reference Guide</i> (ID 0670-007-MC) for chemical performance details</li> </ul>				

NOTE: V-Gard propionate Visors offer both chemical resistance and impact protection, unlike most propionate visors on the market. Not only are they marked with Z87+, but the clear visors are also compliant with EN166, meaning they were tested at a velocity nearly 32% faster than ANSI/ISEA Z87.1-2010.

#### V-GARD VISORS: ELEVATED TEMPERATURE WITH HIGH-PERFORMANCE ANTI-FOG/ANTI-SCRATCH COATINGS

**Markets:** Food manufacturing/canneries, steel mills, construction, open-pit mining, agriculture, oil/gas/petrochemical refineries, rubber manufacturing, steam tunnels **Applications:** Hot/humid conditions, chipping, splash, chiseling, drilling, grinding, machining, power fastening, sanding, sawing, outdoor work

Standards': ANSI/ISEA Z87.1-2015; EN 166 (2C-1.2 MSA IBT9KN); CSA Z94.3 and AS/NZS 1337

Certification: Third-party by Intertek, INSPEC International Ltd.,

CSA International and SAI Global Ltd.

Min Order Qty: 5

Part No. 10115853	Product Specifics					
	Impact-rated (Z87+) with Maximum UV Protection					
	Material Polycarbonate with EN 166 performance-rated anti-fog/ anti-scratch coatings for hot/humid conditions (N,K marks, respectively) — clear	<ul> <li>•10.375" (26.4 cm) x 17" (43.2 cm) x .098" (2.5 mm)</li> <li>•Molded visor for superior optics under heavy-duty use</li> <li>•Extended length for greater coverage of neck/face</li> <li>•Performs well against many chemicals. Refer to MSA's <i>Chemical Application Quick Reference Guide</i> (ID 0670-007-MC) for details</li> </ul>				
10115854	Material Polycarbonate with EN 166 performance-rated anti-fog/ anti-scratch coatings for hot/humid conditions (N,K marks, respectively) — green tint to reduce glare	<ul> <li>•10.375" (26.4 cm) x 17" (43.2 cm) x .098" (2.5 mm)</li> <li>•Molded visor for superior optics under heavy-duty use</li> <li>•Extended length for greater coverage of neck/face</li> <li>◆ Not for use where a Shade infrared (IR) visor is required</li> </ul>				

<sup>1</sup>Standards requirements met by each V-Gard Frame or Headgear/V-Gard Visor combination designated on each V-Gard Visor.

#### V-GARD VISORS: ELEVATED TEMPERATURE

Droduct Spacifics

**Markets:** Food manufacturing/canneries, steel mills, construction, open pit mining, agriculture, oil/gas/petrochemical refineries, rubber manufacturing, steam tunnels **Applications:** Food processing, machine operation, maintenance, millwright, cutting, punching, extrusion, drilling, blasting, casting/conveying, chemical mixing, sanding

Standards': ANSI/ISEA Z87.1-2015; EN 166 (2C-1.2 MSA IBT89KN); CSA Z94.3 and AS/NZS 1337 Certification: Third-party by Intertek, INSPEC International Ltd., CSA International and SAI Global Ltd. Min Order Qty: 5

Devit Ma	riouut specifics					
Part No.	Impact-rated (Z87+) with Maximum UV Protection					
10115844	Material Polycarbonate with EN 166 performance-rated anti-fog/anti-scratch coatings for hot/humid conditions (N,K marks, respectively) — clear	<ul> <li>9.25" (23.5 cm) x 17" (43.2 cm) x .098" (2.5mm)</li> <li>Molded visor for superior optics under heavy-duty use</li> <li>Extra-thick visor helps prevent warping, cracking or crazing</li> <li>Conditioned to a high of 131° F (and a low of -23° F) and then tested to the medium impact rating in the EN166 standard (higher impact speed than ANSI/ISEA Z87.1-2010)</li> <li>Visors do not reflect IR; not recommended for use against radiant heat hazards</li> </ul>				
10115845	Material Polycarbonate with EN 166 performance-rated anti-fog/anti-scratch coatings for hot/humid conditions (N,K marks, respectively) — green tint to reduce glare	<ul> <li>9.25" (23.5 cm) x 17" (43.2 cm) x .098" (2.5mm)</li> <li>Molded visor for superior optics under heavy-duty use</li> <li>Extra-thick visor helps prevent warping, cracking or crazing</li> <li>Conditioned to a high of 131° F (and a low of -23° F) and then tested to the medium impact rating in the EN166 standard (higher impact speed than ANSI/ISEA Z87.1-2010)</li> <li>Visors do not reflect IR; not recommended for use against radiant heat hazards</li> <li>Not for use where a Shade infrared (IR) visor is required</li> </ul>				

NOTE: V-Gard molded, green and clear visors offer superior optical quality and resistance to many chemicals. For details on optics, please refer to the MSA White Paper, "Optical Quality Requirements and V-Gard® Visors" (ID 0302-32 MC) available for download from MSA's Asset Library.

#### **V-GARD VISORS: RADIANT HEAT/ELEVATED TEMPERATURE**

**Markets:** Metal industries, glass manufacturing, iron and steel foundries, chemical manufacturing, construction, general manufacturing, textile manufacturing, mining, oil and gas

**Applications:** Grinding, pouring, casting, blowing/melting, rolling, sawing, cutting, crimping, millwrighting, machining/operating, pipelining, pulping

Standards<sup>1</sup>: ANSI/ISEA Z87.1-2015; EN 166 (2C-2.5 MSA 1BT3R [clear] and 2-4 MSA 1BT3R [green tint]); CSA Z94.3 and AS/NZS 1337 Certification: Third-party by Intertek, INSPEC International Ltd., CSA International and SAI Global Ltd. Min Order Qty: 5

Part No.	Product Specifics					
Part No.	Impact-rated (Z87+) with Maximum UV Protection					
10115848	Material Polycarbonate with EN 166 performance-rated anti-fog/anti-scratch coatings for hot/humid conditions (N,K marks, respectively) — clear	<ul> <li>9.5" (24.1 cm) x 17.75" (45.09 cm) x .07" (1.8 mm)</li> <li>Reflective coating reflects IR and helps dissipate heat: reflects &gt;60% Infrared (IR) radiation (EN166 R mark) in the 780nm to 2000nm wavelength</li> <li>Thick visor helps prevent warping, cracking or crazing</li> <li>Extended length for greater coverage of face and neck; DO NOT use for welding</li> </ul>				
10115850	Material Polycarbonate with EN 166 performance-rated anti-fog/anti-scratch coatings for hot/humid conditions (N,K marks, respectively)—– green tint to reduce glare	<ul> <li>9.5" (24.1 cm) x 17.75" (45.09 cm) x .07" (1.8 mm)</li> <li>Reflective coating reflects IR and helps dissipate heat: reflects &gt;60% Infrared (IR) radiation (EN166 R mark) in the 780nm to 2000nm wavelength</li> <li>Thick visor helps prevent warping, cracking or crazing</li> <li>Extended length for greater coverage of face and neck; DO NOT use for welding</li> <li>Not for use where a Shade infrared (IR) visor is required</li> </ul>				

<sup>1</sup>Standards requirements met by each V-Gard Frame or Headgear/V-Gard Visor combination designated on each V-Gard Visor.

Radiant Heat Resistance Simplified" (ID 0670-023 MC), available on MSAsafety.com.



V-GARD VISORS: WELDING (SHADE 3 AND SHADE 5)

T OARD T				
Markets: Fabrication, steel mills, shipbuilding, construction, open-pit mining, agriculture, oil/gas/petrochemical refineries, rubber manufacturing Applications: Welding, metal pouring, gas soldering, light cutting/brazing, manufacturing, impact and debris			Standards <sup>1</sup> : ANSI/ISEA Z87.1-2015; EN 166 (4-3 4-5/5 MSA 1BT39 [shade 5]); CSA Z94.3 and A: Certification: Third-party by Intertek, INSPEC I CSA International and SAI Global Ltd. Min Order Qty: 5	S/NZS 1337
Dart No	Product Specifics			
Part No.	Impact-rated (Z87+)			
10115859	Material Polycarbonate — Shade 3 IR	• 8" (20.3 cm) x 17" (43.2 cm) x .07" (1.8 mm)     • Thickness helps prevent pitting and warping from heat or weld spatter		
10115860	Material Polycarbonate —	• 8" (20.3 cm) x 17" (43.2 cm) x .07" (1.8 mm) •Thickness helps prevent pitting and warping from heat or weld spatter		

	Polycarbonate — Shade 3 IR	<ul> <li>a (20.3 cm) x17 (43.2 cm) x17 (1.8 mm)</li> <li>Thickness helps prevent pitting and warping from heat or weld spatter</li> <li>Nitrometer; for use with V-Gard Retractable or Standard Chin Protectors</li> </ul>	
10115861	<b>Material</b> Polycarbonate — Shade 5 IR	• 8" (20.3 cm) x 17" (43.2 cm) x .07" (1.8 mm) •Thickness helps prevent pitting and warping from heat or weld spatter	
10115862	<b>Material</b> Polycarbonate — Shade 5 IR	<ul> <li>8" (20.3 cm) x 17" (43.2 cm) x .07" (1.8 mm)</li> <li>Thickness helps prevent pitting and warping from heat or weld spatter</li> <li>Nitrometer; for use with V-Gard Retractable or Standard Chin Protectors</li> </ul>	

#### V-GARD VISORS: ARC FLASH APPLICATION<sup>2</sup>

**Markets:** Manufacturing, utilities, construction, oil/gas/ petrochemical **Applications:** Maintenance, impact and debris, testing/repair

Standards<sup>1</sup>: ANSI/ISEA Z87.1-2015; ASTM F2178-2008 (Ref: NFPA 70E, HRC 2) Certification: Third-party by Intertek and ArcWear Min Order Qty: 5

Dest No	Product Specifics					
Part No.	Impact-rated (Z87+)					
10115847	Material Polycarbonate — special tint, gray-blue visor; molded	<ul> <li>9.25" (23.5 cm) x 18" (45.7 cm) x .065" (1.7 cm)</li> <li>Extended length and width for greater coverage of face and neck</li> <li>Rated to 16.0 cal/cm<sup>2</sup> when tested to ASTM F2178-2008 (ref. NFPA 70E-2015 PPE Category 2), and when worn with a V-Gard Hard Hat (PN 475358) and V-Gard Frame (PN 10115730)</li> <li>Call MSA Customer Service (800-MSA-2222) for protection levels when using this V-Gard Arc Visor with other V-Gard Frames and MSA Helmet combinations</li> </ul>				
10118480	Material Polycarbonate — special tint, gray-blue visor; molded (for use with designated V-Gard Chin Protector)	<ul> <li>Arc Visor Kit—consists of Visor (PN 10115858) + Chin Protector (PN 10115827)</li> <li>8" (20.3 cm) x 17.25" (43.8 cm) x .065" (1.7 cm)</li> <li>Extended length and width for greater coverage of face and neck</li> <li>Rated to 21.0 cal/cm<sup>2</sup> when tested to ASTM F2178-2008 (ref. NFPA 70E-2015 PPE Category 2), and when worn with a V-Gard Hard Hat (PN 475369) and V-Gard Frame (PN 10116627) and V-Gard Standard Chin Protector (PN/10115827)</li> <li>Call MSA Customer Service (800-MSA-2222) for protection levels when using this V-Gard Arc Visor with other V-Gard Frames and MSA Helmet combinations</li> </ul>				

Standards requirements met by each V-Gard Frame or Headgear/V-Gard Visor combination designated on each V-Gard Visor.

<sup>2</sup> Do not use V-Gard Arc Visors with V-Gard Headgear. These visors are designated for use with specified V-Gard Frames and MSA helmets ONLY. See "V-Gard Headgear" for additional details.

### V-Gard Accessory System: V-Gard Headgear

V-Gard Headgear can be used for face protection when head protection is not required. V-Gard Headgear is available in two versions: General Purpose and Elevated Temperature (Extended). V-Gard Headgear are designed and approved for use with V-Gard Visors.<sup>1</sup>

#### **V-GARD HEADGEAR**

**Markets:** General industry, manufacturing, repair and maintenance, construction, oil and gas, forestry, shipbuilding, metalworking, automotive, mining, chemical industries

**Size:** Standard (6½ – 8)

Sandards<sup>2</sup>: ANSI/ISEA Z87.1-2015; EN 166; CSA Z94.3; and AS/NZS 1337 Certification: Third-party by Intertek, INSPEC International Ltd., CSA International and SAI Global Ltd.

**Applications:** Chipping, splash, chiseling, drilling, grinding, machining, power fastening, sanding, sawing, laboratory

Part No.	Product Name	Product Specifics	
10127061	V-Gard Headgear — General Purpose Material: High Density Polyethylene (HDE) – black	<ul> <li>Patent-pending, Infini-just lift/closure with grippable knobs that don't unscrew; no parts to lose</li> <li>Ratchet closure</li> <li>Seven-point crown adjustment</li> <li>Replaceable, sweat-wicking, cushioned headband helps keep workers dry and cool</li> <li>Sweat-wicking ratchet cover keeps nape comfortable</li> <li>For use ONLY with V-Gard Visors; not for use where head protection is required</li> <li>All non-metal construction</li> <li>Minumum order quantity: 10</li> </ul>	
10127062	V-Gard Headgear — Elevated Temperature Material: Heat-resistant nylon — gray	<ul> <li>Extended browguard for additional coverage in high temperatures</li> <li>Tested to withstand temperatures up to 400 °F<sup>3</sup></li> <li>Patent-pending, Infini-just lift/closure with grippable knobs that don't unscrew; no parts to lose</li> <li>Ratchet closure</li> <li>Seven-point crown adjustment</li> <li>Replaceable, sweat-wicking, cushioned headband helps keep workers dry and cool</li> <li>Sweat-wicking ratchet cover keeps nape comfortable</li> <li>For use ONLY with V-Gard Visors; not for use where head protection is required</li> <li>All non-metal construction</li> <li>Minumum order quantity: 5</li> </ul>	
10127063	V-Gard Headgear Kit — General Purpose	<i>Kit Contains:</i> • V-Gard General Purpose Headgear (PN 10127061) • V-Gard Clear, PC Visor, 8" (20.3 cm) x 17" (43.2 cm) x .04" (1.02 mm) (PN 10115836)	
10127065	V-Gard Headgear Replacement Sweatband <sup>4</sup>	<ul> <li>Sweat-wicking material over breathable foam helps keep workers cool, dry and comfortable</li> <li>Hook &amp; loop closure makes replacement easy</li> <li>Tested to the FR requirements in CSA Z94.3-07</li> <li>Sold in boxes of 25 (5 packages of 5)</li> </ul>	

**DO NOT** use V-Gard Headgear with V-Gard Arc Visors tested to ASTM F2178-2008 Test Method (ref. NFPA 70E-2012, Hazard Risk Category). These visors are designated for use with specified V-Gard Frames and MSA helmet ONLY as face protection for workers exposed to high voltage electric arcs. V-Gard Headgear has not been tested or certified to the Test Method, and should not be used for this type of Arc Flash protection.

<sup>2</sup> Standards requirements met by each V-Gard Frame or Headgear/V-Gard Visor combination designated on each V-Gard Visor.

<sup>3</sup> Exposure to extreme heat can cause thermal discomfort. Proper precautions should be taken to prevent heat stress and other injuries.

<sup>4</sup> Use only genuine MSA V-Gard Headgear replacement parts to help ensure compatibility and compliance. MSA does not warrant, guarantee or promote the use of components manufactured by other companies when used in conjunction with MSA products.



### V-Gard Accessory System: V-Gard Chin Protectors<sup>1</sup>

Work with select V-Gard Nitrometer Visors to provide extra protection from impact and splash hazards to face and neck.

V-GARD CI	V-GARD CHIN PROTECTORS							
Part No.	Product Name	Material	Product Specifics					
10115828	Retractable Chin Protector	Polycarbonate – opaque (ensures safety and standards compliance with clear, tinted, shaded and coated V-Gard Visors)	<ul> <li>3.82" (9.7 cm) in height, when unretracted</li> <li>Unique retractable plates allow greater flexibility of head movement both up and down, as well as side-to-side</li> <li>Minimum order quantity: 5</li> </ul>					
10149029	Chin Protector	Polycarbonate – clear (for improved visibility)	<ul> <li>2.86" (7.26 cm) in height</li> <li>Compact, lightweight design provides additional protection between chin and neck area</li> <li>Should not be worn with tinted, arc or shaded nitrometer visors to ensure compliance with stated Standards markings/requirements</li> <li>Minimum order quantity: 5</li> </ul>					
10115827	Standard Chin Protector	Polycarbonate – opaque (ensures safety and standards compliance with clear, tinted, shaded and coated V-Gard Visors)	<ul> <li>2.86" (7.26 cm) in height</li> <li>Compact, lightweight design provides additional protection between chin and neck area</li> <li>Minimum order quantity: 5</li> </ul>	Max				

### V-Gard Accessory System: Replacement Parts<sup>2</sup>

V-GARD A	V-GARD ACCESSORY SYSTEM REPLACEMENT PARTS						
Part No.	Product Name	Product Specifics					
10117496	Slot Adpaters (2 pair)	<ul> <li>For use with V-Gard Frames for Slotted Caps</li> <li>Sold in boxes of 10 (5 packages of 2)</li> </ul>					
10116539	Debris Control for V-Gard Frames	<ul> <li>Debris control exceeds EN requirements for molten metal</li> <li>All-rubber construction</li> <li>Minimum order quantity: 10</li> </ul>					
10117495	Heavy-duty Rubber Strap	<ul> <li>For V-Gard Universal Cap or Hat Frames</li> <li>Minimum order quantity: 10</li> </ul>					

<sup>1</sup> MSA V-Gard Chin Protectors meet the applicable safety requirements as noted on the V-Gard Nitrometer Visor when worn in conjunction with V-Gard Frames and V-Gard Nitrometer Visors. <sup>2</sup> Use only genuine MSA V-Gard Accessory System replacement parts to help ensure compatibility and compliance. MSA does not warrant, guarantee, or promote the use of components manufactured by other companies when used in conjunction with MSA products.

### V-Gard Accessory System: Kits

V-GARD A	CCESSORY SYSTEM I	KITS	
Part No.	Product Name	Product Specifics	
10118695	V-Gard Accessory System Kit — with V-Gard Cap-Style Hard Hat	<ul> <li><i>Kit Contains:</i></li> <li>White V-Gard Cap with ratchet suspension (PN 475358)</li> <li>V-Gard Frame for Slotted Caps; with debris control (PN 10115730)</li> <li>V-Gard Clear, Polycarbonate Visor, 8" (20.3 cm) x 17" (43.2 cm) x .04" (1.02 mm) (PN 10115836)</li> </ul>	
10118697	V-Gard Accessory System Kit — without V-Gard Cap-Style Hard Hat	<ul> <li>Kit Contains:</li> <li>V-Gard Universal Frame for Caps with debris control (PN 10115822)</li> <li>V-Gard Clear, Polycarbonate Visor, 8" (20.3 cm) x 17" (43.2 cm) x .04" (1.02 mm) (PN 10115836)</li> <li>Does not contain an MSA safety helmet.</li> </ul>	
10118694	V-Gard Forestry Kit	<ul> <li><i>Kit Contains:</i></li> <li>Hi-Viz orange V-Gard Cap with ratchet suspension (PN 488146)</li> <li>V-Gard Frame for Slotted Caps; with debris control (PN 10115730)</li> <li>V-Gard Mesh Nitrometer (PN 10116558)</li> <li>V-Gard Retractable Chin Protector (PN 10115828)</li> <li>left/RIGHT, HIGH (NRR 28 db) Cap-Mounted Earmuffs (PN 10087422)</li> </ul>	
10118696 <sup>1</sup>	V-Gard Accessory Arc Kit	<ul> <li><i>Kit Contains:</i></li> <li>White V-Gard Cap with ratchet suspension (PN 475358)</li> <li>V-Gard Frame for Slotted Caps (PN 10121266)</li> <li>V-Gard Arc Nitrometer with V-Gard Standard Chin Protector (PN 10118480); must be assembled by user prior to wearing to secure stated calorie rating.</li> <li>Rated to 11.3 cal/cm<sup>2</sup> when tested to ASTM F2178-2008 (ref. NFPA 70E-2012, Hazard Risk Category 2), and when worn with a V-Gard Cap (PN 475358), V-Gard Frame (PN 10121266) and V-Gard Standard Chin Protector (PN/10115827)</li> </ul>	

<sup>1</sup> Call MSA Customer Service (800-MSA-2222) for protection levels when using this V-Gard Arc Visor with other V-Gard Frames, V-Gard Chin Protectors and MSA Helmet combinations.



### **Hard Hat Accessories**

### V-Gard Winter Liners

V-Gard Winter Liners deliver extra warmth and protection under hard hats.

Part No.	Product Name	Product Specifics	
0118417	V-Gard Winter Liner, Knit Cap	<ul> <li>Stylish skullie cap</li> <li>Design prevents liner from obstructing vision</li> <li>100% high bulk acrylic</li> <li>Sold in sets of 12</li> </ul>	
0118418	V-Gard Winter Liner, Knit Hat/Cap Cover	<ul> <li>100% acrylic</li> <li>Bright yellow-green for greater visibility</li> <li>Full face tube mounts under or over brim of MSA caps or hats, covering ears, mouth, cheeks and neck</li> <li>Extended nape and wraparound collar for tucking into coat/shirt</li> <li>Sold in sets of 12</li> </ul>	
0118427	V-Gard Supreme Liner, Flame-Resistant 2-piece	<ul> <li>Fabric tested to withstand arc exposure to an ATPV of 8 cal/cm<sup>2</sup></li> <li>Water repellant</li> <li>Inside neck pocket holds warming packet<sup>2</sup></li> <li>Multi-layered flame-resistant top cap</li> <li>Extended, zipper on/off high-bulk flame-resistant knit bottom</li> <li>No metal parts</li> <li>Sold in sets of 3</li> </ul>	

FR protection throughout the life of the product.<sup>3</sup> For this reason, only V-Gard Supreme Liner offers resistance to arc exposure.

<sup>1</sup>Follow all instructions and perform daily, pre-, and post-use inspections.

<sup>2</sup> Warming packets available at most sporting goods retailers; not sold with liners.

<sup>3</sup> Garment care instructions must be followed.

### **Hard Hat Accessories**

UNIVERSA	L 4-POINT CHINSTRA	
Part No.	Product Name	
GA90047	Universal 4-Point Chinstrap	

STANDAR	CHINSTRAPS		
Part No.	Product Name	Product Specifics	
<b>10171103</b> <sup>1</sup>	2-Point Chinstrap	<ul> <li>Non-metal chinstraps keep helmets in place</li> <li>Flexible construction and adjustable design for long-wearing comfort</li> <li>¾" Nomex webbing</li> <li>Attaches to shell</li> </ul>	
10171104	2-Point Chinstrap	<ul> <li>Non-metal chinstraps keep helmets in place</li> <li>Flexible construction and adjustable design for long-wearing comfort</li> <li><sup>3</sup>/<sub>4</sub>" polyester webbing</li> <li>Attaches to shell</li> </ul>	
10171105	2-Point Chinstrap	<ul> <li>Non-metal chinstraps keep helmets in place</li> <li>Flexible construction and adjustable design for long-wearing comfort</li> <li>¾" cotton webbing</li> <li>Attaches to shell</li> </ul>	
10171106	2-Point Chinstrap	<ul> <li>Non-metal chinstraps keep helmets in place</li> <li>Flexible construction and adjustable design for long-wearing comfort</li> <li>¾" cotton webbing</li> <li>Attaches to suspension<sup>2</sup></li> </ul>	
10171107	2-Point Chinstrap	<ul> <li>Non-metal chinstraps keep helmets in place</li> <li>Flexible construction and adjustable design for long-wearing comfort</li> <li>¾" polyester webbing</li> <li>Attaches to suspension<sup>2</sup></li> </ul>	
10124238	4-Point Chinstrap	<ul> <li>Non-metal chinstraps keep helmets in place</li> <li>Flexible construction and adjustable design for long-wearing comfort</li> <li>¾" polyester webbing</li> <li>Attaches to suspension<sup>2</sup></li> <li>Pkg/10</li> </ul>	

<sup>1</sup>For elevated temperatures; flame-resistant. Not recommended for use where molten metal splash hazards exist. <sup>2</sup>Staz-On suspension only.



### **Hard Hat Accessories**

SUNSHADE HARD HAT ACCESSORIES			Sun Shield for V-Gard Cap-Style Hard Hat Sun Shield for V-Gard Full-Brim Hard Hat			
			SUN SHIELDS			
Part No. 10098032	Product Name SunShade Hard Hat Accessory Yellow-green,	<ul> <li>Product Specifics</li> <li>Fit most hats and caps</li> <li>Breathable, bright mesh fabric</li> <li>Hat clips help to keep</li> </ul>	Part No.	Product Name Sun Shield for standard V-Gard Cap-Style Hard Hats <i>only</i>	Product Specifics     Easily attaches to helmets and caps     Polyurethane brim extender protects     against sun and heat     Smoke-tinted Lexan front for extra protection	
10098031	with reflective striping SunShade	SunShade from falling or rotating • Minumum order quantity: 5	697410	Sun Shield for standard V-Gard Full-Brim Hard Hats <i>only</i>		
ITT THE	Hard Hat Accessory Orange, with reflective striping		10039114	Sun Shield for standard V-Gard 500 Cap-Style Hard Hats <i>only</i>		

### HARD HAT SWEATBAND

Part No.	Product Name	Product Specifics	
696688	Terri-Band Sweatband Gray, pkg/10	<ul> <li>Custom design fits all MSA suspensions</li> <li>Washable, with plastic snaps</li> </ul>	
10068911	Terri-Band Sweatband Gray, single		

EMERGENO	CY MEDICAL INFO ACCESSOF	8Y	F13	0
Part No.	Product Name Product Specifics			
10013393	Emergency Medical Information Accessory	<ul> <li>Provides crucial, lifesaving information in the event of a medical crisis on the job</li> <li>Pkg of 10</li> <li>Trilingual: English/Spanish/French</li> </ul>	inside view	outside view

### EMERGENCY MEDICAL INFO ACCESSORY

Part No.	Product Name	Product Specifics	DATE PLACED IN SERVICE DATE PLACED IN SERVICE. DATE PL
804358	In-Service Label	<ul> <li>To track shells service life, affix label inside helmet with date of helmet's first use</li> <li>MSA recommended replacement: shell every 5 years/suspension every 12 months</li> </ul>	DATE PLACED N SERVICE DATE PLACED N SERVICE

### **Industrial Hearing Protection and Communication Systems**

MSA has hearing protection products for nearly every industrial application. In fact, MSA offers what customers want most: economical options, cutting-edge technology, quality and outstanding performance.

### **V-Gard Helmet-Mounted Hearing Protection**



### Superior Performance

- Offers the highest attenuation for a cap-mounted earmuff on the market.
- Custom MSA sealing rings allow for optimal NRR performance.
- Works with slotted MSA industrial cap-style hard hats.
- Works with existing MSA visors and frames for seamless integration into your safety program.



### Enhanced Comfort and Fit

- Improved sealing ring and adapters optimize pressure on the ears for all-day comfort.
- Foam-injected ear pads cushion the outer
- Vertical adjustment allows for custom fit.
- Recessed interior foam does not touch user's
- ear while in use.
- When not in use, earmuffs may be stowed in "parking" position, ready for when you need them.



### Modern Style

- Includes the next generation "V" design from the iconic V-Gard.
- Incorporates red, yellow, and green color-coding on the backplate and front logo to easily identify level of attenuation.
- Upgraded fork design provides a sleek look and modernized feel.
- Matte material for both cup and ear pads decreases look of wear and tear.

NRR and CSA (	lass Ratings for	/-Gard Hearin	g Protection	

	LOW		MEDIUM		HIGH	
	NRR	CSA Class	NRR	CSA Class	NRR	CSA Class
V-GARD CAP (medium)	22	В	27	А	31	AL
V-GARD CAP (small)	23	В	28	AL	31	AL
V-GARD CAP (large)	23	В	27	AL	30	AL
THERMALGARD CAP	24	А	27	А	29	AL
SUPER-V CAP	23	В	28	AL	30	AL

NRR and CSA Class Ratings for V-Gard Hearing Protection						
	W	MEDIUM HIGH			GH	
	NRR	CSA Class	NRR	CSA Class	NRR	CSA Class
V-GARD 500 CAP	22	В	28	AL	31	AL
TOPGARD CAP	24	Α	28	AL	30	AL
SMOOTHDOME CAP	24	А	27	AL	30	AL
V-GARD H1 HELMET	coming soon					

#### V-GARD CAP-MOUNTED HEARING PROTECTION

PRODUCT NAME	V-Gard	V-Gard	V-Gard				
ATTENUATION LEVEL	LOW	MEDIUM	HIGH				
PART NO.	10190356	10190357	10190358				
PRODUCT NAME	Hygiene Kit	Hygiene Kit	Hygiene Kit				

PRODUCT NAME	Hygiene Kit	Hygiene Kit	Hygiene Kit
PART NO.	10193450	10193451	10193452
PRODUCT SPECIFICS	for V-Gard Cap-Mounted Hearing Protection, <b>LOW</b>	for V-Gard Cap-Mounted Hearing Protection, MEDIUM	for V-Gard Cap-Mounted Hearing Protection, <b>HIGH</b>

<sup>1</sup> <u>https://www.osha.gov/dts/osta/otm/noise/hcp/attenuation\_estimation.html</u>



#### **DID YOU HEAR?**

The **Noise Reduction Rating (NRR)** describes the average sound level reduction ("attenuation") provided by hearing protectors in a laboratory setting. Because the NRR reflects lab (and perhaps not real-world) usage, the Occupational Safety and Health Administration (OSHA), recommends "de-rating" the NRR to help account for incorrect fit and inconsistent wear time on worksites. OSHA's methodology for Estimating Hearing Protector Attenuation':

- 1. 8-hour Time Weighted Exposure (TWA) = 94 dBA
- 2. NRR of hearing protector = 31 dBA
- 3. Subtract 7 dB from the NRR
- = 31 dB 7 dB is 24 dB = 12 dB
- 4. Reduce value by 50%
- 5. Subtract this value from the TWA = 82 dB (Estimated Protection)
- 6. Decide if the Estimated Protection works for your environment!

### SoundControl Classic Helmet-Mounted Hearing Protection for MSA Non-Slotted Hard Hats

Markets: General industry, manufacturing, repair and maintenance, construction, oil and gas, forestry, shipbuilding, mining Applications: High-noise environments, industrial plants, construction sites Standards: Meets ANSI S3.19-1974 and CSA Class A Standards

**Compatible PPE:** 

- V-Gard Slotted and Universal Frames—no additional parts needed
- Most V-Gard Visors
- MSA non-slotted hard hats

#### SOUNDCONTROL CLASSIC HELMET-MOUNTED HEARING PROTECTION (FOR MSA NON-SLOTTED HARD HATS)





PRODUCT NAME	Sound Blocker <sup>™</sup> 26	Soprano™	SoundBlocker 26 Hygiene Kit
PART NO.	10022021	10034487	10003360
PRODUCT SPECIFICS	<ul> <li>For use with MSA non-slotted cap-style hard hats</li> </ul>	• For use with MSA <b>non-slotted full-brim</b> hard hats	Foam cushions and inserts
	<ul> <li>Requires drilling into the helmet to mount the muffs</li> </ul>	<ul> <li>Requires drilling into the helmet to mount the muffs</li> </ul>	
	• The ANSI/ISEA Z89.1 class rating of a drilled helmet is Class C	• The ANSI/ISEA Z89.1 class rating of a drilled helmet is Class C	



#### **DID YOU HEAR?**

The **EPA requirement (40 CFR 211)** specifies that hearing protectors sold in the U.S. must be tested to ANSI S3.19-1974 and labeled with a Noise Reduction Rating (NRR). MSA Hearing Protectors have been tested and labeled according to the EPA requirements. Standards organizations, such as ANSI and CSA, do not approve or certify hearing protectors.

### Headbands: left/RIGHT Hearing Protection

Markets: General industry, manufacturing, repair and maintenance, construction, OGP, forestry, shipbuilding, mining

#### Applications:

- Heavy mechanical industries, compression rooms, airports (**HIGH**)
- Utilities, construction, general industry (MEDIUM)
- $\bullet$  Food manufacturing, automotive, light industry ( LOW)
- Standards: Meets ANSI S3.19-1974 and CSA Class A Standards

#### left/RIGHT HEARING PROTECTION



PRODUCT NAME	left/RIGHT (HIGH) Hygiene Kit	left/RIGHT (MEDIUM) Hygiene Kit	left/RIGHT (LOW) Hygiene Kit
PART NO.	10092880	10092879	10092878
PRODUCT SPECIFICS	Cushions and inserts     Work with left/RIGHT helmet-mounted or headband products		



#### **DID YOU HEAR?**

The **attenuation of an earmuff depends on the fit** of the muff against the head and around the pinnae (i.e., the "tightness" of the seal). Gaps, including those caused by safety glasses, provide an easy path for sound to travel, reducing protection levels. To reduce this effect, try not to put anything under the cup (such as pencils, hair, etc.). But, if you must wear protective eyewear, select either those with a thin strap or a very thin temple. If the gap is noticeable, the protection level is compromised.



### Headbands: SoundControl Classic Hearing Protection

**Markets:** General industry, manufacturing, repair and maintenance, construction, oil and gas, forestry, shipbuilding, mining

**Applications:** Confined space, sanding/grinding, power tool use, occupations with non-impulse noise, demolition, assembly

Standards: Meet ANSI S3.19-1974 and CSA Class A Standards

#### SOUNDCONTROL CLASSIC HEARING PROTECTION



PRODUCT NAME	SoundControl HPE	SoundControl EXC
PART NO.	10061271	10061229
NRR	26 dBA	24 dBA
PRODUCT SPECIFICS	<ul> <li>Lightweight, low-profile</li> <li>High attenuation and excellent sealing for reliable protection</li> <li>Headband design and 2-point cup mounting distributes weight evenly, offering outstanding balance and comfort</li> <li>No metal parts</li> <li>Cups can be moved to various wearing positions for custom fit</li> </ul>	<ul> <li>Unique injection-molded inserts provide excellent attenuation and maximum ear space</li> <li>Medium attenuation for moderate high noise exposures</li> <li>3 distinct wearing positions</li> <li>Cups can be moved to a range of wearing positions for custom fit</li> </ul>



PRODUCT NAME	EXC Hygiene Kit
PART NO.	10061292
PRODUCT SPECIFICS	<ul> <li>Foam cushions and inserts</li> </ul>

### Economuff<sup>™</sup> Earmuff Value Hearing Protection

Economuff Earmuff hearing protectors provide cost-effective options that don't sacrifice comfort or protection.

Applications: Facility	peration (MRO), mining, food and beverage manufacturing, metal fabrication, maintenance, grinding, machine operations, sanding, welding, demolition, pai S3.19-1974 and CSA Class B Standards helmets <sup>1</sup>	
CONOMUFF HEARI	NG PROTECTION	
PRODUCT NAME	Economuff Multi-Position	Economuff
PART NO.	10061273	10004291
NRR	23 dBA (under chin/behind head) 24 dBA (over the head)	20 dBA
PRODUCT SPECIFICS	<ul> <li>Offers 3 positions: under the chin, behind the head or over the head</li> <li>Under the chin or behind the head positions allow use of head protection</li> <li>Durable design for use in tough environments</li> <li>No metal parts</li> <li>Padded headband makes longer wear possible</li> <li>I size fits most</li> </ul>	<ul> <li>Soft wide cushions maintain comfortable pressure around ears</li> <li>Lightweight</li> <li>1 size fits most</li> <li>No metal parts</li> <li>Most economical option</li> </ul>

<sup>1</sup>Economuff Earmuff multi-position worn in behind-the-head or under-the-chin positions only.

### Sightgard Safety Glasses

#### Material: Polycarbonate

Standards<sup>1</sup>: ANSI/ISEA Z87.1-2015 and CSA Z94.3 (as noted)

#### Indoor

**Markets:** Facility maintenance, repair and operations, construction, food and beverage, general manufacturing and industry, mining, oil and gas, pharmaceuticals, transportation, shipbuilding, automotive

**Applications:** Assembly and mechanical, drilling, grinding, machining, painting, sanding, sawing



## **Certification:** Third-party by ICS and CSA International **Minimum Order Qty:** 12

INDOOR	Ch we we
MODEL	
Vista	
PART NO.	
10070914	
SAFETY FEATURES	STYLING
<ul> <li>Impact-rated (Z87+)</li> </ul>	Clear lens
Tuff Stuff Anti- Scratch	<ul> <li>Frameless and lightweight</li> </ul>
Coating	<ul> <li>Among our most popular models</li> </ul>
	<ul> <li>Full side coverage</li> </ul>

### Indoor/Humid Conditions

sanding, sawing

Markets: Facility maintenance, repair and operations, construction, food and beverage, general manufacturing and industry, mining, oil and gas, pharmaceuticals, transportation, shipbuilding, automotive Applications: Assembly and mechanical, drilling, grinding, machining, painting,

INDOOR/HUMID	
MODEL	
Arctic Elite	- Col
PART NO.	
10038845 🐨	
SAFETY FEATURES	STYLING
<ul> <li>Impact-rated (Z87+)</li> <li>Tuff Stuff Anti- Scratch Coating</li> <li>Anti-fog coating</li> </ul>	<ul> <li>Clear lens</li> <li>Rubber tipped temples and nosebridge for comfortable, yet secure fit</li> </ul>

INDOOR/HUMID	a Dama
MODEL	
Aurora	
PART NO.	
10026005	
SAFETY FEATURES	STYLING
	STIEING

INDOOR/HUMID MODEL Pyrenees PART NO. 10033718	
SAFETY FEATURES	STYLING
<ul> <li>Impact-rated (Z87+)</li> <li>Anti-fog coating</li> </ul>	<ul><li>Clear lens</li><li>Full side protection</li><li>Dual injected, soft-tipped temples</li></ul>

<sup>1</sup> CSA International certified models are denoted with a 🛞 symbol.



### Sightgard Safety Glasses

Material: Polycarbonate

Standards<sup>1</sup>: ANSI/ISEA Z87.1-2015 and CSA Z94.3 (as noted)



### Indoor/Outdoor

**Markets:** General industry, manufacturing, construction, oil and gas, forestry, shipbuilding, automotive, food and beverage, mining, pharmaceuticals, primary metals, transportation

**Applications:** Assembly and mechanical, chipping, chiseling, cleaning, drilling, grinding, machining, masonry, riveting, sanding, sawing, UV protection



## **Certification:** Third-party by ICS and CSA International **Minimum Order Qty:** 12

#### Outdoor

Markets: Aviation, general manufacturing, mining, oil and gas, pharmaceuticals, primary metals, transportation

Applications: Assembly and mechanical, chipping, chiseling, drilling, grinding, machining, sanding, sawing

OUTDOOR MODEL Arctic PART NO. 697515	
SAFETY FEATURES	STYLING
<ul> <li>Impact-rated (Z87+)</li> <li>Anti-scratch coating</li> </ul>	<ul><li>Gray tint lens</li><li>Temples flex for a custom fit</li><li>Full side coverage</li></ul>

OUTDOOR MODEL Arctic Elite PART NO. 10038846	
SAFETY FEATURES	STYLING
<ul> <li>Impact-rated (Z87+)</li> <li>Anti-fog coating</li> </ul>	<ul> <li>Gray tint lens</li> <li>Rubber tipped temples and nosebridge for comfortable, yet secure fit</li> </ul>

OUTDOOR	unit of the second s
MODEL	
Easy Flex	
PART NO.	
10070918 🕅	
SAFETY FEATURES	STYLING
<ul> <li>Impact-rated (Z87+)</li> <li>Tuff Stuff Anti- Scratch Coating</li> </ul>	<ul><li>Gray tint lens</li><li>Temples flex for a custom fit</li></ul>



<sup>1</sup> CSA International certified models are denoted with a 🛞 symbol

### **Sightgard Safety Glasses**

Material: Polycarbonate

Standards<sup>1</sup>: ANSI/ISEA Z87.1-2015 and CSA Z94.3 (as noted)

OUTDOOR MODEL	
Luxor	
PART NO.	
697517	
SAFETY FEATURES	STYLING
<ul> <li>Impact-rated (Z87+)</li> <li>Tuff Stuff Anti- Scratch Coating</li> </ul>	<ul><li>Gray tint lens</li><li>Horizontal temple adjustment</li><li>Wrap-style single lens</li></ul>
OUTDOOR	
MODEL	
Pyrenees	
Pyrenees m	
Pyrenees m	STYLING

### Outdoor with UV Exposure

Markets: General industry, manufacturing, construction, oil and gas, forestry, shipbuilding

**Applications:** Chipping, splash, chiseling, drilling, grinding, machining, power fastening, sanding, sawing

OUTDOOR/UV MODEL Feather Fit PART NO. 10106384	STYLING
<ul> <li>Impact-rated (Z87+)</li> <li>Maximum UV protection (U6)</li> </ul>	<ul> <li>Gray tint lens</li> <li>Comfortable rubber flange nosepiece</li> <li>Rubber temple grips help glasses stay put under hot working conditions</li> <li>Full side coverage</li> </ul>
OUTDOOR/UV MODEL Voyager PART NO. 10065850	
SAFETY FEATURES • Impact-rated (Z87+) • Anti-scratch coating • Maximum UV protection (U6)	STYLING • Gray tint lens • Single lens

**Certification:** Third-party by ICS and CSA International **Minimum Order Qty:** 12

OUTDOOR/UV MODEL Racer Red PART NO. 10106381	
SAFETY FEATURES	STYLING
<ul> <li>Impact-rated (Z87+)</li> <li>Anti-fog coating</li> <li>Maximum UV protection (U6)</li> </ul>	<ul> <li>Rich-red mirrored lens reflects light and reduces glare without color degradation</li> <li>Ideal for utility, aviation, mining, and transportation markets</li> <li>Sporty, single, wide-wrap lens</li> <li>Full side coverage</li> </ul>

#### **DID YOU KNOW?**

A common misconception is that all polycarbonate blocks UV. This is not the case. Under ANSI/ISEA Z87.1-2015 there is a required marking if the manufacturer claims protection from UV. Look for eyewear that both meets ANSI/ISEA Z87.1-2015 and has a **U mark**.

### Over-the-Glasses

Markets: Facility safety, maintenance, repair and operations, overhaul, general industry, manufacturing, construction, oil and gas, metalworking, automotive **Applications:** Assembly and mechanical, drilling, grinding, machining, masonry, power fastening, riveting, sanding, sawing



<sup>1</sup> CSA International certified models are denoted with a 🛞 symbol.



### **Sightgard Safety Glasses**

Material: Polycarbonate

Standards<sup>1</sup>: ANSI/ISEA Z87.1-2015 and CSA Z94.3 (as noted)



### Low Light

Markets: Transportation, inspection and repair, assembly, general industry, indoor construction, shipbuilding, automotive, food and beverage, pharmaceuticals **Applications:** Assembly, chipping, chiseling, drilling, grinding, machining, pouring/ casting, power fastening, riveting, sanding, sawing

LOW LIGHT MODEL Easy Flex PART NO. 10070919	
SAFETY FEATURES	STYLING
<ul> <li>Impact-rated (Z87+)</li> <li>Tuff Stuff Anti- Scratch Coating</li> </ul>	<ul> <li>Amber lens increases contrast in low light</li> <li>Temples flex for a custom fit</li> <li>Full side coverage</li> </ul>

LOW LIGHT MODEL Pyrenees PART NO.	
10033740	
SAFETY FEATURES	STYLING
<ul> <li>Impact-rated (Z87+)</li> <li>Anti-fog coating</li> </ul>	<ul> <li>Amber lens increases contrast in low light</li> <li>Full side protection</li> <li>Dual-injected soft-tipped temples</li> </ul>

**Certification:** Third-party by ICS and CSA International **Minimum Order Qty:** 12

### Magnifiers

**Markets:** Facility safety, maintenance, repair and operations, overhaul, general industry, manufacturing, construction, metalworking, automotive

Applications: Fine assembly and detail work, drilling, grinding, machining, soldering, riveting, sanding

MAGNIFIERS MODEL Pyrenees MAG PART NO. 10068832 1.5 bifocal magnification 10065847 2.0 bifocal magnification	
SAFETY FEATURES	STYLING
<ul> <li>Impact-rated (Z87+)</li> <li>Anti-fog coating</li> </ul>	<ul><li>Clear lenses</li><li>Full side protection</li><li>Dual-injected soft-tipped temples</li></ul>

### Welding

Markets: General industry, manufacturing, construction, oil and gas, forestry, shipbuilding, metalworking; automotive, aviation

**Applications:** Welding, chiseling, drilling, grinding, machining, masonry, pouring/ casting, power fastening, riveting, sanding, sawing

WELDING MODEL Clearvue® IR PART NO. 10012847	
SAFETY FEATURES	STYLING
• Impact-rated (Z87+)	<ul> <li>Classic look with Infrared (IR) radiation eye protection, up to Shade 5</li> <li>Fits over most Rx glasses</li> <li>Integral, vented side shields</li> </ul>

<sup>&</sup>lt;sup>1</sup> CSA International certified models are denoted with a 🛞 symbol

## Head, Eye, Face, and Hearing Protection

### Sightgard Safety Goggles

SIGHTGARD SAFETY GOGGLES SELECTION GUIDE				
	CONDITIONS			
STYLE	General purpose: impact/splash	Industrial: impact/splash	Industrial: chemical/splash	
SIGHTGARD NV				
SIGHTGARD IV				
CLEARVUE® 200				
FLEXICHEM™ IV				
VAULT™				
VERTOGGLE™				

Standards<sup>1</sup>: ANSI/ISEA Z87.1-2015 and CSA Z94.3

Certification: Third-party by ICS and CSA International

 $^{1}$  CSA International certified models are denoted with a symbol .

WARNING: The products listed below can expose you to chemicals including Di(2-ethylhexyl)phthalate (DEHP) which is known to the State of California to cause cancer or reproductive harm. For more information, visit www.P65Warnings.ca.gov.

MSA Product Part No.	MSA Product Description	CA Prop 65 Chemical Name	Chemical Hazard Type
10106281	Safety Goggles, FlexiChem iV, Clear	DEHP (di-(2-ethylhexyl)phthalate	Carcinogen & Reproductive



### Sightgard Safety Goggles

Standards1: ANSI/ISEA Z87.1-2015 and CSA Z94.3

Certification: Third-party by ICS and CSA International



<sup>1</sup> CSA International certified models are denoted with a 🛞 symbol.

WARNING: The products listed below can expose you to chemicals including Di(2-ethylhexyl)phthalate (DEHP) which is known to the State of California to cause cancer or reproductive harm. For more information, visit www.P65Warnings.ca.gov.

MSA Product Part No.	MSA Product Description	CA Prop 65 Chemical Name	Chemical Hazard Type
10106268	Safety Goggles, Sightgard NV, Clear	DEHP (di-(2-ethylhexyl)phthalate	Carcinogen & Reproductive
10106270	Safety Goggles, Sightgard iV, Clear	DEHP (di-(2-ethylhexyl)phthalate	Carcinogen & Reproductive
10029693	Safety Goggles, Clearvue 200, Clear	DEHP (di-(2-ethylhexyl)phthalate	Carcinogen & Reproductive
10150069	Safety Goggle and Faceshield Combination, Clear	DEHP (di-(2-ethylhexyl)phthalate	Carcinogen & Reproductive

### **Eyewear and Goggle Accessories**

ACCESSORIES			
Part No.	Product Name	Product Specifics	
459458 for caps (1977) 449895 for hats (1977)	Goggle Retainer	<ul> <li>Sturdy neoprene-rubber accessory</li> <li>Can be used with any protective cap or hat</li> <li>Retains goggle on headwear when not in use</li> <li>Holds goggle securely when worn for eye protection.</li> <li>MSA goggle retainers are manufactured for use</li> <li>ONLY with MSA goggles in order to comply with the applicable standards of the products in the assembly.</li> </ul>	
10020871	Deluxe Eyewear Lanyard	<ul> <li>Holds eyewear securely</li> <li>Lanyard strap slides over temple</li> <li>Pkg of 12</li> </ul>	
13016	Fogpruf™ Cleaner Refill	• 4 0z. bottle	
10022087	Towelettes	• Pre-moistened • Box of 100	



# Save money, increase revenue and reduce inventory costs with our comprehensive Above-the-Neck safety solutions:

• "Try It" sample program offers 100+ leading MSA products, including V-Gard Hard Hats, V-Gard Accessories, left/RIGHT earmuffs, and Sightgard<sup>®</sup> eyewear—completely **FREE of charge!** Look for the *m* that tells you which products are in the program.

• Our products are tested by engineers in our own test facilities. They are also certified and/or tested by qualified, third-party test houses.

Note: This Bulletin contains only a general description of the products shown. While product uses and performance capabilities are generally described, the products shall not, under any circumstances, be used by untrained or unqualified individuals. The products shall not be used until the product instructions/user manual, which contains detailed information concerning the proper use and care of the products, including any warnings or cautions, have been thoroughly read and understood. Specifications are subject to change without prior notice. MSA is a registered trademark of MSA Technology, LLC in the US, Europe, and other Countries. For all other trademarks visit https://us.msasafety.com/Trademarks.

MSA operates in over 40 countries worldwide. To find an MSA office near you, please visit <u>MSAsafety.com/offices</u>.