



Fall Protection

Only
available in
France

Technical Data Sheet

AA420NG - 3M™ Protecta® Pro™ Kit

Kit includes: 3M™ Protecta® Pro™ Harness,
3M™ Protecta® Rebel™ Web Self-Retracting
Lifeline, 3M™ Protecta® Nylon Webbing Sling,
3M™ Protecta® Back Pack

Description

Industry:	Construction
Brand:	Protecta®

Composition of the kit AA420NG

Harness:

3M™ Protecta® Pro™ Harness - AB10033NG (M)

Harness:	<ul style="list-style-type: none">- 1 fall arrest dorsal D-ring- Adjustable chest and thigh straps
Webbing:	<ul style="list-style-type: none">- Polyester- Width: 44 mm- Stitching: high-strength polyester thread- Breaking strength > 2600 daN
Fitting:	<ul style="list-style-type: none">- High-strength zinc-plated steel- Attachment D-rings in zinc-plated steel- Energy absorbing dorsal plate- Quick adjustment pass thru buckles
System Breaking Strength:	> 1500 daN
Weight Capacity:	140 kg
Net Weight:	0.90 kg
Standards:	CE EN361

Self-Retracting Lifeline:

3M™ Protecta® Rebel™ Web SRL - 3100443

Web:	<ul style="list-style-type: none">- Polyester- 25 mm wide
Recall Spring Material:	Carbon steel
Opening:	17 mm
Connection Level:	Can be connected from shoulder level and above
Weight Capacity:	140 kg
Standards:	CE EN360



Sling:

3M™ Protecta® Nylon Webbing Sling - AM450/80

Webbing:	- Polyester
	- Length: 800 mm
	- Width: 24 mm

System Breaking Strength:	22 kN
----------------------------------	-------

Capacity:	2 users
------------------	---------

Net Weight:	0.08 kg
--------------------	---------

Standards:	EN795 Class B, EN354, EN566, CEN/TS 16415
-------------------	---

Back Pack:

3M™ Protecta® Back Pack - AK053NG

Back Pack:	- Front pocket zip fastener
	- Main pocket zip fastener
	- Grab handle
	- Padded shoulder straps

Dimensions:	- Length: 200 mm
	- Width: 290 mm
	- Height: 465 mm

Colour:	Red, black and grey
----------------	---------------------

Net Weight:	0.45 kg
--------------------	---------

Important Notice

The mounting and use of the product described within this document assumes that the user has previous experience of this type of product and that it will be assembled by a competent professional according to product documentation. Before any use of this product it is recommended to complete some trials to validate the performance of the product within its expected application.

All information and specification details contained within this document are inherent to this specific 3M product and would not be applied to other products or environment. Any action or usage of this product made in violation of this document is at the risk of the user.

Compliance to the information and specification relative to the product contained within this document does not exempt the user from compliance with additional guidelines (safety rules, procedures). Compliance to operational requirements especially in respect to the environment and usage of tools with this product must be observed. The 3M Group (who cannot verify or control these elements) would not be held responsible for the consequences of any violation of these rules which remain external to its decision and control.

Warranty conditions for products are determined with the sales contract documents and with the mandatory and applicable law, excluding any other warranty or compensation.

3M Fall Protection Business

Capital Safety Group (NE) Ltd
5a Merse Road, North Moons Moat
Redditch, B98 9HL, UK

Phone 00 800 999 55500

Email informationfallprotection@mmm.com

Web 3M.com/FallProtection

Capital Safety Group (EMEA)
Le Broc Center, Bâtiment A, Z.1. 1re Avenue – BP15
06511 Carros Le Broc, Cedex, FRANCE

3M is a trademark of 3M Company. Capital Safety and Pro™ are trademarks of D B Industries, LLC.
Protecta® is a trademark of Capital Safety Group EMEA.



Fall Protection