

Mk7[®] HI-TEMP 150[™] NON-VENT - SLIP RATCHET

PRODUCT CODE: AHR120-000-100

Mk7[®] HI-TEMP 150[™] HAS THE ABILITY TO STILL BE EFFECTIVE AT TEMPERATURES OF UP TO 150°C

TECHNICAL SPECIFICATION

HEAD PROTECTION

INSTRUCTIONS FOR USE

Fit helmet on head and fasten strap to ensure fit

For adequate protection this helmet must be worn with peak facing forward

Ensure the helmet is adjusted to the size of the user's head

SHELL:

High temperature polyimide

WEBBING HARNESS:

HDPE Strap & high temperature Webbing Clips with Polyester Webbing Straps

CHAMLON[™] SWEATBAND:

Egyptian cotton core with porous PU coating for maximum sweat absorption. PH neutral, dermatologically tested

SLIP RATCHET:

EasyJust[®] Slip Ratchet



CONFORMITY

Conforms to EN 397 and EN50365

EC Certificate Num.00279, issued by BSi Product Certification

Meets optional 150°C high temperature performance

Meets optional -40°C very low temperature performance

Meets optional Lateral Deformation performance

Meets optional Molten Metal Splash performance

Meets optional Electrical Insulation requirements

Wide size range

High comfort fit

Company personalisation available by printing

Incorporates a rain channel

Accessories available

CLEANING & MAINTENANCE

The unit may be cleaned with soap and warm water and dried with a soft cloth

The helmet should not be cleaned with chemical or abrasive cleaners

The helmet should be stored out of direct sunlight

The helmet should be stored away from chemicals and extremes of temperature

Mk7[®] HI-TEMP 150[™] NON-VENT - SLIP RATCHET

PRODUCT CODE: AHR120-000-100

Mk7[®] HI-TEMP 150[™] HAS THE ABILITY TO STILL BE EFFECTIVE AT TEMPERATURES OF UP TO 150°C

TECHNICAL SPECIFICATION

HEAD PROTECTION

DIMENSIONS OF OUTER PACKAGING

Quantity: 10

Weight: 6.25kg (Approx.)



HEIGHT:
466mm

LENGTH:
590mm

WIDTH:
255mm

DIMENSIONS OF HELMET

Length: 296mm

Width: 224mm

Height: 164mm

Weight: 500g (Approx.)



HELMET COLOURS

The Mk7[®] Hi-temp 150[™] is only available in white



HELMET FEATURES

EN STANDARD	EN397 EN50365	Yes Yes
PERFORMANCE	Impact Resistance Electrical Insulation	Yes 50 Joules Yes: EN397 440V EN50365 1000V
TEMPERATURE RESISTANCE	Molten Metal (MM) +150°C -40°C	Yes Yes Yes
SHELL MATERIAL	High temperature polyimide Recyclable	Yes Yes
HARNESS MATERIAL	LDPE Textile	Yes Yes
OPTIONS	Universal Accessories Integrated Eyewear 2pts or 3pts Chinstrap Hi-Temp Resistance	Yes Yes Yes Yes
HARNESS SYSTEM OPTIONS	Slip Ratchet 8 pts	Yes Yes
LOGO OPTIONS	Front Rear Side MOQ Logo Individual Name	Yes Yes Yes 10 Yes

LIMITATIONS OF USE

Protection will only be offered if the helmet is fitted correctly

Any helmet subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer

The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice

The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer