

PRODUCT CODE: AJB170-40 - 00

CR2 - HIGH INTENSITY REFLECTIVE OFFERING AN AVERAGE OF 60% MORE REFLECTIVITY THAN STANDARD REFLECTIVE CLOTHING MATERIAL

TECHNICAL SPECIFICATION

HEAD PROTECTION

INSTRUCTIONS FOR USE

Fit helmet on head and fasten strap to ensure fit

For adequate protection this helmet must be worn with peak facing forward

Ensure the helmet is adjusted to the size of the user's head



MIDPEAK - WHEEL RATCHET - VENTILATED - CR2

SHELL: High strength engineering grade ABS which has been UV Stabilised



HDPE Strap & Webbing Clips with Polyester Webbing Straps CHAMLON™ SWEATBAND:

Egyptian cotton core with porous PU coating for maximum sweat absorption. PH neutral, dermatologically tested

CR2 REFLECTIVE:

High Intensity Reflective offering, on average, 60% more reflectivity than standard reflective clothing material



SLIP RATCHET: One Touch[™] Slip Ratchet version

of the EVOLite® is so simple to fit that it can be adjusted with just one finger



evolution lite

CONFORMITY

EN 397 for Industrial Safety Helmets

- EC Certificate Number 00279, issued by BSi Product Certification
- Meets optional Lateral Deformation performance
- Meets optional Molten Metal Splash performance
- Wide size range. Slip or wheel ratchet High comfort fit
- Available vented. Available with mid or micro peak
- Company personalisation available by printing

CR2 REFLECTIVE

EVOLite CR2 is the biggest step-up in night time visbility/ reflectivity of head protection to date

Meeting reflective performance requirements of EN12899-1 (High performance reflective sign face material)



MANUFACTURING FOR SAFETY

UKSALES@JSP.CO.UK TEL: +44 (0)1993 826050





EVOLite®

MIDPEAK - WHEEL RATCHET - VENTILATED - CR2

PRODUCT CODE: AJB170-40_-_00

CR2 – HIGH INTENSITY REFLECTIVE OFFERING AN AVERAGE OF 60% MORE REFLECTIVITY THAN STANDARD REFLECTIVE CLOTHING MATERIAL

SPECIFICATION

TECHNICAL

HEAD PROTECTION

DIMENSIONS OF OUTER PACKAGING

Quantity: 10

Weight: 3.2kg (Approx.)



DIMENSIONS OF HELMET

Size: 530 - 640mm

Weight: 299g (Approx.)

CLEANING & MAINTENANCE

The unit may be cleaned with soap and warm water and dried with a soft cloth

The helmet should not be cleaned with chemical or abrasive cleaners

The helmet should be stored out of direct sunlight The helmet should be stored away from chemicals

and extremes of temperature



HELMET COLOURS

Insert the following two digit number in place of the dashes in the product code of your desired helmet





MANUFACTURING FOR SAFETY

UKSALES@JSP.CO.UK TEL: +44 (0)1993 826050 O



HELMET FEATURES

EN STANDARD	EN397 EN12899-1	Yes Yes
PERFORMANCE	Impact Resistance Lateral Deformation	Yes 50 Joules Yes
TEMPERATURE RESISTANCE	Molten Metal (MM) +50°C -30°C	Yes Yes Yes
SHELL MATERIAL	ABS Recyclable UV Stabilised	Yes Yes Yes
HARNESS MATERIAL	HDPE Textile	Yes Yes
OPTIONS	Universal Accessories Reflective CR2 option Integrated Eyewear	Yes Yes Yes
HARNESS SYSTEM OPTIONS	JSP 3D Slip Ratchet 6 pts	Yes Yes Yes
CHINSTRAP OPTIONS	4 pts 2 pts	Yes Yes
LOGO OPTIONS	Front Rear Side MOQ Logo Individual Name	Yes Yes Yes 10 Yes

LIMITATIONS OF USE

Protection will only be offered if the helmet is fitted correctly

Any helmet subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer

The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice

The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer