

PW30 - Visitor Safety Glasses

Collection: Eye Protection

Range: Eye Protection

Materials: Polycarbonate

Inner Pack: 12

Outer Carton: 288

Product information

Designed with a moulded-in browguard and vented side shields, the PW30 offers excellent protection and comfort. Manufactured using tough impact resistant polycarbonate. Metal free.

Eye Protection

PORTWEST® eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.

Eye Protection

PORTWEST eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of the workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.

Standards

EN 166 (1 F)
EN 170 (2C-1.2)
ANSI/ISEA Z87 +



Features

- Single panoramic lens glasses
- Excellent side protection
- Transparent colour for better side visibility
- Suitable for wearing over most prescription glasses
- Moulded side shield and browguard for optimised protection against impacts
- 99% UV protection
- Anti-scratch coating for added durability
- CE certified
- UKCA marked
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PW30 - Visitor Safety Glasses Commodity Code: 9004901000

Test House

DIN CERTCO Gesellschaft fur Konformitätsbewertung mbH (Notified Body No.: NB: 0196)

Alboinstrabe 56

, Germany

Cert No: C5278PW_R2

TUV Rheinland UK Ltd (Notified Body No.: 2571)

5 Mallard Way

DE24 8GX, Derby

Cert No: 60166623

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
PW30CLR	Clear	65.0	35.0	59.0	0.0500	0.1342	5036108134632	25036108635997