


Helixon



II 2 G Ex h IIC T6 Gb



HS CODE
84798997
CARTON SIZE / PCS.
60 x 40 x 24 cm / 3
AET N°2777/10833-02/E01-02
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.01
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland
ACKNOWLEDGEMENT OF RECEIPT N°3975/1/2018 (ATEX)
Technická Inšpekcia, a.s. N°1354 Trnavská cesta 56, 821 01 Bratislava, Slovenská Republika


REF.	FA 20 402 15B FA 20 402 20	FA 20 402 20S
LG. 	15 m 20 m	20 m
KG 	140 KG	140 KG
CE 	EN 360:2002	EN 360:2002
MAT. 	Polyamide 6 - 30% fiber glass  STEEL Ø4.5 mm	Polyamide 6 - 30% fiber glass  INOX Ø4.5 mm
	 FA 50 225 23B / FA 50 203 20 with fall indicator	 FA 50 225 23B / stainless steel connector with fall indicator
	x2	x2
R(kN)	12 kN	12 kN
	NO	NO
+	 II 2 Exh IIC T6 Gb EN 360 §4.6 (endurance test) EN 80079-36:2016 EN 80079-37:2016	 II 2 Exh IIC T6 Gb EN 360 §4.6 (endurance test) EN 80079-36:2016 EN 80079-37:2016
	7.49 KG 7.70 KG	7.70 KG

LG.
KG


Longueur Poids maxi utilisateur
Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers

MAT.
 / 

Matière carter / câble
Material of casing / wire rope
Material cárter / cable
Material dei carter / cavo
Material Gehäuse / Seil

 / 

Matière connecteur haut / connecteur bas
Material of top connector / bottom connector
Material conector alto / conector bajo
Materiale connettore alto / connettore basso
Material oberes / unteres Verbindungselement



Nombre d'émerillons
Number of swivels
Cantidad de eslabones giratorios
Numero di tornichetti
Anzahl der Wirbel



Homologué pour le travail à proximité d'arêtes vives
Approved for work near sharp edges
Homologado para trabajo cerca de aristas vivas
Omologato per lavoro in prossimità di spigoli vivi
Zugelassen für Arbeiten in der Nähe scharfer Kanten