





II 2 G Ex h IIC T6 Gb



①

x2 EN 795
x2 pulleys


②



③



④



⑤



HS CODE
76169990
CARTON SIZE / PCS.
FA 60 101 00 : 147 X 29 X 26 cm / 1 FA 60 102 00 : 212 x 35 x 30 cm / 1
AET (UE) N°2777/10800-02/E06-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.01
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland
ACKNOWLEDGEMENT OF RECEIPT N°3975/1/2018 (ATEX)
Technická Inšpekcia, a.s. N°1354 Trnavská cesta 56, 821 01 Bratislava, Slovenská Republika

REF.	FA 60 101 00	FA 60 102 00
CE	EN 795:2012 Type B	
	X 1	
 1 2	500 kg / 250 kg	
MAT.		
DIM. $\updownarrow$ H	1.15 m $\rightarrow$ 2.15 m	1.9 m $\rightarrow$ 2.9 m
R (kN) / MBS (kN)	12 kN / 20 kN	
	1.08 m $\rightarrow$ 1.62 m	1.52 m $\rightarrow$ 2.05 m
+	(1) Machinery Directive + EN 1808 (2) FA 60 002 01, FA 60 002 02 (2) FA 20 401 XX + FA 60 101 01 (2) FA 60 003 XX, FA 60 023 20/R + FA 60 101 02 EN 80079-36:2016 EN 80079-37:2016	
	14.6 kg	22,35 kg



Nombre d'utilisateurs
Number of users
Cantidad de usuarios
Quantità di utilizzatori
Anzahl der Benutzer



Charge maxi admissible sous tête / sur jambe
Max. allowable load under head/on leg
Carga máxima admisible bajo cabezal / en pata
Peso massimale sotto la testa su una gamba
Zulässige Höchstlast unter Kopf / auf Bein

DIM. $\updownarrow$ H

Hauteur
Height
Altura
Altezza
Höhe



Empattement du trépied
Tripod footprint
Distancia entre ejes del trípode
Basamento
Standbreite des Dreibeins

+

Point fort
Key feature
Ventaja principal
Punti forti
Produktvorteil

+

À utiliser avec
To be used with
Para usar con
Ad essere utilizzato con
Verwendet werden soll mit