

# TECHNICAL DATASHEET

## PRO 2000 CF32 ABEK2P3 COMBINED FILTER

### DESCRIPTION

Part Number	5042799
Shelf Life	5 years factory sealed
Package	20
Storage Conditions	-10 °C + 50 °C (factory sealed)
Diameter	110mm
Height	105mm
Weight	386g
Connection	40 mm thread
Body Material	Polypropylene, reinforced



### APPROVAL

EN14387

### PRO 2000 CF32 ABEK2P3 COMBINED FILTER PROTECTS AGAINST:

A	A = Gases and vapours from organic compounds with a boiling point above 65°C
B	B = Inorganic gases and vapours, e.g. chlorine, hydrogen sulphide, hydrogen cyanide
E	E = Acid gases and vapours, e.g. sulphur dioxide
K	K = Ammonia and organic ammonia derivatives
P3	P3 = Solid and liquid particles, toxic and radioactive particles, micro-organisms (e.g. bacteria and viruses). And enzymes
R	R = Reusable

### TECHNICAL DATA

	PRO 2000 CF32 ABEK2P3	EN14387 Requirements
<b>BREATHING RESISTANCE</b>		
30 l/m	1.3 mbar	Max 2.6 mbar
95 l/m	4.5 mbar	Max 9.8 mbar
<b>GAS FILTER CAPACITY WITH TEST GAS @ 30 L/M</b>		
Tetrachloromethane CCl <sub>4</sub> (0.5 vol.-%)	-	
Cyclohexan C <sub>6</sub> H <sub>12</sub> (0.5 vol.-%)	50 min	Min. 35 mins
Chlorine Cl <sub>2</sub>	55 min	Min 20 mins
Hydrogen sulphide H <sub>2</sub> S	> 120 min	Min 40 min
Hydrogen cyanide HCN	56 min	Min 25 min
Sulphur dioxide SO <sub>2</sub>	26 min	Min 20 min
Ammonia NH <sub>3</sub>	85 min	Min 40 min
<b>PARTICLE FILTER EFFICIENCY @ 95 L/MIN</b>		
Sodium chloride NaCl (S)	< 0.001%	Max 0.05%
Paraffin oil (L)	< 0.003%	Max 0.05%