



Murmullo with cord



Hearing protection: earplugs

Description:

Made out of polyurethane foam, with a non-porous, soft texture, making them more resistant to dirt.

Hypo-allergenic. Their cone-shape makes insertion and adaptation easier.
Loss-prevention cord.

SNR: 37 dB

Weight: 2.7 g


EN 352-2 CE



Soft
polyurethane
foam



With cord



Ref:	Product
910.351	Murmullo with cord

Characteristics table

Washable	✗
Hypo-allergenic	✓
Reusable	✗
Disposable	✓
Detectable	✗
Cord	✓
Nominal size	12

Hearing protection: earplugs

Standard and certification	EN 352-2 CE																																						
Applications	Workplaces with high temperatures. Exposure to continuous noise. Work environments with a high noise level between 108 dB and 122 dB. General industrial use.																																						
Conservation Storage - Expiry	Store in a cool, dry place in their case, avoiding humidity, dirt and dust.																																						
Directions Use	This equipment is for personal use and should not be used by several people. The earplugs must be worn continually in noisy areas. These plugs must not be used in environments where there is a risk of the joining cord being snagged during use.																																						
Presentation	Pairs in individual bags. Dispenser box with 200 pairs in individual bags. 10 boxes per carton.																																						
Bar code	GTIN-13: 8423173840020 GTIN-14: 88423173840026																																						
Attenuation table	<table><tr><td>Frequency in Hz</td><td>125</td><td>250</td><td>500</td><td>1,000</td><td>2,000</td><td>4,000</td><td>8,000</td></tr><tr><td>Assumed attenuation</td><td>38.1</td><td>37.9</td><td>39.6</td><td>37.7</td><td>37.3</td><td>48.8</td><td>45.9</td></tr><tr><td>Typical deviation</td><td>4.9</td><td>6.3</td><td>6.5</td><td>4.2</td><td>3.5</td><td>5.1</td><td>4.5</td></tr><tr><td>Average attenuation</td><td>33.2</td><td>31.6</td><td>33.1</td><td>33.5</td><td>33.8</td><td>43.3</td><td>41.4</td></tr></table> <table><tr><td>Global attenuation in frequencies</td><td>High (H) H = 36</td><td>Mid (M) M = 34</td><td>Low (L) L = 33</td><td>SNR</td><td>37</td></tr></table>	Frequency in Hz	125	250	500	1,000	2,000	4,000	8,000	Assumed attenuation	38.1	37.9	39.6	37.7	37.3	48.8	45.9	Typical deviation	4.9	6.3	6.5	4.2	3.5	5.1	4.5	Average attenuation	33.2	31.6	33.1	33.5	33.8	43.3	41.4	Global attenuation in frequencies	High (H) H = 36	Mid (M) M = 34	Low (L) L = 33	SNR	37
Frequency in Hz	125	250	500	1,000	2,000	4,000	8,000																																
Assumed attenuation	38.1	37.9	39.6	37.7	37.3	48.8	45.9																																
Typical deviation	4.9	6.3	6.5	4.2	3.5	5.1	4.5																																
Average attenuation	33.2	31.6	33.1	33.5	33.8	43.3	41.4																																
Global attenuation in frequencies	High (H) H = 36	Mid (M) M = 34	Low (L) L = 33	SNR	37																																		

