

VeriShield™ VS130N Passive Earmuff

PRODUCT INFORMATION

Rev.: 01

Date: 2019.06.20

SPECIFICATIONS

ARTICLE	VeriShield Passive Behind-the-Neck Earmuff, VS130N		
MODEL NO	1035116-VS		
REGION	Americas		
BARCODES	Box	7312550351161	7312550351178
	Case	17312550351168	17312550351175
WEIGHT	251g		
ACCESSORIES	1035138-VS		
	Hygiene Kit	1000365	1000365
	Cool Pads		
SALES UNITS	1 EA		
	Box	10 boxes	1 EA
	Case		10 boxes
VOLUME	Box	L 165*W 120*H 150mm	L 165*W 120*H 150mm
	Case	2.97dm^3	2.97dm^3
	Box	L 615*W 345*H 182mm	L 615*W 345*H 182mm
	Case	38.62dm^3	38.62dm^3
MATERIAL	Box	Cardboard	Cardboard
	Case	Corrugated cardboard	Corrugated cardboard



POS.	PART LISTING	MATERIAL	COLOR
1	Ear Cup	ABS	NCS 8500-N
2	Rim	PP	NCS 8500-N
3	O-ring	Silicon	NATURAL
4	Foam Insert	PU foam	PMS 7621C
5	Ear Cushion	PVC/PU Foam	NCS 9000-N
6	Wire Guide	POM	NCS 9000-N
7	Headband	PU/Steel	NCS 9000-N

VeriShield™ VS130N Passive Earmuff

PRODUCT INFORMATION

CUSTOM TARIFFS
39269099
COUNTRY OF ORIGIN
China
TEMPERATURE OPERATION RANGE
0°C to +55°C/32°F to +131°F
PRODUCT MARKING

"Honeywell HOWARD LEIGHT" - cup

"VS130N" – cup

For more information

www.honeywellsafety.com

Honeywell Industrial Safety

9680 Old Bailes Road, Fort Mill, SC 29707

Phone: 803-835-8000

Fax: 401-232-3110

Honeywell

HOWARD
LEIGHT

Rev.: 01 Date: 2019.06.20

NRR

VeriShield™ VS130N Passive Earmuff is tested according to ANSI S3.19-1974 at Michael & Associates Inc.

Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000	NRR
Mean Value, dB	21.8	25.0	31.5	37.8	38.2	38.6	39.5	39.3	39.4	
Standard Deviation, dB	2.4	2.5	2.3	2.4	2.0	2.9	3.6	2.5	3.9	28 dB
APV/dB	19.4	22.5	29.2	35.4	36.2	35.7	35.9	36.8	35.5	
CSA Class AL										

Clamping force: 2.9 lbs

SNR

VeriShield™ VS130N Passive Earmuff is tested according to EN 352-1:2002 at Michael & Associates Inc.

Frequency Hz	125	250	500	1000	2000	4000	8000	SNR
Mean Value, dB	22.5	24.8	31.4	36.9	36.5	37.9	38.9	
Standard Deviation, dB	2.6	2.9	2.8	2.5	2.8	3.4	2.8	33 dB
Assumed Protection, dB	19.9	21.9	28.6	34.4	33.7	34.5	36.2	

H=35 dB M=31 dB L=25 dB

SLC80

VeriShield™ VS130N Passive Earmuff is tested according to AS/NZS 1270:2002 at Michael & Associates Inc.

Frequency Hz	125	250	500	1000	2000	4000	8000	SLC80
Mean Attenuation, dB	20.1	22.4	30.3	35.5	35.5	36.0	38.0	
Standard Deviation, dB	4.1	4.1	3.6	3.3	3.8	3.1	3.4	31 dB
Mean-Minus-Std Deviation, dB	16.0	18.3	26.7	32.2	31.7	32.9	34.6	

Class 5