Moulded Disposable Mask 111- FFP1

PRODUCT CODE: BEJ110-001-000

"SHAPE TO FIT" QUALITY MOULDED DISPOSABLE MASK AVAILABLE IN SMALL, MEDIUM OR LARGE

TECHNICAL SPECIFICATION

RESPIRATORY PROTECTION

INSTRUCTIONS FOR USE

Mask must be fitted in accordance with the instructions supplied Care must be taken to ensure that the correct mask type is selected for the work to be carried out


If in doubt as to the type of mask required seek professional guidance

PERFORMANCE

Offers an assigned protection factor (APF) of 4 \times Workplace Exposure Limit (WEL) for fine non-toxic dusts, fibres, fumes and mists

DIMENSIONS OF OUTER PACKAGING

Quantity: 200 (10 inner packs of 20 masks) Weight: 3.6kg (Approx)



DIMENSIONS OF MASK

Depth: 73mm
Width: 146mm
Height: 128mm
Weight: 9g (Approx)

CLEANING & MAINTENANCE

Not Applicable - Disposable Product

Store the masks out of sunlight away from chemicals in a dry atmosphere



LIMITATIONS OF USE

Protection will only be offered if the mask is fitted correctly

The mask, when in contact with the skin may cause allergic reactions to susceptible individuals

Do not use where exposure to chemical gases may be experienced

Use in well ventillated areas only, which are not deficient in oxygen and do not contain explosive atmospheres

Ensure good seal around the face is created before entering the hazard area

The working life of the mask is nominally one day (this is based on an working day shift of 8 hours), however it may be affected by many factors, including work rate, airflow and concentration of any contaminent in the atmosphere. The mask should be changed immediately if,

a.) Breathing difficulties due to clogging are

experienced,

b.) Breakthrough of a contaminent is detected by smell, taste or any other means, or

c.) The mask becomes damaged

CONFORMITY & MARKINGS

Meets the FFP1 requirements of EN149

EC Certificate Number 560229, issued by BSi Product Certification EN149:2001 + A1:2009



MANUFACTURING FOR SAFETY
<u>www.jsp.co.uk</u>

UKSALES@JSP.CO.UK TEL: +44 (0)1993 826050

