


DOC NO	ISSUE	REVISION	PRODUCT REF.	DATE	QUALITY PLAN
QF/RD/05	01	00	FAR0302	01.10.14	
TECHNICAL SPECIFICATIONS				SIGNATURE	
				PRESIDENT (TECHNICAL)	

FULL BODY HARNESS (FAR0302)



DESIGN

- One dorsal attachment D-ring for fall arrest and front textile loops for fall arrest.
- Adjustable leg straps.
- Sit Strap.

WEBBING

- Material : Polyester.
- Width : 44±1mm.
- Breaking strength : 23 kN.

STITCHING THREAD

- Material : High-tenacity polyester.

METAL COMPONENTS

- Material : Alloy Steel .
- Plating : Galvanized with Yellow Passivation.
- Finish : Deburred & Shot Blasted.

VITAL TEST COMPLIANCE

- Static Strength : 15 kN or 1,530 kgf for 3 Minutes at each attachment element.
- Dynamic strength : Free fall from 4 meters height donned to a test dummy weighing 100 kg at each attachment element.


WEIGHT

- : 875 gm ±10 gm.



DOC NO	ISSUE	REVISION	PRODUCT REF.	DATE	QUALITY PLAN
QF/RD/05	01	00	FAR0305	10.10.14	
TECHNICAL SPECIFICATIONS				SIGNATURE	
				PRESIDENT (TECHNICAL)	

ENERGY ABSORBING WEBBING LANYARD (FAR0305)



DESIGN

- Webbing lanyard incorporated with Energy absorber (400)
- One side of the lanyard equipped with Karabiner (112) while other side of the lanyard equipped with Steel scaffold hook (131).

WEBBING

- Material : Polyester.
- Width : 30±1mm.
- Breaking strength : 25 kN.

STITCHING THREAD

- Material : High-tenacity polyester.

VITAL TEST COMPLIANCE

- Static Strength : 15 kN for 3 Minutes.
- Dynamic Performance : Maximum breaking force does not exceed 6 kN in the line when tested on a free fall from 4 meters height attached to a test mass of 100 kg.

WEIGHT

- 2.0 meter : 1100 gm ±10gm

