

 GRAND PROTECTION INT. SAFETY AND WORK SHOES	ARTICLE TECHNICAL SPECIFICATION LS25JCB S2 SRC	CODE	LS25JCB S2 SRC
		REVISION	0
		DATE	02/12/2025

1. ARTICLE AND STANDARD.

REF. LS25JCB S2 SRC

2. PICTURES



3. MATERIALS

ITEM	MATERIAL	FINISHING	COLOR	COMMENTS
UPPER1	White microfiber		White	Thickness 1,4 mm- 1.6mm
UPPER2	White microfiber		White	
TOE CAP	White microfiber		White	
BACK PART	White microfiber		White	
TONGUE	White microfiber	-	White	-
FOOTBED	Grey Mesh with EVA+label	-	Grey	Antistatic stitching
COLLAR 1	White microfiber	-	White	Thickness 1.4mm
VAMP LINING	White non-voven fabric	-	White	Thickness 1.2mm -
QUARTER LINING	Grey PK mesh	-	Grey	+3mm foam +TC net
TONGUE LINING	Grey PK mesh		Grey	+3mm foam +TC net
SOLE	PU/PU	-	Light Grey Midsole, Light grey Outsole	Antistatic
TOE CAP	Steel toe cap	-	-	604 -
INSOLE	Antistatic insole board	-	-	Antistatic stitching
TONGUE FOAM	N/A		-	
COLLAR FOAM	Foam	High-elasticity foam	-	15mm
HEEL COUNTER	Hot melt glue	-	-	1.5-1.6mm
Button	White Elastic	-		21mm
THREADS	Polyester	-	Match with the upper	42*3

 GRAND PROTECTION INT. SAFETY AND WORK SHOES	ARTICLE TECHNICAL SPECIFICATION LS25JCB S2 SRC	CODE	LS25JCB S2 SRC
		REVISION	0
		DATE	02/12/2025

4. MARKS – BRANDING

TYPE	MARK	POSITION	SIZE
Side LOGO		2.2*0.9CM	Visible size
TONGUE LOGO	N/A		
FOOTBED LOGO		White printing logo +antistatic stitching and front embossed	5cm length 1cm wide
Insole logo			-
SHOE LACES	N/A		
Back strap			
Plastic bags	Transparent bag	Size:36-42: 50*35cm 43-48: 55*40cm	
Micro-PAK		Green	

5. CE LABELS



Melted on the back of Tongue

Size: 3.5 x 4.5 cm(height)

Pls change shoe size, date of produce 06(month)/20 (year), lote number and the size in this line accordingly.

Size reference list (UK/EURO/USA)

Equivalences		
UK	EURO	US
2	34	3
3	35	4
4	36	5
4.5	37	5.5
5.5	38	6.5
6	39	7
7	40	8
7.5	41	8.5
8.5	42	9.5
9.5	43	10.5
10	44	11
11	45	12
11.5	46	12.5
12.5	47	13.5
13	48	14
14	49	15
15	50	16

6. BOXES AND PACKING

The packing will be at 5 pairs per ctn. All the pairs in the same carton must have the same size. It’s not allowed mix different sizes in the same carton.

Pair box design:



holes on the middle of side

Pair box measurements

PAIR BOX SIZE RANGES	Length* width * height
36-41#	31x19x11.5cm
42-44#	33x20x12cm

Pair box label:

 GRAND PROTECTION INT. SAFETY AND WORK SHOES	ARTICLE TECHNICAL SPECIFICATION LS25JCB S2 SRC	CODE	LS25JCB S2 SRC
		REVISION	0
		DATE	02/12/2025



Pair box label: SIZE 14,3*7 cm （height）
 Pls change shoe size, lote number and the size in this line , FECHA/DATE : (production date) and barcode accordingly.

Carton box design:

Carton sealing tape:

Carton box measurements:

CARTON SIZE RANGES	Length* width * height
36-42#	59.5*21,5*33,5
43-48#	64´5*22´5*36,5

Carton label: 80mm(height)*100mm



CODE	LS25JCB S2 SRC
REVISION	0
DATE	02/12/2025

Pls change size, lote number and the size in this line , FECHA /DATE :and barcode accordingly

7. HANGTAGS



8. **USER INSTRUCTIONS** (10cm(Height)*7cm(Width)) new users with ENISO20347 standard and new styles .see attachment . The newest update .

ΗΜΕΡΟΜΗΝΙΑ ΛΗΞΗΣ

- Ημερομηνία λήξης αυτής των υποδημάτων εξαρτάται κυρίως από τη σωστή χρήση, τις συνθήκες χρήσης και τη φροντίδα τους.
- Τα υποδήματα αποσπούνται από αξιωματικά μέσα τα οποία πολύ ανεπιτυχώς στην πράξη του χρόνου είναι διατηρούνται σε κατάλληλες συνθήκες, από την έλλειψη σωστής φροντίδας. Μεγάλη διάρκεια 5 έτη. Το εν λόγω χρονικό διάστημα είναι μόνο για την υποστήριξη, συντηρητική και διατηρητική σε λειτουργικές συνθήκες, απορροφώντας τις έντονες θερμικές διακυμάνσεις και τη σχετικά υγρασία.
- Διάρκεια χρήσης: Εξαρτάται από τη σωστή χρήση των υποδημάτων.

ΕΥΕΙΚΕΥΑΣΙΑ, ΑΠΟΦΗΚΕΥΗ, ΣΥΝΤΗΡΙΣΗ ΚΑΙ ΚΑΘΑΡΙΣΜΟΣ

- Τα υποβλήματα είναι υποκειμενικά ενώ οι κοινότητες και πληθυσμοί είναι πολύμορφοι και με μέγιστη θερμοκρασία διασποράς (γιατί 5°C και 15°C).
- Αποφεύγετε την ελαστική απορρόφηση (ή αποδοχή) των αλλοίων αερίων (αποκλίσεις), της επιθετικότητας και διαφθορικών ουσιών (όξινα, διαλύτες, λιπαντικά, πετρέλαιο κ.λπ.).
- Συντηρείστε να καθαρίζετε τα υποβλήματα τακτικά (από την εμφάνιση). Η χρήση ποτιστικού χημικού παραπορεύει τη διάρκεια (ως 100).
- Είναι σημαντικό να αφαιρέσετε τα υποβλήματα.
- Τα υγρά υποβλήματα δια βήματα να τοποθετούνται σε τμήματα διαφθορικών και της χρήσης, να τα υποβλήματα απορροφούν αλλοιότατα (από διαφθορικούς αλλοιότατα) που αλλοιώνει τους υποβλήματα.

[illegible]

Η διάθεση συλλογιστικής ΕΕ για αυτό το πακέτο βρίσκεται στη διάθεση <https://www.bellota.com>

Bellota Herramientas SLU
C/Urola nº 10 - 20230 Legami

Gureckaa, Spain

Gureckaa, Spain

Bellota Herramientas, S.L.U.

Urola nº 10/20230 Legazpi, Gipuzkoa, Spain
TFL (34)943 73 90 00

FAX: (34)943 73 15 01.
<http://www.bellota.com>

email:comercial@beilofta.com

PARTES DEL CALENDARIO

[illegible]

Curve	Curve grade	T_{500}	GR4
-------	-------------	-----------	-----



9. BARCODES

PAIR BOX	CARTON BOX
8414299026245	8414299026283
8414299026320	8414299026450
8414299026474	8414299026498
8414299026511	8414299026535
8414299026559	8414299026573
8414299026597	8414299026610
8414299026634	8414299026658
8414299026672	8414299026696
8414299026719	8414299026757
8414299026771	8414299026795

 GRAND PROTECTION INT. SAFETY AND WORK SHOES	ARTICLE TECHNICAL SPECIFICATION LS25JCB S2 SRC	CODE	LS25JCB S2 SRC
		REVISION	0
		DATE	02/12/2025

10. TESTS

1.- Before the production starts it's necessary to arrange a Chromium VI test at Intertek laboratory to ensure our products are manufactured without this toxic component. The results must be available before the start of production.

3.- With the first shoes manufactured, the following tests will be carried out in our internal laboratory to verify that the most important quality points are as expected. The following tests are carried out: Upper/Outsole Bond Strength, Midsole Bond, Anti-static, Midsole hardness, Outsole hardness, Outsole density, Outsole Flexing Resistance and Outsole Abrasion Resistance.

The Test Report will be sent immediately to the whole quality team to be analyzed.

11. OTHER