

ESPUNA – QUALITY CONTROL AND INSURANCE

PRODUCT CHART 87037	INFORMATION AND USING INSTRUCTIONS	SPE 003/B Folio 1/1
--------------------------------------	---	--------------------------------------

DESCRIPTION : Knitted glove, 13gauge, made of cut resistant fibres, knitwrist, nitrile foam palm coated .
87037.01 : antistatic gloves

SIZES	6		7	X	8	X	9	X	10	X	11	X	(12)		(13)		standard 9/10
--------------	----------	--	----------	----------	----------	----------	----------	----------	-----------	----------	-----------	----------	-------------	--	-------------	--	----------------------

MARKING



This article is in accordance with the CE directive / 89 / 686: innocuousness, comfort, solidity

It has been the subject of the CE type examination certificate Nr **0075/076/162/05/08/0160**

Given by **CENTRE TECHNIQUE DU CUIR CHAUSSURE MAROQUINERIE** - (n° 0075)

4, rue Hermann Frenkel – F-69367 LYON

STANDARDS REFERENCES

EN 388 (2003) : mechanical risks	
	<i>Abrasion</i> : 4 / 4 <i>Blade cut</i> : 5 / 5 <i>Tear</i> : 4 / 4 <i>Puncture</i> : 2 / 4
EN 420 (2003) : general requirements	
	<i>Dexterity</i> : 5 / 5

These performances are only for the palm

USING INSTRUCTIONS : Protective glove for **handlings sharp objects** in dry and oily environment, exclusively **against mechanical risks**.

Characteristics according to EN 388 :

Each characteristics is classified according to a scale including 4 levels from 1 to 4 (5 for blade cut)..

High level means good protection (0 = level 1 unreached ; X = test unexecuted).

Abrasion : **4**
Blade cut : **5**
Tear : **4**
Puncture : **2**

Levels of performance are obtained with tests executed in environment conditions definite in the standards.

Thus, each use in new conditions are the concern of users responsibility.

These gloves have got a high tensile strength but must not be used when there is a risk of snapping up by machines in movement.

PERSONAL PROTECTIVE EQUIPMENT - CATEGORY II

STORAGE AND MAINTENANCE INSTRUCTIONS : keep sheltered from light and humidity.

Recycling under users responsibility. We do not guarantee the recycled products levels of performance.

espuna®

ESPUNA S.A.S - Route de Luc – 44 rue Ferdinand Buisson - BP 110 - 11205 LEZIGNAN-CORBIERES Cedex - France
Phone : + 33 (0) 4 68 27 05 72 - Fax : + 33 (0) 4 68 27 28 38 – E-mail : info@espuna.fr