



APPLICATIONS

Harnais ht 34

Harnais ht 43 with belt CE01

DESCRIPTION and PRINCIPLE

Harness multiple anchor

1 back anchor forged D

1 sternal anchor forged D

2 thoracic anchor forged D

2 shoulders adjustment

2 legs adjustments

1 Working belt incorporating side « D » for attaching a work positioning lanyard.

Adjustable with quick opening using a single set of buckles.

The back support is made of thermoformed foam.

The inside surface has a sponge type covering.

FEATURES

Side anchoring : 2 « D » rings ZINGED STEEL.

Adjustable with quick opening.

3 sizes,

Lightweight,

Rot-proof.

MODELES

Ht34 S : Small

Ht34 M : Medium

Ht34 XL : Large

TECHNICAL DATA

Size Weight

Manufactured in accordance with

standard EN 358 / EN 361

APAVE n° 0082/352/160/05/97/0087

APAVE n° 0082/352/160/04/97/0158

Double thickness foam back support with closed cells blue exterior, black knitted material inside.

Buckles : STEEL YELLOW ZINC

stamped 2017A, 25 CD4

PES belt, dried thread, width : 45 mm,

automatic stitching : PES thread

APPLICATIONS

Harnais ht 34

Harnais ht43 équipé d'une ceinture de maintien ce01

DESCRIPTION & PRINCIPE

Harnais ancrage multiple

1 ancrage dorsal d forgé

1 ancrage sternal d forgé

2 ancrages thoraciques d forgé

2 réglage de bretelle

2 réglage de cuissard

1 Ceinture comportant 2 D latéraux, permettant l'amarrage d'une longe de maintien.

Réglable de la taille & ouverture rapide

Dosseret en mousse thermoformée , avec sur la face intérieure un revêtement en tissu éponge

CARACTERISTIQUES

Amarrage latéral: deux D ACIER ZINGUE.

Réglage & ouverture rapide.

3 tailles.

Légèreté

Imputrescible

MODELES

Ht34 S : petite taille

Ht34 M : taille moyenne

Ht34 XL : grande taille

SPECIFICATIONS TECHNIQUES

Taille Poids

Conforme: NF EN 358 / EN 361

Attestation d'examen CE de type :

APAVE n° 0082/352/160/05/97/0087

APAVE n° 0082/352/160/04/97/0158

Dosseret mousse double densité, à cellules fermées, bleu à l'extérieur, tissu bouclettes noir à l'intérieur.

Bouclerie: fil: ACIER ZINGUE BICROMATE

découpée: 2017A, 25CD4.

Sangle PES, teintée masse, larg.: 45 mm,

Couture automatique: fil PES