

**MO-185-BL****MO-185-J****MO-185-R****MO-185-B****FIELD OF USE:**

Safety industrial helmet with ARC FLASH integrated face shield.
Shockproof for the head, 1000 V insulating protection of the shell and eyes and face protection of thermal effect due to an arc.

RANGE :

- **MO-185-BL : white shell**
- **MO-185-BLM : white shell and chin strap**
- **MO-185-R : red shell**
- **MO-185-J : yellow shell**
- **MO-185-B : blue shell**

FEATURES:

- **Shell:**
 - IEC 397 - 440V.
 - EN 50365 insulated 1000V AC, 150  DC.
 - High density polypropylene helmet.
 - Head base points to ensure a precise adjustment for a perfect fit and intermediate positions of the face shield.
 - Deformable helmet in case of shock, equipped with a “gutter”.
 - Adjustable size from 52 to 66 cm, adjustment of head rim at 5 mm intervals.
 - 4 points textile head base, adjustable for a perfect fit.
 - Frontal trimming.
 - Textile with « clip » : MO-185-BL.
 - Textile chin-strap with « clip »: MO-185-BLM.
 - Recommended time of use: 5 years

- **Face shield: Retractable face shield**
 - IEC 61482-1-2 class 1 (4kA-500ms – 300mm-Energy 3.48 cal/cm²).
 - GS-ET 29.
 - Large polycarbonate face shield treated anti-scratch and anti-mist.
 - Absorbs >99,9% of harmful UV radiation.
 - 70% light transmission.
 - Face shield totally retractable inside the helmet.
 - Protection against ejections of molten metal (MM).
 - EN 166 / EN 170 : 2-1.2. (U.V).
 - Optical class : 2.
 - Mechanical resistance: B.
 - Protection against electrical arc of short-circuit: 8.
 - Large polycarbonate face shield treated anti-scratch and anti-mist.
 - Face shield totally retractable inside the helmet.

Approximate weight: 736gr

- **Helmet certified  by Certotticca: certificate n° 02041**

SPARE PARTS:

- M-881838: reversible sticker



- M-87384: Protection



- MS-12: lamp 5 Leds

**REPLACEMENT PARTS**

- M-882677 : Replacement visor
- M-882671 : Replacement chin strap
- M-881836 : Replacement headband

