

Elipse P3 R

Das Atemschutzgerät ELIPSE P3 R hat die höchste Klasse für einen Partikelfilter. EN143 fordert eine Filterleistung von mindestens 99,95%. ELIPSE P3 R erreicht eine Leistung von 99,98 % bei 0,3 Mikron.
Das Gerät ist perfekt für den alltäglichen Gebrauch in DIY und Gewerbebau bis hin zu den anspruchsvolleren Umgebungen in der Metallindustrie, Schweißarbeit und Steinbearbeitung.
Ersatzfilter sind erhältlich.

Eigenschaften und Vorteile

- > zugelassen nach der europäischen Norm EN140 : 1998. APF 20
- > Elipse Doppelfilter gebrauchsfertige Halbmaske
- > latex- und silikonfrei, leicht, TPF Gesichtsstück, das bequem für lange Zeit zu tragen ist, niedrige Profilverfilter für ein ungehindertes Sichtfeld
- > Kompatibel mit anderen PSA Schutzausrüstungen einschließlich Visiere und geschweißte Helme



PRODUCT CODE	DESCRIPTION
SPR299	Elipse P3 Respirator S/M
SPR316	Elipse P3 Filter Kit
SPECIFICATIONS	
Product code	SPR316
Description	Elipse P3 replacement twin filters
Materials of construction	Mask Body: TPE (Thermo Plastic Elastomer)
Filter media	HESPA (High Efficiency Synthetic Particulate Air filter)
Pore size (µm)	0.3
Dimension	12 x 94 x 50mm
Weight (g)	Mask + Filter: 132 g, Mask body: 97.6 g
Retention range	99.95% (minimum efficiency)
Ref. standard	CA 29.416, EN140, EN143
Temperature	-5°C +55°C
Notes	Filter P3 - smaller, thinner, more flexible, innovative encapsulation design.
SPR501	Elipse P3 Respirator M/L



