

# NEVADA S3 SRC



FT545001U - Update SR 03-2014

Item code: **545001U**

## DESCRIPTION

- Composite an functional low safety shoes.
- Water-resistant pigmented full grain leather upper with no stitching on the outside surface of the foot and with a lateral retro-reflecting cord.- Lined and padded ankle collar.
- Padded bellows tongue fastening system. Lacing closed metal loops.
- Breathable honeycomb-type mesh lining.
- Ventilated and ergonomic insole.
- Lightweight and large safety 200-joule toe cap (athermal and non-magnetic).
- Flexible, lightweight and composite anti-perforation sole (athermal and non-magnetic).
- PU2D sole assembly with an overcap.

## SHOE SIZE

- 38 to 47

## USE

- Multi-use low safety shoes.

## WEIGHT

- Shoe size 42 : 1150g

## MAINTENANCE / STORAGE

- Clean. brush and polish.
- Store in a cardboard box in a dry location at a normal temperature.

## EC DECLARATION OF CONFORMITY

- Certified under reference 545001U NEVADA according to ISO standard EN ISO 20345 : 2011.
- Résultats :
  - S3 Backfoot area enclosed - antistatic properties.  
Shock absorption in the heel.  
Resistance to water penetration and water absorption.  
Cleated sole.  
Protective midsole against perforation up to 1.100 N.
  - SRC Slip-resistant sole.
- EC certificate N°0161/20793/13 of the 2th décembre 2013 granted by the CIMAC laboratory (0465).

| Résistance au glissement SRC selon tests EN13287 et norme EN ISO 20345:2004/A1:2007 |                                                  |                                       |                                                  |     |
|-------------------------------------------------------------------------------------|--------------------------------------------------|---------------------------------------|--------------------------------------------------|-----|
| SRA<br>Céramique + détergent                                                        |                                                  | SRB<br>Acier + glycérine              |                                                  | SRC |
| Mini standard<br>when flat $\geq 0,32$                                              | Min standard at<br>the heel at 7°<br>$\geq 0,28$ | Min standard<br>when flat $\geq 0,18$ | Min standard at<br>the heel at 7°<br>$\geq 0,13$ |     |
| 0.41                                                                                | 0.31                                             | 0.21                                  | 0.18                                             | SRC |