



## **VD PRO 1500 SF**

Safety shoe EN ISO 20345:2011 S3 SRC

Sizes: 36 - 50 (225 - 322)

- + Light-weight microfibre, seamless shoe design
- + Dust flap
- + Shaft applications
- + Aluminum toe cap
- + Highly flexible, metal-free puncture resistance SECURA FLEX

Fitting Options: NB, XB (S, XXB)

- + Breathable, functional lining
- + Comfort Insole ERGO-SOFT ESD

## TPU Athletic ESD, light-blue

- + Outsole with a profile of 3,5 mm
- + With increased protection against twisted ankles, reduced lever arms
- + Supports the natural movement
- + Light and flexible
- + Very good scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 120° C




## Multiflex® Technology

Lever arms of the shoe force the foot to make unnatural movements and can lead to foot and Achilles tendon complaints, knee pain and back problems. Furthermore, lever arm forces can increase the risk of injuries such as sprained ankles. Lever arm reduced shoes are characterized by lower heel heights, increased insertion depth, softer material and lesser thickness of the sole, which is rounded in the peripheral areas. A result of the Multiflex® technology is the multiflexible outsole.

























Aluminum


toe cap



















Subject to technical modifications.

Different soles may be used for extreme sizes.

