

MODEL



VX 749 Bau Perbunan

Safety shoe EN ISO 20345:2011 S3 SRC HRO

FEATURES

Sizes: 38 - 48/49 (240 - 315)

Fitting Options: NB, XB (S, XXB)

- + Full-grained smooth leather
- + Dust guard tongue
- + Toe guard
- + Reflective applications
- + Breathable, functional lining

- + Leather insole
- + Comfort insole ERGO-COOL®

OUTSOLE

Perbunan VX, blue-grey

- + Outsole with a profile of 3,8 mm
- + Flexion zone with pivot point
- + Hard-wearing and excellent cut resistance
- + Broad contact surface
- + Best possible scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 220° C



CUSHIONING

SECURA VARIO® System

The replaceable, weight and pressure dependent heel shock absorption system ensures cushioning adapted to the individual needs of the wearer. The pressure load in the shoe is reduced to a natural extent and provides targeted relief to the back. At the same time, it helps to significantly reduce fatigue and increases the ability to compensate pressure loads by the leg and trunk musculature.

- above 105 kg
- up to 105 kg
- up to 91 kg
- up to 79 kg
- up to 57 kg



Certified and recommended by Association
Forum Healthy Back - Better living and
Federal Association of German Back Schools.

More information:
AGR e. V. · P.O. Box 103 · D-27443 Selsingen
Phone +49 4284 92 69 990 · www.agr-ev.de



KEY

- | | | | |
|---|-------------------------------------|--|---|
| Original multi-width system | STEITZ FLEX-ZONE® with flexion zone | Highly flexible, metall free puncture resistance | Leather-Insole |
| VARIO® Multiflex technology | Aluminum toe cap | Protection against electrostatic discharge | Certified for german insole treatment |
| VARIO Vitality® multi-zone shock absorption | Steel toe cap | Fire fighter boot according to EN 15090 | GORE-TEX® membrane, waterproof and breathable |
| SECURA VARIO® heel shock absorption | Composite toe cap | Warm winter lining, good thermal insulation | Subject to technical modifications.
Different soles may be used for extreme sizes. |
| SECURA CARE heel cushioning | Puncture resistant steel midsole | Cut protection tested according to EN ISO 17249 | |

STEITZ SECURA
SAFETY FOOTWEAR