

MODEL



VX 7750 ESD S3

Safety boot EN ISO 20345:2011 S3 SRC CI HRO

FEATURES

Sizes: 36 - 48/49 (225 - 315)

- + Full-grained smooth leather
- + Dust guard tongue
- + Toe guard
- + Shaft applications
- + Cushioned collar
- + Aluminum toe cap

Fitting Options: NB, XB (S, XXB)

- + Puncture-resistant steel midsole
- + Breathable, functional lining
- + Leather insole
- + Full-length, removable insole ERGO-SOFT ESD with additional cushioning effect and excellent moisture transportation

OUTSOLE

Perbunan Dynamics ESD, anthracite-grey

- + Outsole with a profile of 2,6 mm
- + Light and flexible with tailored arch support
- + Flexion zone with pivot point
- + Cushioning structure in the heel area
- + Best possible scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 220° C



CUSHIONING

VARIO Multiflex® Technology

Lever arms of the shoe force the foot to make unnatural movements and can lead to foot and Achilles tendon complaints, knee pain and back problems. Furthermore, lever arm forces can increase the risk of injuries such as sprained ankles. Lever arm reduced shoes are characterized by lower heel heights, increased insertion depth, softer material and lesser thickness of the sole, which is rounded in the peripheral areas. A result of the VARIO Multiflex® technology is the multiflexible outsole.

- above 105 kg
- up to 105 kg
- up to 91 kg
- up to 79 kg
- up to 57 kg



Certified and recommended by Association
Forum Healthy Back - Better living and
Federal Association of German Back Schools.

More information:
AGR e. V. · P.O. Box 103 · D-27443 Selsingen
Phone +49 4284 92 69 990 · www.agr-ev.de



KEY

- | | | | |
|---|-------------------------------------|--|--|
| Original multi-width system | STEITZ FLEX-ZONE® with flexion zone | Highly flexible, metall free puncture resistance | Certified for german insole treatment |
| VARIO® Multiflex technology | Aluminum toe cap | Protection against electrostatic discharge | GORE-TEX® membrane, waterproof and breathable |
| VARIO Vitality® multi-zone shock absorption | Steel toe cap | Fire fighter boot according to EN 15090 | |
| SECURA VARIO® heel shock absorption | Composite toe cap | Warm winter lining, good thermal insulation | |
| SECURA CARE heel cushioning | Puncture resistant steel midsole | Cut protection tested according to EN ISO 17249 | Subject to technical modifications. Different soles may be used for extreme sizes. |

STEITZ SECURA