# **EVOLite<sup>®</sup>**

### **ID HOLDER- WHEEL RATCHET - VENTILATED - CR2**

THE JSP EVOLITE® HELMET FEATURING THE NEW ID HOLDER ALLOWING EASY IDENTIFICATIONS OF PERSONNEL ON SITE

# **SPECIFICATION**

**TECHNICAL** 

SHELL:

High strength engineering grade ABS which has been UV Stabilised

### **HEAD PROTECTION**

### **INSTRUCTIONS FOR USE**

**WEBBING HARNESS:** 

HDPE Strap & Webbing Clips

with Polyester Webbing Straps

Fit helmet on head and fasten strap to ensure fit

For adequate protection this helmet must be worn with peak facing forward

Ensure the helmet is adjusted to the size of the user's head



### **CHAMLON™ SWEATBAND:**

Egyptian cotton core with porous PU coating for maximum sweat absorption. PH neutral, dermatologically tested

#### **CR2 REFLECTIVE:**

High Intensity Reflective offering, on average, 60% more reflectivity than standard reflective clothing material



#### WHEEL RATCHET:

The Revolution® Wheel Ratchet RE is the new easy to use wheel ratchet adjustment system to create a firm comfort fit with added security

**ID HOLDER:** 

Fully waterproof card holder with easy visibility and quick interchanging of cards from the simple push and slide mechanism. Accommodate standard UK (85 x 55mm) and US (89 x 51mm) business cards



evolution lite

### CONFORMITY

EN 397 for Industrial Safety Helmets EC Certificate Number 00279, issued by BSi Product Certification

Meets optional Lateral Deformation performance

Meets optional Molten Metal Splash performance

Wide size range. Slip or wheel ratchet - High comfort fit

Available vented. Available with mid or micro peak

Company personalisation available by printing



EVOLite CR2 is the biggest step-up in night time visibility/ reflectivity of head protection to date

Meeting reflective performance requirements of EN12899-1 (High performance reflective sign face material)



MANUFACTURING FOR SAFETY <u>www.jsp.co.uk</u> 





# 

### **ID HOLDER- WHEEL RATCHET - VENTILATED - CR2**

HEIGHT: 450mm

THE JSP EVOLITE® HELMET FEATURING THE NEW ID HOLDER ALLOWING EASY IDENTIFICATIONS OF PERSONNEL ON SITE

# TECHNICAL SPECIFICATION

### **HEAD PROTECTION**

**DIMENSIONS OF OUTER PACKAGING** 

Quantity: 10

4.1kg (Approx.) Weight:



### **DIMENSIONS OF HELMET**

Size: 530 - 640mm

Weight: 363g (Approx.)

# **CLEANING & MAINTENANCE**

The unit may be cleaned with soap and warm water and dried with a soft cloth

The helmet should not be cleaned with chemical or abrasive cleaners

The helmet should be stored out of direct sunlight

The helmet should be stored away from chemicals and extremes of temperature



### **HELMET COLOURS**



**UKSALES@JSP.CO.UK** 



### **HELMET FEATURES**

| EN<br>STANDARD            | EN397<br>EN12899-1  | Yes<br>Yes                     |
|---------------------------|---|--------------------------------|
| PERFORMANCE               | Impact Resistance<br>Lateral Deformation  | Yes 50 Joules<br>Yes           |
| TEMPERATURE<br>RESISTANCE | Molten Metal (MM)<br>+50°C<br>-30°C   | Yes<br>Yes<br>Yes              |
| SHELL<br>MATERIAL         | ABS<br>Recyclable<br>UV Stabilised  | Yes<br>Yes<br>Yes              |
| HARNESS<br>MATERIAL       | HDPE<br>Textile   | Yes<br>Yes                     |
| OPTIONS                   | Universal Accessories<br>Reflective CR2 option<br>Integrated Eyewear<br>ID Holder | Yes<br>Yes<br>Yes<br>Yes       |
| HARNESS SYSTEM<br>OPTIONS | JSP 3D<br>Slip Ratchet<br>6 pts   | Yes<br>Yes<br>Yes              |
| CHINSTRAP<br>OPTIONS      | 4 pts<br>2 pts  | Yes<br>Yes                     |
| LOGO<br>OPTIONS           | Front<br>Rear<br>Side<br>MOQ Logo<br>Individual Name                              | Yes<br>Yes<br>Yes<br>10<br>Yes |

# **LIMITATIONS OF USE**

 $(\Theta)$ 

Protection will only be offered if the helmet is fitted correctly

Any helmet subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer

The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice

The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer

 $(\mathcal{O})$ 



**MANUFACTURING FOR SAFETY** WWW.JSP.CO.UK

TEL: +44 (0)1993 826050