EVO2®

MID PEAK - SLIP RATCHET - NON-VENTILATED

PRODUCT CODE: AJE030-000-_00

THE EVO2® OFFERS THE MOST ECONOMICAL TOP LEVEL PROTECTION

TECHNICAL SPECIFICATION

HEAD PROTECTION

SHELL: UV Stabilised High Density

Polyethylene (HDPE)

INSTRUCTIONS FOR USE

Fit helmet on head and fasten strap to ensure fit

For adequate protection this helmet must be worn with peak facing forward

Ensure the helmet is adjusted to the size of the user's head

CHAMLON™ SWEATBAND: Egyptian cotton core with porous PU coating for maximum sweat absorption. PH neutral, dermatologically tested

SLIP RATCHET: One Touch[™] Slip Ratchet version of the EVO2® is so simple to fit that it can be adjusted with just one finger







CONFORMITY

| Conforms to EN397 & FOCT P 50460-92 |
|---|
| EN 50365 for Helmets for use in low voltage installations |
| EC Certificate Number 0279, issued by BSi Product Certification |
| Low dome profile |
| Helmet offers electrical insulation |
| Compatible with other JSP safety products |
| Available in a choice of colours |
| Company personalisation available by printing |

CLEANING & MAINTENANCE

The unit may be cleaned with soap and warm water and dried with a soft cloth

The helmet should not be cleaned with chemical or abrasive cleaners

The helmet should be stored out of direct sunlight

The helmet should be stored away from chemicals and extremes of temperature



MANUFACTURING FOR SAFETY WWW.JSP.CO.UK

UKSALES@JSP.CO.UK TEL: +44 (0)1993 826050



EV02®

MID PEAK - SLIP RATCHET - NON-VENTILATED

PRODUCT CODE: AJE030-000-_00

THE EVO2® OFFERS THE MOST ECONOMICAL TOP LEVEL PROTECTION

TECHNICAL SPECIFICATION

HEAD PROTECTION

DIMENSIONS OF OUTER PACKAGING

Quantity: 10 Weight: 3.8kg (Approx.)



DIMENSIONS OF HELMET

Size: 530 - 640mm Weight: 350g (Approx.)



HELMET COLOURS

Insert the following two digit number in place of the dashes in the product code of your desired helmet



| | SP | |
|------|----|--|
| ALS. | | |

HEIGHT: 450mm

HELMET FEATURES

| EN STANDARD | EN397 EN50365 | Yes Yes | |
|---------------------------|---|--|--|
| PERFORMANCE | Impact Resistance Electrical Insulation | Yes 50 Joules Yes: EN397 440V EN50365 1000V | |
| TEMPERATURE RESISTANCE | Low Temperature | Yes: EN397 -30°C FOCT P 50460-92 -30°C | |
| SHELL MATERIAL | HDPE Recyclable UV Stabilised | Yes Yes Yes | |
| HARNESS MATERIAL | HDPE LDPE | Yes Yes | |
| OPTIONS | Universal Accesories Reflective CR2 option Integrated Eyewear | Yes Yes Yes | |
| HARNESS SYSTEM OPTIONS | JSP 3D Slip Ratchet 6 pts | Yes Yes Yes | |
| CHINSTRAP | 4 pts | Yes | |
| LOGO OPTIONS | Front Rear Side MOQ Logo Individual Name | Yes Yes 10 Yes | |

LIMITATIONS OF USE

Protection will only be offered if the helmet is fitted correctly Any helmet subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice

The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer



Y UKSALES@JSP.CO.UK TEL: +44 (0)1993 826050