



40 CAL Arc Flash PPE

Salisbury Arc Flash Lift Front Hoods

- 40 cal/cm² ATPV ratings
- Made from arc flash resistant material
- Includes the most transparent lens available
- 40 Calorie Polycarbonate dual lens, anti-fog and abrasion resistant
- Chin Guard Transparent chin protector with trigger mechanism
- Sewn with Nomex® thread (extremely heat resistant/does not melt)
- FR hook and pile attaches shroud to shield assembly
- Hard hat is included
- One size fits all
- Meets ASTM F2178 and NFPA 70E standards and the flammability requirements for ASTM F1506
- Complies with NFPA70E HRC4*

Part No	LFH40PLT
Material	40 cal Premium Light Weight, 2 layer, 5oz/yd2
Weight	1kg
Measurements	510mmH x 270mmW x 280mmD
Viewing Area	190mm x 510mm

Features

Comfort

- Total fabric weight of 11 oz/yd2 compared to 18.5 oz/yd2
- makes this suit the lightest in the industry
- Lighter fabric allows for added ease of movement
- Keeps user cooler longer than a standard HRC 4 suit
- Adjustable gussets on overall cuffs allow for a more comfortable fit

Safety

- Longer coat creates better body coverage
- Complies with NFPA 70E HRC4
- Meets ASTM F1506-02A
- Meets ASTM F1959M/F1959M-99
- Arc Rated for the life of the garment
- Heat Attenuation Factor of 93.20%, meaning garment is not only flame

PRO WEAR™ Arc Flash Kits

- Arc Flash Coat
- Arc Flash Bib Overalls
- Arc Flash Pro-Hood/Lift Front Hood
- Hard Hat
- Bag
- Safety Glasses
- Sizes S 3XL
- Complies with NFPA70E HRC4*

*Important: NFPA 70E does not have a Hazard Risk Category above 40 cal/cm². Working on levels above 40 cal/cm² should be avoided because of the blast hazards caused by arc flash.

Part No	Cal/cm² Rating	Colour & Material
SK40PLT*	40 cal/cm ²	Premium Light Weight with Hood
SK40PLT*-LFH40	40 cal/cm ²	Premium Light Weight with Lift Front hood
^Add suffix for desired size S M L XL 2XL or 3XL. Contact TEN for a sizing chart		



The Energy Network (Australia) Pty Ltd ABN 72 093 052 441 www.lengroup.com.au

WORKSHO

0408 228 47 WORKSHO

WORKSH



NSW/ACT

www.tengroup.com.au