

TIG15K



WELDER'S LEATHER GLOVE / 15 CM GAUNTLET.

Ref. TIG15K



Product specifications

Goatskin full grain leather. Cowhide split leather cuff. Kevlar® Technology sewn. American assembly. 15 cm cuff. Length: 35 cm.

Full grain goatskin.
Split cowhide leather.
Kevlar® Technology sewn.
Thickness of between 0.8 and 1.0 mm.

COLOUR

Grey

SIZE

08, 09, 10

Product Use - Risks



Heat



Wearing



Heavy industry

Product's highlights & user's benefits



Heat resistant welder gloves:

- Very good mechanical resistance
- Flame resistant, heat resistant and big molten metal spray

Goatskin leather :

- Flexibility, dexterity
- Very good mechanical resistance

Certifications and Standards



RÈGLEMENT (UE) 2016/425

EN420:2003+A1:2009 General requirements

4: Dexterity (from 1 to 5)

EN388:2016



2: Resistance to abrasion (from 1 to 4)

1: Resistance to cutting (from 1 to 5)

1: Resistance to tear (from 1 to 4)

1: Resistance to puncture (1 to 4)

X: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)

EN407:2004 Protective gloves against Heat & Fire risks (X = Unrealized test)



4: Resistance to flammability (from 1 to 4)

1: Resistance to contact heat (from 1 to 4)

X: Resistance to convective heat (from 1 to 4)

X: Resistance to radiant heat (from 1 to 4)

4: Resistance to small projections of liquid metal (from 1 to 4)

X: Resistance to large projections of molten metal (from 1 to 4)

EN12477:2001/A1:2005 Protective gloves for welders

TYPE B: Welding - High dexterity required Type B

References

References	Bar code	COLOUR	SIZE		
TIG15K08	3295249033965	Grey	08	36	6
TIG15K09	3295249033972	Grey	09	36	6
TIG15K10	3295249033989	Grey	10	36	6