

# TER250



# HEAT-RESISTANT COWHIDE WELDER'S GLOVE

Ref. TER250





# Product specifications

Heat-resistant cowhide split leather palm (HR). Wool fleece lining on palm. Cuff with canvas lining. Kevlar® Technology sewn. American assembly. 20 cm cuff. Length: 40 cm.

Heat-resistant treated split cowhide leather. Thickness between 1.2 and 1.4 mm.

Cuff: Split cowhide.

Lining: wool.

Kevlar® thread.

#### **COLOUR**

Brown-Grey

#### SIZE

10

## Product Use - Risks





Cutting / Perforation









# Product's highlights & user's benefits





Heat-resistant leather (HR):

- Better Resistance to contact heat
- Reduction of the reactivity on flames contact
- Flexible leather

Kevlar® seams

## Certifications and Standards



## **RÈGLEMENT (UE) 2016/425**

### EN420:2003+A1:2009 General requirements

1: Dexterity (from 1 to 5)

## EN388:2016 Gants contre les risques Mécaniques (Niveaux obtenus sur la paume)



- 3: Resistance to abrasion (from 1 to 4)
- 2: Resistance to cutting (from 1 to 5)
- 4: Resistance to tear (from 1 to 4)
- 3: Resistance to puncture (1 to 4)
- X: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)

# EN407:2004 Protective gloves against Heat & Fire risks (X = Unrealized test)



- 4: Resistance to flammability (from 1 to 4)
- 1: Resistance to contact heat (from 1 to 4) 3: Resistance to convective heat (from 1 to 4)
- X: Resistance to radiant heat (from 1 to 4)
- 4: Resistance to small projections of liquid metal (from 1 to 4)
- X: Resistance to large projections of molten metal (from 1 to 4)

#### EN12477:2001/A1:2005 Protective gloves for welders

TYPE A: Welding - Other welding processes - less dexterity - Type A



References					
References	Bar code	COLOUR	SIZE	•	<b>~</b>
TER25010	3295249157722	Brown-Grey	10	60	6