



**TEGERA® INFINITY 8815**



[Learn more](#)

**OUR THINNEST NITRILE DIPPED CUT F**

Dexterous cut resistant glove with highest cut level F, suitable for precision work. Ultra light thanks to 18 gg knitted with CRF® Omni cut resistant technology. Palm dipped with super soft nitrile foam that provides excellent grip on dry surfaces. Reinforced thumb crotch for improved longevity. Breathable materials for all day comfort. Wide range of sizes means a perfectly fitting glove for everyone. Skin friendly with Derma-test and Oeko-Tex certificate.

**CHARACTERISTICS**

- Highest level of protection
- Good fingertip sensitivity
- Extra flexible
- Durable
- Good grip
- Extra comfortable

**FUNCTIONS**

- Withstands contact heat up to 100°C
- Approved for handling foodstuffs
- Reinforcement between index finger and thumb
- Ultra thin
- Super soft



**PREVENTS RISK OF**

Cut injuries, Abrasion injuries, Blisters, Grazes, Scratches, lacerations, Contact with dirt

**PRIMARY ENVIRONMENTS OF USE**

Cut risk environments, Dry environments, Moist environments, Dirty environments

**PRIMARY AREAS OF USE**

Assembly, Building and construction, Carpentry, Engineering, Fine assembly, Glass industry work, Machine driving, Machine operating, Metalwork, Paper industry work, Repair work, Sheet-metal work

**PRIMARY INDUSTRIES OF USE**

Pulp and paper, Rubber and plastic, Glass, bricks, concrete, Metal fabrication, Machinery and equipment, MRO, Automotive, Transportation, Utilities, Building and construction, Logistics, Retail

**TYPE OF WORK**

Medium weight

**SPECIFICATION**

**TYPE** Cut resistant gloves, Heat protection gloves

**CATEGORY** Cat. II

**COLLECTION** Infinity

**KNITTING GAUGE (GG)** 18

**LINING MATERIAL** CRF® Omni Technology, HPPE, Nylon, Spandex

**LENGTH** 220-270 mm

**DEXTERITY** 5

**GRIP DESIGN** Foam grip pattern

**COLOUR** Black

**PAIRS PER: BUNDLE/CARTON** 6/120

**DISPLAY TYPE** Bulk pack

**DIPPING** Palm-dipped

**DIPPING MATERIAL** Nitrile foam

**CUFF STYLE** Knitwrist cuff

**CUFF MATERIAL** Textile

**CUT RESISTANCE (EN ISO 13997)** Cut resistance level F

**CUT RESISTANCE (EN ISO 13997) TDM:** 31.2N

**INNER MATERIAL SPECIFICATION** HPPE (High performance polyethylene), Nylon, Tungsten fibre thread, Elastane

**OUTER MATERIAL SPECIFICATION** Nitrile

**COMPLIANCE**



TP TC 019:2011



EN ISO 21420:2020



EN 388:2016+A1:2018 4X43F



EN 407:2020 (No flame protection) X1XXXX



STANDARD 100 SE 14-214 RISE



Contact heat rating valid for palm area only

**FEATURES**



Cut protection

SIZE		ARTICLE NUMBER	EAN
10	XL	8815-10	7340118371320
11	XXL	8815-11	7340118371412
12	3XL	8815-12	7333506023871
6	X5	8815-6	7340118370965
7	S	8815-7	7340118371054
8	M	8815-8	7340118371146
9	L	8815-9	7340118371238

**ejendals**

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com