# **TEGERA**<sup>®</sup>



## **TEGERA**<sup>®</sup> INFINITY 8807



### SUPER SOFT, THIN GLOVE, CUT LEVEL D

Dexterous, thin glove with cut resistant level D, suitable for fine assembly work. 15 gg knitted with CRF<sup>°</sup> cut resistant technology. Palm dipped with super soft nitrile foam that provides excellent grip on dry surfaces. Reinforced thumb crotch for improved longevity. Breathable materials for all day comfort. Protection against contact heat up to 100°C/212°F. Wide range of sizes means a perfectly fitting glove for everyone. Skin friendly with Derma-test and Oeko-Tex certificate.

CHARACTERISTICS	FUNCTIONS	
High level of protection	<ul> <li>Withstands contact heat up to 100°C</li> </ul>	
<ul> <li>Good fingertip sensitivity</li> </ul>	<ul> <li>Approved for handling foodstuffs</li> </ul>	
Good grip	• Thin	
Extra comfortable	<ul> <li>Reinforcement between index finger and</li> </ul>	
Flexible	thumb	
Durable		



#### PREVENTS RISK OF

Cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping

#### PRIMARY ENVIRONMENTS OF USE

Cut risk environments, dry environments, moist environments, dirty environments

#### PRIMARY AREAS OF USE

Fine assembly, assembly, machine operating, building and construction, carpentry, installation work, hvac installation, sheetmetal work, engineering, transport work, machine driving, warehouse work, airport work, metalwork, glass industry work, repair work, paper industry work, service work, shop work

#### PRIMARY INDUSTRIES OF USE

Pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, mro, automotive, transportation, utilities, building and construction, logistics, facilities, service, retail

#### **TYPE OF WORK**

Medium weight

#### SPECIFICATION

TYPE Cut resistant gloves, Heat protection gloves CATEGORY Cat. II **COLLECTION** Infinity LINING MATERIAL 15 gg, CRF<sup>®</sup> Technology, Glass fibre thread, HPPE, Nylon, Spandex LENGTH 205-265 mm **DEXTERITY** 5 **GRIP DESIGN** Foam grip pattern **COLOUR** Black, Yellow PAIRS PER: BUNDLE/CARTON 6/120 **DISPLAY TYPE** Bulk pack **DIPPING** Palm-dipped DIPPING MATERIAL Nitrile foam, Waterbased PU **CUFF STYLE** Knitwrist cuff **CUFF MATERIAL** Textile CUT RESISTANCE (EN ISO 13997) Cut resistance level D CUT RESISTANCE (EN ISO 13997) TDM: 17N INNER MATERIAL SPECIFICATION HPPE (High performance polyethylene), Nylon, Glass fibre thread, Elastane **OUTER MATERIAL SPECIFICATION** Nitrile

# COMPLIANCE



TP TC 019:2011



4X43D

ויק

FAL





EN 420:2003 +A1:2009



 $\mathbf{a}$ 

#### OEKO TEX® STANDARD 100 SE 14-214 RISE



#### Contact heat rating valid for palm area only

#### FEATURES



	SIZE		ARTICLE NUMBER	EAN
	5	XXS	8807-5	7340118328232
	6	XS	8807-6	7340118319650
	7	S	8807-7	7340118319667
	8	М	8807-8	7340118319674
	9	L	8807-9	7340118319681
	10	XL	8807-10	7340118319636
	11	XXL	8807-11	7340118319643



Limavägen 28, SE-793 32 Leksand, Sweden Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com