

AIR SCRATCH S1P SRC ESD



Poromax® lining



AIR SCRATCH ORANGE



AIR SCRATCH LADY AUBERGINE

EN ISO 20345 SAFETY FOOTWEAR

SB : Basic requirement (innocuousness, comfort, strength, resistance to shocks hazards & compression 200 J)

S1 : SB + closed back + A + E + FO

S1P : S1 + P

S2 : S1 + WRU

S3 : S2 + P + studded sole

MARKING

A : Antistatic footwear

AN : Ankle protection

CI : Insulation against cold

E : Energy absorption in the heel region

ESD : Electro Static Discharge

FO : Resistance to fuel oil of outsole

HI : Insulation against heat

M : Metatarsal protection

P : Penetration resistance

SRA : Slipping resistance on ceramic tile wet with dilute soap solution

SRB : Slipping resistance on smooth steel with glycerol

SRC = SRA + SRB

WR : Water resistant

WRU : Water resistant upper

HRO : Heat resistant outsole 300°C

Model	Item code	Standard	Marking	EUR Sizes	UK Sizes	US Sizes	Net weight/pair (kg) (42 = men) (38 = ladies)
AIR SCRATCH AUBERGINE	AFBV1	EN ISO 20345 2011	S1P SRC ESD	36/42	3,5/9	5,5/11	1
AIR SCRATCH ORANGE	AHBV1			39/47	3,5/9	6/12,5	1,08

SOLE

- Textile antiperforation midsole
- Extra light PU dual density
- High performance grip: SRC

ENVIRONMENT

- Industry, transport & logistics
- Services

UPPER

- 240J composite toecap
 - 3D Mesh for upper ventilation and printed PU leather at the front & back of the shoe for protection
 - Heel grip
 - Poromax® lining: antibacterial
- 100% ventilated & high water-absorbing capacity
high resistance to abrasion, foot-hygienic proof.

FOCUS

- ESD: ElectroStatic Discharge (IEC EN 61340-5-1)
Static electricity absorption
- Metal free (airport friendly safety shoe)
- Flexible materials and dynamic design
- ‘LADY’ models: the shoe last is specific to a women’s foot shape.

