








Product Family

BACOU ORIGINAL FREE

- The Bacou Original Free range is recommended for industry, building and construction. All models are 100% non metallic protection and comply with the EN ISO 20345 : 2011 standard.

Honeywell

Product Numbers & Ordering Information

	Product Numbers	Details
	6246155	BACOU TRACK AMG S3 CI SRC Water resistant oiled leather ankle boot. PU2D outsole injected. SRC certified. 200J Spacium™ toe cap in injected polymer. Flexium™ non metallic anti-puncture sole. Complies with EN ISO 20345:2011 standard. From 38 to 47
	6246156	BACOU MARSH AMG S3 CI SRC Water resistant oiled leather shoe. PU2D outsole injected. SRC certified. 200J Spacium™ toe cap in injected polymer. Flexium™ non metallic anti-puncture sole. Complies with EN ISO 20345:2011 standard. From 38 to 47
	6246157	BACOU PEAK AMG S3 CI SRC Water resistant oiled leather ankle boot with black textile panels. PU2D outsole injected. SRC certified. 200J Spacium™ toe cap in injected polymer. Flexium™ non metallic anti-puncture sole. Complies with EN ISO 20345:2011 standard. From 35 to 49
	6246158	BACOU CREEK AMG S3 CI SRC Water resistant oiled leather shoe with black textile panels. PU2D outsole injected. SRC certified. 200J Spacium™ toe cap in injected polymer. Flexium™ non metallic anti-puncture sole. Complies with EN ISO 20345:2011 standard. From 35 to 49
	6246159	BACOU SUMMIT AMG S1P SRC Perforated grey suede leather shoe with black textile panels. PU2D outsole injected. SRC certified. 200J Spacium™ toe cap in injected polymer. Flexium™ non metallic anti-puncture sole. Complies with EN ISO 20345:2011 standard. From 35 to 49



6246160

BACOU CROSS AMG S1P SRC

Perforated grey suede leather ankle boot with black textile panels. PU2D outsole injected. SRC certified. 200J Spacium™ toe cap in injected polymer. Flexium™ non metallic anti-puncture sole. Complies with EN ISO 20345:2011 standard. From 35 - 49



6246161

BACOU EAGLE AMG S1P SRC

Water resistant perforated oiled leather sandal. PU2D outsole injected. SRC certified. 200J Spacium™ toe cap in injected polymer. Flexium™ non metallic anti-puncture sole. Complies with EN ISO 20345:2011 standard. From 35 to 49

Additional Information

- The Bacou X'Max Black Insole (ref 6000350) can be sold separately. Available from 1 unit (by pair) in an individual packaging

Overview

Recommended Industries/Use

- Construction
- Manufacturing
- Oil and Gas
- Utilities
- Wind Energy

Hazards

- Abrasion
- Impact
- Slip
- Splash

Regulations

- EN ISO 20345:2011 -

Historical Brand

- BACOU

Specifications

100% non metallic range

- Comfort, durability and flexibility

FLEXIUM Non-metallic anti-puncture midsole

- The midsole is light and flexible. No constraints for the wearer when flexing the foot. Antistatic and comfortable

200J Spacium™ non metallic toe cap

- Light, non magnetic, thermal insulator, unalterable and suits all foot types

High performance PU2D outsole injected, SRC certified

- Resistance and Flexibility. High slip resistance and with marked heel

Literature & Documents

User Instruction EN ISO 20345 2011-Footwear-Honeywell-032012

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Footwear/4294983585/1033.aspx