



REVENGER 7TR06

S3 HRO SRC
EN ISO 20345:2011
38 to 47

High shoe
All terrain style



STARK®



- ⊗ Black safety boot, all-terrain hiking style .
- ⊗ Water-repellent full-grain leather upper. Thickness 1.9/2.1mm.
- ⊗ Protective **STARK®** scuff cap reinforcement to vamp. Reinforce the boot and prolong its life under hostile working conditions.
- ⊗ **3D.LINING®** in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- ⊗ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- ⊗ Ergonomic padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- ⊗ Padded and lined leather tongue for instep protection with side bellows to keep out dust and dirt.
- ⊗ Lace up on 4 pairs of lace stays and 1 pair of open hooks. Laces 150 cm.
- ⊗ Complete **CONFORT PLUS®** inlay, antistatic and anatomically shaped in flexible polyurethane covered in breathable, absorbent fabric.
- ⊗ Stab-proof non-metallic **FLEX-SYSTEM® zéro** liner : total protection of the sole of the foot.
- ⊗ **LIGHT-PLUS®** protective toecap in synthetic material offering protection from an impact of 200 J.

Slip resistance EN ISO 20345:2011
Qualité SRC (SRA+SRB)

SRA Test ground/Ceramic/lubricant
Water and detergent

On flat **0,40** (>0,32) - On the heel **0,31** (>0,28)

SRB Test ground : steel/lubricant
Glycerine

On flat **0,29** (>0,18) - On the heel **0,21** (>0,13)

KOMPACT VIBRAM® sole, designed and tested by Vibram®, made in high performance rubber compound to obtain A superb adherence and grip, the optimal durability and an avant-garde design.

Designed to face rough terrains, harsh environments, often in difficult weather conditions, this sole offers the best grip and reliability even on most demanding surfaces. Contact heat-resistance up to 300° C.



Weight	Gross weight (42) : 1550 g / Net weight (42) : 1380 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Dimensions	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350
Dimensions boites (mm)	306 x 192 x 114		340 x 210 x 133	