

JALAS® 7148 ZENIT EVO

EN ISO 20345:2011, S3, SRC

PROPERTIES

Excellent grip, perfect fit, extra comfortable, very breathable, excellent shock absorption, extremely light

SPECIFICATION

TYPE OF SHOE Safety footwear, low shoes

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Regular

SIZE RANGE (EU) 35-48

PLATFORM Custom

UPPER MATERIAL Textile

UPPER MATERIAL THICKNESS 1,8-2,0

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester

SOLE MATERIAL PU midsole, plastic shank, RPU outsole

INSOLE FX3 Supreme

INSOLE MATERIAL Textile, soft EVA, rigid EVA, polyester-based conductive thread, neo foam, double shock absorption zones in Poron® XRD®

FASTENING Laces

COLOUR Black



ZENIT EVO
COLLECTION

SIZE	ART. NO.	EAN NO.	SIZE	ART. NO.	EAN NO.
35	7148-35	6408487508332	47	7148-47	6408487508455
36	7148-36	6408487508349	48	7148-48	6408487508462
37	7148-37	6408487508356			
38	7148-38	6408487508363			
39	7148-39	6408487508370			
40	7148-40	6408487508387			
41	7148-41	6408487508394			
42	7148-42	6408487508400			
43	7148-43	6408487508417			
44	7148-44	6408487508424			
45	7148-45	6408487508431			
46	7148-46	6408487508448			

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



JALAS® 7148 ZENIT EVO

FEATURES

Low weight, oil-resistant outsole, anti-static properties, bellows tongue, padded shaft edge in memory foam, ventilating insole, water repellent, ergonomically shaped, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic, slipping

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, environments with risk for outsole penetration, dry environments, clean environments

2(3)



Aluminium toecap



Nail protection in plasma-treated composite (PTC) textile



Water repellent



Oil-resistant outsole



Ergothon Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-07-15

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 7148 ZENIT EVO

COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

S3: S2 + P

WRU: Water-repellent upper

P: Penetration-resistant outsole

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

DGUV 112-191: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

Ö-Norm Z 1259: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Aluminium toecap



Nail protection in plasma-treated composite (PTC) textile



Water repellent



Oil-resistant outsole



Ergothen Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-07-15

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com