



JALAS[®] 2108 VIP SAFETY

EN ISO 20345:2011, S3, SRA, HRO

PROPERTIES Good fit, comfortable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE Safety footwear, low shoes

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Narrow/Regular

SIZE RANGE (EU) 35-48

COLLECTION VIP Collection

UPPER MATERIAL Full-grain leather

UPPER MATERIAL THICKNESS 1,5-1,7

TOECAP MATERIAL Steel

LINING MATERIAL Leather

SOLE MATERIAL Rubber outsole

INSOLE FX2 VIP Safety

INSOLE MATERIAL Leather, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron[®] XRD[®]

FASTENING Laces

COLOUR Black

EAN NO.

6408487510113 6408487510120

SIZE	ART. NO.	EAN NO.	SIZE	ART. NO.
35	2108-35	6408487509995	47	2108-47
36	2108-36	6408487510007	48	2108-48
37	2108-37	6408487510014		
38	2108-38	6408487510021		
39	2108-39	6408487510038		
40	2108-40	6408487510045		
41	2108-41	6408487510052		
42	2108-42	6408487510069		
43	2108-43	6408487510076		
44	2108-44	6408487510083		
45	2108-45	6408487510090		
46	2108-46	6408487510106		

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.





CE Steel toecap



Nail protection in plasma-treated composite (PTC) textile











ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS[®] 2108 VIP SAFETY

FEATURES

Anti-static properties, ventilating insole, water repellent leather, specially designed details, shock absorbing, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Prevents risk of:, toe injuries, nail penetration, sprain injuries, antistatic, strain injuries

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, office environments, environments with risk for outsole penetration, dry environments, clean environments

PRIMARY AREAS OF USE

Engineering, office work



EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden Phone +46 (0) 247 360 00 Fax+46(0)24736010 info@ejendals.com order@ejendals.com www.ejendals.com 2(3)





CE



The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS[®] 2108 VIP SAFETY

COMPLIANCE EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S1P: S1+P

S2: S1 + WRU

S3: S2 + P

WRU: Water-repellent upper

P: Penetration-resistant outsole

HRO: Heat-resistant outsole compound tested at 300°C

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

ESD: Electro Static Discharge

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

DGUV 112-191: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

Ö-Norm Z 1259: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden Phone +46 (0) 247 360 00 Fax +46 (0) 247 360 10 info@ejendals.com order@ejendals.com www.ejendals.com