

JALAS® 9985 EXALTER

EN ISO 20345:2011, S3, SRC, HRO

PROPERTIES

Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE Safety footwear, boots/Ankle boots

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Regular

SIZE RANGE (EU) 34-47

COLLECTION Exalter

PLATFORM Performance

UPPER MATERIAL Microfiber, Textile

UPPER MATERIAL THICKNESS 1,5-1,7

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester

SOLE MATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX3 Supreme

INSOLE MATERIAL Textile, soft EVA, rigid EVA, polyester-based conductive thread, neo foam, poron® XRD®

FASTENING BOA® Fit System

COLOUR Black, Red



EXALTER²



SIZE	ART. NO.	EAN NO.	SIZE	ART. NO.	EAN NO.
34	9985-34	6408487512001	46	9985-46	6408487512247
35	9985-35	6408487512025	47	9985-47	6408487512261
36	9985-36	6408487512049			
37	9985-37	6408487512063			
38	9985-38	6408487512087			
39	9985-39	6408487512100			
40	9985-40	6408487512124			
41	9985-41	6408487512148			
42	9985-42	6408487512162			
43	9985-43	6408487512186			
44	9985-44	6408487512209			
45	9985-45	6408487512223			

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS® 9985 EXALTER

FEATURES

Heat-resistant outsole, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, BOA® Fit System, quick-tie, stabilizator, water repellent, ergonomically shaped, soft, specially designed details, double shock absorption zones, conforms with IEC 61340-5-1 (ESD), vegan

PREVENTS RISK OF

Toe injuries, nail penetration, sprain injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, environments with risk for outsole penetration, clean environments

2(3)



Aluminium toecap



Anti-static properties



Nail protection in plasma-treated composite (PTC) textile



ESD



Heat-resistant outsole



Water repellent



Oil-resistant outsole



Ergothon Shock Absorption System



Stabilizator

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-03-19

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com



CE



Aluminium toecap



Anti-static properties



Nail protection in plasma-treated composite (PTC) textile



ESD



Heat-resistant outsole



Water repellent



Oil-resistant outsole



Ergo Shock Absorption System



Stabilizer

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-03-19

JALAS® 9985 EXALTER

COMPLIANCE

EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

S3: S2 + P

WRU: Water-repellent upper

P: Penetration-resistant outsole

HRO: Heat-resistant outsole compound tested at 300°C

A: Electrical resistance (between 0.1-1000 Mega Ohms

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

DGUV 112-191: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

Ö-Norm Z 1259: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com