

# TREKTEX S3



Standard EN ISO 20345 : 2011



## LEMAITRE

Safety since 1974



**ParaBolic®**  
Technology

### Parabolic® Outsole

- Excellent grip
- Anti-fatigue spring effect
- MSD prevention

### Membrane lining waterproof breathable

- 100% waterproof, breathable and anti-bacterial
- optimal foot breathing
- comfort improvement
- full-length shoe

Sizes 35 to 49

Ref. TREXS30BF

## Product Highlights



- All-terrain shoe available with men's and women fit.



- 2,0 mm thick high strength leather (against abrasion, tearing and puncture).

- Reinforced vamp and quarter with very few seams

- Tongue with gusset to avoid any infiltration of dust / stones.

- Back pull for easy donning.

- Memory Foam Titan insole for immediate and long-lasting comfort: antibacterial properties, respects foot hygiene



- Protective toe-cap: composite HDFC.



- Puncture-resistant midsole: high tenacity fabric "0" penetration.



## TRAIL PU2D antistatic sole

- **Protruding studs:** grip and hold on uneven ground, breaking up earth while walking.
- **Liquid and mud drainage channels** to prevent aquaplaning.
- **Parabolic® patent** with dynamic anti-fatigue effect.
- **15 mm stepped heel** for improved safety, especially on ladders.

## USE

- Public works, forestry and agriculture, green spaces, roads, networks.
- Wet environments and difficult terrain.



[lemaitre-securite.com](http://lemaitre-securite.com)

Lemaitre takes care.



# TREKTEX S3



Standard EN ISO 20345 : 2011

## Characteristics of the upper

- **Upper material:** water-repellent pull-up leather,
- **Tongue with gusset**
- **Lining:** complete waterproof-breathable membrane liner

## Characteristics of the sole

- **Designation:** TRAIL PU2D
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**  
forward flat slip: 0,40 (standard  $\geq 0,32$ )  
forward heel slip: 0,45 (standard  $\geq 0,28$ )
- **Coefficient d'adhérence SRB :**  
forward flat slip: 0,21 (standard  $\geq 0,18$ )  
forward heel slip: 0,18 (standard  $\geq 0,13$ )

## VARIANT



**Trek brun S3**  
TREKS30BFVA

## Practical information

### Women's fitting 35-39

**AET N°**  
0075/007/161/10/19/3219  
EXT 06/03/22

### Men's fitting 40-49

Weight of one shoe size 42:  
704 g

**AET N°**  
0075/007/161/10/19/3219  
EXT 07/03/22

## Packaging

### size 35 to 39

**shoobox** 355 x 290 x 130 mm

**carton** 670 x 305 x 370 mm

**5 shoeboxes per carton**

### size 40 to 49

**shoobox** 355 x 340 x 130 mm

**carton** 670 x 355 x 360 mm

**5 shoeboxes per carton**

## Gencods

<b>35</b>	3237154446355	<b>43</b>	3237154446430
<b>36</b>	3237154446362	<b>44</b>	3237154446447
<b>37</b>	3237154446379	<b>45</b>	3237154446454
<b>38</b>	3237154446386	<b>46</b>	3237154446461
<b>39</b>	3237154446393	<b>47</b>	3237154446478
<b>40</b>	3237154446409	<b>48</b>	3237154446485
<b>41</b>	3237154446416	<b>49</b>	3237154446492
<b>42</b>	3237154446423		

## Memo for basic and additional requirements of the standard EN ISO 20345: 2011

### Safety Footwear

SBP



S1



(A) (E) (Fo)

S1P



(A) (E) (Fo)

S2



(A) (E) (Fo) (Wru)

S3



(A) (E) (Fo) (Wru)



200 J toe-cap: protection of the forefoot against impact and crushing.



Anti-perforation insert 1100 N: foot protection against perforation.



Anti-static footwear



Shock absorption at the heel



Fuel oil-resistant outsole



Water penetration and water absorption resistant upper



Electrostatic discharge



Insulation against cold



Insulation against heat



Outsole resistance to hot contact



Water resistant



Ankle protection



Slip-resistance on ceramic floors with detergent



Slip-resistance on steel floors with glycerol



**SRC = SRA + SRB**

**Lemaitre Sécurité**  
17 rue de Bitschhoffen - CS 90024  
F - 67350 Val de Moder  
Tél. +33 (0)3 88 72 28 80

**lemaitre-securite.com**

**LEMAITRE**

*Safety since 1974*

Member of  
**SINAMAP**



**DON\_LS 04 TDS 0173**  
update: 20/03/24