



- Urban sport-style safety shoe incorporating **MAXI-Soft Duo™ anti-fatigue technology** designed for work stations that require standing for long periods (Upright or sustained activity).
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes **ESD Environmental Class II** tested according to **EN 61340-4-3/4-5/5-1**.
- Full-grain water-repellent leather upper with pull-up finish. Reflective insert at the heel. Colour black.
- The polyurethane toe cap, having been **SC-rated**, complies with **EN ISO 20345:2021**, which guarantees the footwear's sturdiness and longevity, as well as its increased resistance to impacts and scuffing.
- Upper lined in breathable **3D mesh** with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- Ergonomic padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- Closed by **BOA® Fit System**, delivers micro-adjustable, precision fit engineered to perform in the toughest conditions. **The BOA® Fit System** is guaranteed for the lifetime of the product on which it is integrated.
- Padded and lined textile tongue for instep protection with side bellows to keep out dust and dirt.
- Perforated insole for enhanced comfort : **MAXI-Soft Duo™** composed of a soft **BASF® Dynamic PU** midsole with heat sensitive memory foam and a maximum size **BASF® Elastopan** insert that improves weight distribution by reducing pressure points and absorbs and relieves body stress associated with a prolonged standing working position and when walking. Anatomical, breathable and fitted with the **Link ESD™** system, an innovative and seamless, multi-contact, static electricity dissipater.
- The **FLEX-SYSTEM® S-type** mounting insole **by Jallatte** is puncture-resistant to sharp objects up to **3mm in diameter (Small)** in compliance with **standard 22568-4:2021**, antistatic, **100% composite**, sewn directly onto the upper and covers **100% of the foot** for all-round protection.
- **LIGHT-PLUS®** type **B** safety toe cap made of synthetic material protecting against impacts of up to 200 J. Minimum height after test  $\geq 4\text{mm}$  in relation to the Type A toe cap in accordance with **Standard 22568-2:2019**.

**Slip resistance tests results**  
EN Standard : EN ISO 20345:2022

Sol céramique/ Laurylsulfate de sodium NaLS

- A - Heel forward **0,65** ( $>0,31$ )
- B - Forward to backward **0,64** ( $>0,36$ )

**Exigence additionnelle SR**

- Ceramic /Glycérine
- C - Heel forward **0,31** ( $>0,19$ )
- D - Forward to backward **0,38** ( $>0,22$ )

Double-density PU :

- ▶ Resistant to oils and hydrocarbons.
- ▶ Double unhooked heel with  $\geq 35$  mm camber zone and  $\geq 1.5$  mm deep transverse studs standardised **LG**.
- ▶ Heel shock absorption  $> 20$  joules.
- ▶ Maximum comfort.



Weight	Gross weight (42) : 1496 g / Net weight (42) : 1290 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	335 x 210 x 130		335 x 245 x 130	
Cartons (mm)	680 x 234 x 356	685 x 440 x 356	680 x 514 x 356	685 x 256 x 356