

PRODUCT NUMBER: 1003222 AMORSTOP - Shock-Absorbing Lanyard - 2m - w/c

> Honeywell <u>M</u>iller[®]

Q



Product Use Rope Shock-Absorbing Lanyard - 2m - Without connector

Features & Benefits

Feature

Made of a highly resistant and durable 23mm polyester webbing or 12mm Polyamid rope for increased durability.

Benefit

Adapted to harsh work conditions and difficult work environments. The lanyards offer a better comfort in case of a fall. Small size tear off dissipating element, which reduces the weight and makes the lanyard easier to handle and carry. Come with a variety of attachments and designed to better meet fall protection needs.

Technical Description

Length

2m

Weight 0.386Kg

Breaking Strength 15 KN

Operating Temperature -30°C to +50°C

Rope

Rope Raw Material Polyamide 12mm

Rope Breaking Strength > 2500 daN

Rope Standard

EN 696

Connector

Connector Type Type

Connector Raw Material Raw Material

Connector Opening
Opening

Connector Breaking Strength Breaking Strength

Connector Standard Standard

Energy Absorber

Energy Absorber Raw Material Polyester / Polyamide 30mm

Energy Absorber Breaking Strength for linked webbing : 3200 daN, for unlinked webbing : 1500 daN

Certifications

E.C. Declaration of Conformity

EC Category PPE 3

Quality Assurance ISO 9001 / 2000

EC Certificate Number 333

EC Attestation EC Attestation

EC Attestation Number 0082/042/160/08/98/0256 EXT N°01/01/99

Additional Information

User Manual NT90004208 IND L

User Information Sheet User manual

Honeywell International Inc.