


# PowerFlex® 80-813

MECHANICAL PROTECTION

 SPECIAL PURPOSE

 HEAVY

| STYLE #                                                                                    | CONSTRUCTION | GAUGE | LINER MATERIAL                       | COATING MATERIAL | FINISHING   | CUFF STYLE | COLOUR                    | EN SIZE               | LENGTH MM | PACKAGING                                       |
|--------------------------------------------------------------------------------------------|--------------|-------|--------------------------------------|------------------|-------------|------------|---------------------------|-----------------------|-----------|-------------------------------------------------|
| 80-813<br> | Knitted      | 13    | Modacrylic<br>Glass fiber<br>Kevlar® | Foam<br>neoprene | Palm coated | Knitwrist  | Black and<br>green/yellow | 6, 7, 8, 9, 10,<br>11 | 225-260   | 12 pairs in<br>a bag,<br>12 bags in<br>a carton |



## New-to-market flame resistant solution

### PRIMARY INDUSTRIES



### IDEAL APPLICATIONS

- Equipment assembly
- Replacing filters and parts
- Facility and machinery maintenance
- Pipe installation and repair
- Carpentry/scaffolding
- Heavy duty metal handling
- Heavy equipment and vehicle maintenance
- De-energized electrical wiring & clean-up

### DESCRIPTION


- First glove to combine outstanding flame resistance, high cut protection and ergonomic design.
- Materials used in the glove are inherently flame resistant, even after washing.
- Arc Flash Hazard/Risk Category 2\*: helps protect workers against arc flash hazards.
- Exclusive composite yarn provides exceptional cut resistance for safe handling of sharp objects and materials.
- Soft foam coating to ensure great flexibility and a secure grip in a variety of environments.
- Ergonomic design for superior comfort and reduced hand fatigue.

### REMARKS

- Antistatic according to EN1149
- \*\* Arc Flash – NFPA 70E - Test Method/Standard: ASTM F1959-05 - Result: Hazard/Risk Category (HRC) 2 - Arc Rating (ATPV) 12.0 cal/cm².\*

### FEATURED TECHNOLOGY

Kevlar®



**CATEGORY III**

Print date: 15-12-2015

**Ansell Healthcare Europe N.V. (European Head Office)**

Riverside Business Park, Block J

Boulevard International 55, 1070 Brussels, Belgium

Tel. +32 (0) 2 528 74 00 • Fax +32 (0) 2 528 74 01 • Fax Customer Service +32 (0) 2 528 74 03

<http://www.ansell.eu> • E-mail [info@ansell.eu](mailto:info@ansell.eu)

**Ansell**