



PRODUCT NUMBER: 1004590

ME05 - Forked Shock Absorbing Lanyard - 2m - 2xML04+CS20

Honeywell
MILLER

Overview

Reference Number

1004590

Product Type

Fall Protection

Range

Shock Absorbing Lanyards

Brand

Miller by Honeywell

Industry

- Industry
- Building and Construction

Product Use

2m forked shock absorbing webbing lanyard equipped with two 50mm opening scaffolding hooks and a karabiner

Features & Benefits

Feature

Fall arrest lanyard feature a built-in shock absorber which limits the fall arrest force in a fall situation to within 6 kN. 100% Tie off

Benefit

Lightweight & versatile fall arrest lanyard designed for maximum protection

Technical Description

Length

2m

Weight

1.500 kg

Breaking Strength

> 15 KN

Operating Temperature

-30°C to +500°C

Webbing

Webbing Raw Material

Polyester webbing 23mm

Webbing Breaking Strength

> 3000 daN

Connector

Connector Type

Typekarabiner

Connector Raw Material

Raw Materialgalvanised steel

Connector Opening

Opening17 mm

Connector Breaking Strength

Breaking Strength> 2500 daN

Connector Standard

StandardEN 362(04)

Connector

Connector Type

TypeScaff hook

Connector Raw Material

Raw Materiallight alloy

Connector Opening

Opening65 mm

Connector Breaking Strength

Breaking Strength> 2200 daN

Connector Standard

StandardEN 362(04)

Energy Absorber

Energy Absorber Raw Material

Polyester/ Polyamide 30mm

Energy Absorber Breaking Strength

for linked element: > 3200 daN,for unlinked element: > 1500 daN

Certifications

E.C. Declaration of Conformity

EC Category PPE

3

Quality Assurance

ISO 9001 / 2000

EC Certificate Number

333

EC Attestation

EC Attestation

EC Attestation Number

0082/490/160/04/00/0143

Additional Information

User Manual

NT90004208 IND L

User Information Sheet

User manual

Packaging

EAN Code

7312550045909

© Honeywell International Inc.