



PRODUCT NUMBER: 1032394
Miller kernmantel edge forked shock absorbing lanyard 1,5 meters with twist lock karabiner and 2 GO65 scaffold hooks.

Miller kernmantel edge forked shock absorbing lanyard 1,5 meters with an aluminium twist lock karabiner and 2 GO65 aluminium scaffold hooks.



Overview

Reference Number

1032394

Product Type

Fall Protection

Range

Shock Absorbing Lanyards

Line

Cut resistant

Brand

Miller by Honeywell

Industry

- Building and Construction
- Utilities

Product Use

Fall arrest lanyards will allow the worker to fall but prevents him from hitting the next lower level, such as the ground, (if well attached). It includes a shock absorber that dissipates the forces exerted on the body in the case of a fall to stay below 6 KN.

This single lanyard is edge tested for safe working on edges ($r \geq 0,5$ mm).

Features & Benefits

Feature

New design : * the new kernmantel lanyard is manufactured with a light green rope with black stripes, which are highly visible from a distance increasing the safety at work. * The stitches are highly visible which facilitates the safety check before use.

Benefit

* The lanyard is edge tested. It is manufactured with high quality kernmantel ropes and have a special cut resistance for safe working on edges ($r \geq 0,5$ mm). * The kernmantel rope is 2 times more resistant to the abrasion than the other standard ropes.

Technical Description

Length

1,5 M

Weight

1,700 KG

Breaking Strength

> 22 KN

Operating Temperature

-30°C to +50°C

Rope

Rope Raw Material

Kernmantel Ø 11 mm. Polyester sheath. Polyamide core.

Webbing

Webbing Raw Material

Resistant webbing with protective cover

Connector

Connector Type

Twist lock karabiner

Connector Raw Material

aluminium

Connector Opening

18 mm

Connector Breaking Strength

> 23 KN

Connector Standard

EN 362 : 2004

Connector

Connector Type

GO65 Scaffold hook

Connector Raw Material

aluminium

Connector Opening

63 mm

Connector Breaking Strength

> 22 KN

Connector Standard

EN 362 : 2004

Certifications

E.C. Declaration of Conformity**EC Category PPE**

3

Quality Assurance

ISO 9001 / 2000

EC Attestation

EC Attestation

EC Attestation Number

0082-490-160-06-13-0170

Certifications

- EN 355 / VG 11 PFE 11.074

REACH

EU Regulation 1907/2006 (REACH) Compliance

The substance(s) listed below may be contained in this product above the threshold level of 0.1% by weight of the listed article.

Product Reference Sold in Europe	Substance > 0.1%
Substance Name	CAS Number
No Substance Content	

Additional Information

User Manual

NT90004208 IND L

User Information Sheet

User manual

Maintenance

Life Cycle

Life expectancy of our harnesses is 10 years from the date of manufacture.

Care Instructions

Some factors can contribute to reduce the performance or life expectancy of the product:

- Incorrect stocking
- Incorrect use
- Stopping a fall
- Mechanical deformation or cut
- Contact with chemical products (an acid or a base)
- Exposure to extreme heat sources > 60°C
- Exposure to UV rays

Please remember that:

- the product must be checked at least once a year by a qualified person. This inspection must be registered.
- before each use, the product must be visually inspected by the user.

The compulsory annual inspection will be the deciding factor as to whether your PPE should be put back into service or not.