

PRODUCT NUMBER: 2049294 WELDING CUT

MIG and ARC welding in dry or light oily conditions with cut hazards.

Honeywell

Q

• Iron and steel industry

Overview	
Reference Number 2049294	
Product Type Gloves	
Range Thermal Protection	
Line Welding gloves	
Brand Honeywell	
Brand formerly known as SPERIAN	
Industry	
 Industry Automotive and Part Manufacturer Metal steel Ship Building Welding 	Building and Construction

Product Use

MIG and ARC welding in dry or light oily conditions with cut hazards.

Features & Benefits

Feature

Water repellent cowhide grain leather with back Water repellent velvet cowhide palm with palm Water repellent cowhide grain back US assembly, winged thumb with cord, Crispin type Elasticated at the back of the hand Hand fully lined with Kevlar cotton Split leather, heatproof cuff, 150 m

Benefit COMFORT

Page 1 Of 3 © Honeywell International Inc.

WELDING CUT - 2049294

The grain leather has undergone a special tanning process to make it more water repellent.

This provides outstanding comfort and flexibility.

Its US assembly, winged thumb and the flexible materials used make this glove ergonomic, thus providing the user with comfort of use.

The Kevlar® fleece lining increases the glove's comfort and thermal insulation.

SAFETY

The grain leather with its heatproof and water repellent treatment can perform welding or cutting operations in a damp environment without the entrance of humidity.

The split leather cuff helps to protect a large part of the forearm against mechanical hazards and splashes.

Technical Description

Description

CE CATEGORY : II Intermediary risks In accordance with standards : NF EN 420-03 EEC Basic standard NF EN 388-03 Mechanical risks NF EN 407-04 Thermical risks EN 12477-02 Type A Welding risks

CHARACTERISTICS :

Cowhide leather glove Gunn cut, winged thumb with yoke, gauntlet type Water-repellent velvet leather palm Water-repellent grain leather back Elasticated back Fully lined in Kevlar® cotton 150 mm heat resistant split leather cuff

Product Technology Cut and Sewn

Coating Type Leather and Kevlar®

Length 39 cm

Thickness Palm and back : 0,8/1,1 mm - Cuff : 1,1/1,3 mm

Harmlessness

In conformity with the European standards

Dexterity

Class 5

Sizes 7 to 12

EN 407 - Heat and/or Fire

Behaviour and/or fire	4
Resistance to contact heat	1
Resistance to convective heat	4
Resistance to radiant heat	Х
Resistance to small metal splashes	4
Resistance to molten metal splashes	Х

EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	3
Cutting resistance (Coupe test)	2

WELDING CUT - 2049294

Tear resistance	2
Puncture resistance	2

EN 12477

Protective gloves for welders T	Гуре А	
---------------------------------	--------	--

Packaging Label

 Tagging

 CE HONEYWELL

 2049294 XX

 EN 420

 EN 388 : 3222

 EN 407 : 413X4X

 EN 12477 : A

Certifications

E.C. Declaration of Conformity

EC Category PPE 2

EC Certificate Number 0075/797/162/10/12/0763

EC Attestation EC Attestation

EC Attestation Number 0075/797/162/10/12/0763

Additional Information

User Manual UI 111 User Information Sheet 111

Maintenance

Storage Information Minimum packaging 10 pairs. Cartons of 100 pairs.

Care Instructions In order to keep its properties, this article should not be cleaned.

© Honeywell International Inc.