



+  [View More](#)

PRODUCT NUMBER: 2091911
ELECTROSOFT CLASS 1

For electrical work with a maximal voltage of 7500 volts. Must be used with a leather overglove.

Overview

Reference Number

2091911

Product Type

Gloves

Range

Electrical Protection

Line

Latex

Brand

Sperian

Brand formerly known as

ELECTROSOFT

Industry

☒ Energy or Electricity ☒ Maintenance ☒ Telecoms

Product Use

For electrical work with a maximal voltage of 7500 volts. Must be used with a leather overglove.

Features & Benefits

Feature

Beige natural latex insulating glove
Cut edge
Category RC

Benefit**COMFORT**

Its ergonomic design combined with a lightly powdered interior increases the comfort by providing additional softness and allows the glove to be put on and taken off very easily.

RESISTANCE

The natural latex base offers high dielectric characteristics.
Its thickness (1.5mm) provides good dexterity while offering protection up to 7,500 volts.

SAFETY

Its length protects a large part of the forearm.
It must be used with a leather overglove.

Technical Description

Description

CE CATEGORY : III Irreversible risks
In accordance with standards :
EN 60903-2003
CEI 903-2002

CHARACTERISTICS :

Beige natural latex insulating glove
Cut edge
Category RC

Product Technology

Dipped Gloves

Glove/liner color

Beige

Coating Type

Latex

Length

41 cm

Thickness

1.5 mm

Harmlessness

In conformity with the European standards

Dexterity

Class 1

Sizes

8 à 11

Packaging Label**Tagging**

CE SPERIAN
2091911 XX

EN 60903-2003
CEI 903-2002

Certifications

E.C. Declaration of Conformity

EC Category PPE

3

Quality Assurance

ISO 9001 / 2000

EC Attestation

 EC Attestation

EC Attestation Number

0077/016/078/02/98/0001 - EXT 04/09/06

Photos & Images

We're sorry, there are no images available at this time.

Additional Information

User Information Sheet

106

Maintenance

Storage Information

Gloves that are used frequently should be tested at intervals less than 6 month.

Gloves that are used only occasionally should be tested after each use and, in any case, at intervals of not more than 12 months.

Gloves held in stock should be retested at intervals not exceeding 12 months.

Store in original packaging (Opaque and anti-UV packaging used for protection and instructions for use). Do not compact or fold.

Do not expose to heat sources (sunlight, radiators, artificial light). Store between 10°C and 21°C.

Inspection : Before each use, carry out a visual inspection and check the glove inflation. Any puncture or perforation makes the gloves unusable.

Precautions : Do not expose to solvents or chemicals that may cause deterioration. Do not use the glove when damp.

Cleaning : use water and soap. Dry below 65°C with ambient humidity.

Care Instructions

This article can be washed with soap and water at a temperature not exceeding 65°C.
The gloves must be dried throughly at a temperature not exceeding 65°C.