



PRODUCT NUMBER: 2299405

C&G DeepTril 5

Assembly work with high cut risks in greasy/oily environment. Outdoor handling in wet environment.

Honeywell

Overview

Reference Number

2299405

Product Type

Gloves

Range

Cut and Puncture Protection

Line

Cut resistant

Brand

Honeywell

Industry

- Industry
- Automotive and Part Manufacturer
- Building and Construction
- Logistics
- Maintenance
- Mining and Quarrying
- Offshore
- Transportation

Product Use

Assembly work with high cut risks in greasy/oily environment. Outdoor handling in wet environment.

Features & Benefits

Feature

Black HPPE/composite fiber knitted glove

Fully dipped black foam nitrile coating.

Elasticated knitted wrist.

Gauge 13.

Length : 25 cm

Benefit

COMFORT

The ergonomics seamless knit construction conforms better to the natural shape of the hand for greater strength and durability, superior comfort

The filament yarn reduce linting for the most sensitive applications and easily laundered for extended use.

The tight knit gives the glove perfect support, limits the penetration of dirt and offers a good touch.

The foam coating optimise the glove's breathability.

The nitrile foam and PVC dots on palm improves the grip.

The knitted and elasticated wrist gives the glove good support.

RESISTANCE

The nitrile foam coating provides outstanding abrasion resistance and good protection in light oily environment.

HPPE mixed with composite fiber provides very high resistance to cut.

HYGIENE

The black colour is suitable for work in a soiled atmosphere.

Technical Description

Description

CE CATEGORY : II Intermediary risks

In accordance with standards :

EN 420-2003 Basic standards

EN 388-2016 Mechanical hazards

CHARACTERISTICS :

Black HPPE/composite fiber knitted glove

Fully dipped black foam nitrile coating.

Elasticated knitted wrist.

Gauge 13.

Length : 25 cm

Product Technology

Knitted Coated

Gauge

13

Glove/liner color

Black

Coating Type

nitrile foam

Coating Color

Black

Length

25 cm

Harmlessness

In conformity with the European standards

Dexterity

Class 5

Sizes

7 to 11

EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	4
Cutting resistance (Coupe test)	X
Tear resistance	4
Puncture resistance	2
Cutting resistance (TDM test)	C

Certifications

E.C. Declaration of Conformity

EC Category PPE

2

Quality Assurance

ISO 9001 / 2000

EC Certificate Number

0075/797/162/05/18/0791 EXT 02/05/18

EC Attestation

CE Certificate

Additional Information

User Manual

UI 202

Maintenance

Storage Information

Minimum packaging : 10 pairs.

Cartons of 100 pairs.

Care Instructions

This article can be cleaned. For cleaning instructions, please contact Honeywell Safety Products.